





# SOLID STATE AUTOMATIC AM-FM STEREO RECEIVER

# TK-88



## SPECIFICATIONS

### AMPLIFIER SECTION:

**TOTAL MUSIC POWER:**

100 watts (IHF Standard 4 ohms)

90 watts (IHF Standard 8 ohms)

**CONTINUOUS POWER:**

32 watts per channel (0.5% T.H.D.)

**FREQUENCY RESPONSE:**

20 Hz — 50,000 Hz ( $\pm 2$  dB)

**POWER BANDWIDTH:**

20 Hz — 30,000 Hz ( $-3$  dB)

**SIGNAL TO NOISE RATIO:**

Phono — 63 dB, Tape HD — 63 dB, AUX — 70 dB

**INPUT SENSITIVITY:**

Phono 2 mV, Tape HD 2.5 mV, AUX 150 mV

**MAXIMUM INPUT SIGNAL:**  
(Mag. Input)

100 mV P-P (1,000 Hz)

**DAMPING FACTOR:**

46 (16 ohms), 23 (8 ohms)

**LOW FILTER:**

80 Hz roll-off

**HIGH FILTER:**

6,000 Hz roll-off

**$\pm 10$  dB (at 50 Hz)**

$\pm 10$  dB (at 10,000 Hz)

**SIGNAL TO NOISE RATIO:**

(below rated output)

**INPUT SENSITIVITY:**

Phono 2 mV, Tape HD 2.5 mV, AUX 150 mV

**MAXIMUM INPUT SIGNAL:**

100 mV P-P (1,000 Hz)

**DAMPING FACTOR:**

46 (16 ohms), 23 (8 ohms)

**LOW FILTER:**

80 Hz roll-off

**HIGH FILTER:**

6,000 Hz roll-off

**$\pm 10$  dB (at 50 Hz)**

$\pm 10$  dB (at 10,000 Hz)

**SIGNAL TO NOISE RATIO:**

(below rated output)

**INPUT SENSITIVITY:**

Phono 2 mV, Tape HD 2.5 mV, AUX 150 mV

**MAXIMUM INPUT SIGNAL:**

100 mV P-P (1,000 Hz)

**DAMPING FACTOR:**

46 (16 ohms), 23 (8 ohms)

**LOW FILTER:**

80 Hz roll-off

**HIGH FILTER:**

6,000 Hz roll-off

**$\pm 10$  dB (at 50 Hz)**

$\pm 10$  dB (at 10,000 Hz)

**SIGNAL TO NOISE RATIO:**

(below rated output)

**INPUT SENSITIVITY:**

Phono 2 mV, Tape HD 2.5 mV, AUX 150 mV

**MAXIMUM INPUT SIGNAL:**

100 mV P-P (1,000 Hz)

**DAMPING FACTOR:**

46 (16 ohms), 23 (8 ohms)

**LOW FILTER:**

80 Hz roll-off

**HIGH FILTER:**

6,000 Hz roll-off

**$\pm 10$  dB (at 50 Hz)**

$\pm 10$  dB (at 10,000 Hz)

**SIGNAL TO NOISE RATIO:**

(below rated output)

**INPUT SENSITIVITY:**

Phono 2 mV, Tape HD 2.5 mV, AUX 150 mV

**MAXIMUM INPUT SIGNAL:**

100 mV P-P (1,000 Hz)

**DAMPING FACTOR:**

46 (16 ohms), 23 (8 ohms)

**LOW FILTER:**

80 Hz roll-off

**HIGH FILTER:**

6,000 Hz roll-off

**$\pm 10$  dB (at 50 Hz)**

$\pm 10$  dB (at 10,000 Hz)

**SIGNAL TO NOISE RATIO:**

(below rated output)

**INPUT SENSITIVITY:**

Phono 2 mV, Tape HD 2.5 mV, AUX 150 mV

**MAXIMUM INPUT SIGNAL:**

100 mV P-P (1,000 Hz)

**DAMPING FACTOR:**

46 (16 ohms), 23 (8 ohms)

**LOW FILTER:**

80 Hz roll-off

**HIGH FILTER:**

6,000 Hz roll-off

**$\pm 10$  dB (at 50 Hz)**

$\pm 10$  dB (at 10,000 Hz)

**SIGNAL TO NOISE RATIO:**

(below rated output)

**INPUT SENSITIVITY:**

Phono 2 mV, Tape HD 2.5 mV, AUX 150 mV

**MAXIMUM INPUT SIGNAL:**

100 mV P-P (1,000 Hz)

**DAMPING FACTOR:**

46 (16 ohms), 23 (8 ohms)

**LOW FILTER:**

80 Hz roll-off

**HIGH FILTER:**

6,000 Hz roll-off

**$\pm 10$  dB (at 50 Hz)**

$\pm 10$  dB (at 10,000 Hz)

**SIGNAL TO NOISE RATIO:**

(below rated output)

**INPUT SENSITIVITY:**

Phono 2 mV, Tape HD 2.5 mV, AUX 150 mV

**MAXIMUM INPUT SIGNAL:**

100 mV P-P (1,000 Hz)

**DAMPING FACTOR:**

46 (16 ohms), 23 (8 ohms)

**LOW FILTER:**

80 Hz roll-off

**HIGH FILTER:**

6,000 Hz roll-off

**$\pm 10$  dB (at 50 Hz)**

$\pm 10$  dB (at 10,000 Hz)

**SIGNAL TO NOISE RATIO:**

(below rated output)

**INPUT SENSITIVITY:**

Phono 2 mV, Tape HD 2.5 mV, AUX 150 mV

**MAXIMUM INPUT SIGNAL:**

100 mV P-P (1,000 Hz)

**DAMPING FACTOR:**

46 (16 ohms), 23 (8 ohms)

**LOW FILTER:**

80 Hz roll-off

**HIGH FILTER:**

6,000 Hz roll-off

**$\pm 10$  dB (at 50 Hz)**

$\pm 10$  dB (at 10,000 Hz)

**SIGNAL TO NOISE RATIO:**

(below rated output)

**INPUT SENSITIVITY:**

Phono 2 mV, Tape HD 2.5 mV, AUX 150 mV

**MAXIMUM INPUT SIGNAL:**

100 mV P-P (1,000 Hz)

**DAMPING FACTOR:**

46 (16 ohms), 23 (8 ohms)

**LOW FILTER:**

80 Hz roll-off

**HIGH FILTER:**

6,000 Hz roll-off

**$\pm 10$  dB (at 50 Hz)**

$\pm 10$  dB (at 10,000 Hz)

**SIGNAL TO NOISE RATIO:**

(below rated output)

**INPUT SENSITIVITY:**

