


# Service Manual

CD Changer

Compact Disc Changer


**MASH**<sup>\*</sup>  
multi-stage noise shaping
\* MASH is a trademark of NTT.


Because of unique interconnecting cables, when a component requires service, send or bring in the entire system.

**Colour**

(N) ..... Gold Type

**Area**

E ..... Europe.

**System: SC-HD70****RAE0161Z Mechanism Series****Specifications****Audio**DA converter: 1 bit 2 DAC MASH<sup>\*\*</sup>**General**

Dimensions : 196(Wide)/ 67(High)/ 229(Depth) mm

Weight: 1.7 kg

**Pickup**

Wavelength: 780 nm

**Notes:**

1. Weight and dimensions shown are approximate.
2. Design and specifications are subject to change without notice.

System	Tuner	CD Changer	Amplifier	Cassette deck	Speakers
SC-HD70	ST-HD70	SL-HD70	SE-HD70	RS-HD70	*SB-HD70

\* Made in PAES

**WARNING**

This service information is designed for experienced repair technicians only and is not designed for use by the general public. It does not contain warnings or cautions to advise non-technical individuals of potential dangers in attempting to service a product. Products powered by electricity should be serviced or repaired only by experienced professional technicians. Any attempt to service or repair the product or products dealt with in this service information by anyone else could result in serious injury or death.

# Technics<sup>®</sup>

© 1996 Matsushita Electric Industrial Co., Ltd.  
 All rights reserved. Unauthorized copying and distribution is a violation of law.

## Contents

	Page	Pa
Precaution of Laser Diode .....	2	
Location of Control .....	3	
Handling Precautions for Traverse Deck .....	3	
Operation Checks and Main Component		
Replacement Procedures .....	4~24	
Replacement of the Foot .....	24	
Error Code Display and Servo Adjustment Function .....	25, 26	
Measurements and Adjustments .....	27	
Block Diagram .....	28~31	
Wiring Connection Diagram .....	32	
Schematic Diagram .....	33~37	
Printed Circuit Board Diagram .....	38,	
Terminal Guide .....	40~	
Replacement Parts List (Electrical) .....		
Resistors and Capacitors .....	47,	
Replacement Parts List (Cabinet) .....		
Cabinet Parts Location .....		
Loading Mechanism Parts Location .....		
Replacement Parts List (Loading Mechanism) .....		
Replacement Parts List		
(Packing Material / Test Disc / Service Kit) .....		
Packaging .....		

## NOTES:

- Refer to the service manual for Model No. ST-HD70 (ORDER No. AD9610197C2) for information on "Installation" and "Connections".
- Refer to the service manual for Model No. SE-HD70 (ORDER No. AD9610196A2) for information on "Accessories".

## Precaution of Laser Diode

**CAUTION:** This product utilizes a laser diode with the unit turned "on", invisible laser radiation is emitted from the pick lens.

Wave length: 780 nm

Maximum output radiation power from pickup: 100 µW/VDE

Laser radiation from the pickup lens is safety level, but be sure the followings:

1. Do not disassemble the optical pickup unit, since radiation from exposed laser diode is dangerous.
2. Do not adjust the variable resistor on the pickup unit. It was already adjusted.
3. Do not look at the focus lens using optical instruments.
4. Recommend not to look at pickup lens for a long time.

**ACHTUNG:** Dieses Produkt enthält eine Laserdiode. Im eingeschalteten Zustand wird unsichtbare Leserstrahlung von der Lasereinheit abgestrahlt.


Wellenlänge: 780 nm

Maximale Strahlungsleistung der Lasereinheit: 100 µW/VDE


Die Strahlung an der Lasereinheit ist ungefährlich, wenn folgende Punkte beachtet werden:

1. Die Lasereinheit nicht zerlegen, da die Strahlung an der freigelegten Laserdiode gefährlich ist.
2. Den werkseitig justierten Einstellregler der Lasereinheit nicht verstellen.
3. Nicht mit optischen Instrumenten in die Fokussierlinien blicken.
4. Nicht über längere Zeit in die Fokussierlinien blicken.

Back side



Upper side



DANGER	INVISIBLE LASER RADIATION WHEN OPEN AVOID DIRECT EXPOSURE TO BEAM.
ADVARSEL	USYNLIG LASERSTRÅLING VED ÅBNING. NÅR SIKKERHEDSÅBRYDERE ER UDE AF FUNKTION. UNDÅD UDSETTELSE FOR STRÅLING.
VARO!	AVATTAMASSA JA SISÄÄLÄKUTUS OHTEESSA OLET ALTTIMA NÄKYMÄTÖNÄ LASERSTRÄNLINJILLE. ÄLÄ KATSO SÄTEESEEN.
VARNING	OSYNLIG LASERSTRÅLNING NÄR DENNA DEL ÄR ÖPPNAD OCH SPÄRREN ÄR URKOPPLAD. DRAKTA EJ STRÅLEN.
ADVARSEL	USYNLIG LASERSTRÅLING NÄR DEKSEL ÅPNES OG SIKKERHEDSÅS BRYTES. UNDGA UDSETNING FOR STRÅLEN.
VORSICHT	UNSICHTBARE LASERSTRÄHLUNG, WENN ABDECKUNG GEÖFFNET. NICHT DEM STRAHN AUSSETZEN.


LUOKAN 1 LASERLAITE  
KLASS 1 LASER APPARAT

**CAUTION!**

THIS PRODUCT UTILIZES A LASER.

USE OF CONTROLS OR ADJUSTMENTS OR PERFORMANCE OF PROCEDURES OTHER THAN  
THOSE SPECIFIED HEREIN MAY RESULT IN HAZARDOUS RADIATION EXPOSURE.

## ■ Location of Control



- ① Disc select buttons and indicators (DISC)
- ② Disc tray
- ③ Disc tray open/close button (▲ OPEN/CLOSE)
- ④ Random play button (RANDOM)
- ⑤ Repeat button (REPEAT)
- ⑥ AI edit button (AI EDIT)
- ⑦ Skip/search buttons (◀◀ / ◀◀, ▶▶ / ▶▶)
- ⑧ Stop button (■)
- ⑨ Pause button (■■)
- ⑩ Play button and indicator (▶)


## ■ Handling Precautions for Traverse Deck

The laser diode in the traverse deck (optical pickup) may break down due to potential difference caused by static electricity of clothes or human body.

So, be careful of electrostatic breakdown during repair of the traverse deck (optical pickup).

### ● Handling of traverse deck (optical pickup)

1. Do not subject the traverse deck (optical pickup) to static electricity as it is extremely sensitive to electrical shock.
2. The short land between the No. ⑫ (GND) and No. ⑬ (LD) pins on the flexible board is shorted with a solder build-up to prevent damage to the laser diode.  
To connect to the PC board, be sure to open by removing the solder build-up, and finish the work quickly.
3. Take care not to apply excessive stress to the flexible board (FFC).
4. Do not turn the variable resistor (laser power adjustment). It has already been adjusted.



### ● Grounding for electrostatic breakdown prevention

#### 1. Human body grounding


Use the anti-static wrist strap to discharge the static electricity from your body.

#### 2. Work table grounding

Put a conductive material (sheet) or steel sheet on the area where the optical pickup is placed, and ground the sheet.

#### Caution:

The static electricity of your clothes will not be grounded through the wrist strap. So, take care not to let your clothes touch the traverse deck (optical pickup).



## ■ Operation Checks and Main Component Replacement Procedures

- NOTE**
1. This section describes procedures for checking the operation of the major printed circuit boards and replacing the main components.
  2. For reassembly after operation checks or replacement, reverse the respective procedures. Special reassembly procedures are described only when required.
  3. Select items from the following index when checks or replacement are required.
  4. Refer the parts No. on the page of "Main Component Replacement Procedures", if necessary.



### • Contents

• Checking Procedures for each P.C.B.	page.
1. Checking for the main P.C.B. and operation P.C.B. ....	5~8.
2. Checking for the traverse deck separated from the loading unit. ....	9.
• Main Component Replacement Procedures	
1. Replacement for the traverse deck and spindle motor ass'y. ....	10,11.
2. Replacement for the loading motor. ....	11,12.
• Loading unit component disassembly/reassembly	
1. Loading unit component disassembly. ....	12~16.
2. Loading unit component reassembly. ....	17~23.
3. Manual operation check of loading components. ....	23,24.

## ■ Preparation


- For checking the P.C.B., following service kit should be prepared.

- Service kit No. RFKZ0078**
  - Extension cable × 3
  - Spacer for traverse deck
  - Clamper
  - Mechanism stand leg




## ■ Checking procedures for each P.C.B.

### Checking for the main P.C.B. and operation P.C.B.




Step 1 Remove the 4 screws (a).



Step 2 Remove the side panel (L),(R).

- Spread the lower part of the side panels in the direction of arrow (→①) to release the ribs, and then lift to remove the side panels (→②).




Step 3 Remove the 1 screw (b).

Step 4 Remove the cabinet.

Step 5 Remove the 2 screws (c).


Step 6 Pull out the front panel ass'y.




- Step 7** Remove the insulation sheet.
- Step 8** Release the claw, and then remove the sensor P.C.B..
- Step 9** Remove the 4 screws (d).
- Step 10** Release the 2 claws, and then remove the rear panel.
- Step 11** Remove the 2 screws (e).
- Step 12** Remove the mechanism spacer (C).
- Step 13** Remove the 4 screws (f).


- Step 14** Lift up the loading unit, and then remove the FFC.

**NOTE**  
Install a short pin into the optical pickup FFC.




#### Removal of the FFC






**Step 15** Remove the 6 screws (g, h).

**Step 16** Remove the main P.C.B..



**Step 17** Remove the 4 screws (i).

**Step 18** Release the 2 claws, and then remove the operation P.C.B..




**Step 19** Remove the 4 screws (i).

**Step 20** Remove the mechanism spacer (L), mechanism spacer (R), floating spring (A) and floating spring (B).


**NOTE**

- Take care not lose the floating spring (A) and (B).




## Checking for the traverse deck separated from the loading unit.

Follow the traverse deck replacing procedures  
 ( Step 1 ~ Step 5 ) on the main components  
 replacement procedures. (See pages 10 and 11.)



**Step 1** Install the spacers (3 points) to the traverse deck.




**Step 4** Connect the lead wire between the GND plate and bottom chassis ass'y.

Check the main P.C.B. and operation P.C.B.  
 as shown left.

## ■ Main Component Replacement Procedures



### Replacement for the traverse deck and spindle motor ass'y.

Follow the items ( **Step 1** ~ **Step 5** ) of main P.C.B. checking. (See page 5.)




**Step 1**

Rotate the elevation cam in the direction of arrow (counterclockwise), and then rise the elevation block ass'y.



**Step 2**

Remove the 2 screws (a) and 2 washers.




**Step 3**

Release the hook of traverse deck.

**Step 4**

Release the cam slot of traverse deck from the clamp rack plate shaft.



## Step 5

Release the traverse deck shaft from the slot, and then remove the traverse deck.

## NOTE

Take care not to damage the FFC.


## Step 6

Remove the 2 screws (b).

## Step 7


Detach the connector, and then remove the spindle motor ass'y.

## Remove of the connector



## Replacement for the loading motor.

Follow the items (Step 1 ~ Step 5) of main P.C.B. checking. (See page 5.)




## Step 1

Remove the 2 screws (a).

## Step 2

Lift the motor angle in the direction of arrow ①, and then remove it with pushing in the direction of arrow ②.




**Step 3** Remove the 2 screws (b).

**Step 4** Remove the motor angle.


**Step 5** Unsolder the motor terminals (2 points).

## ■ Loading unit component disassembly/reassembly

### Loading unit component disassembly




**Step 1** Remove the tray ornament ass'y in the direction of arrow.




**Step 2** Remove the 2 screws (a).

**Step 3** Lift the mechanism chassis bracket ass'y in the direction of arrow ①, and then remove it in the direction of arrow ②.



**Step 4** Move the step cam (L) ass'y in the direction of arrow ①, and then align it with the slots.

**Step 5** Remove the step cam (L) ass'y in the direction of arrow ②.




**Step 6** Rotate the conversion reduction gear (A) in the direction of arrow (clockwise).

**Step 7** Slide the tray base toward the front, then, pull the tray unit fully.

**Step 8** Remove the disc stopper.


**Step 9** Remove the 3 screws (b).

**Step 10** Release the 3 claws, and then remove the gear cover.




**Step 11** Remove the washer and load main gear.

**Step 12** Release the 1 claw, and then pull the tray unit.




**Step 14** Remove the elevation cam.

**Step 15** Slide the step cam (R) ass'y in the direction of arrow ① and align it with the slots, then remove the step cam (R) ass'y in the direction of arrow ②.



**Step 16** Remove the 1 screw (c).


**Step 17** Remove the washer and the elevation gear holder.



**Step 18** Lift the elevation block ass'y in the direction of arrow ①, and then remove it in the direction of arrow ②.


**NOTE**

Take care not to bend or damage the FFC.



**Step 19** Remove the 2 screws (d) and 2 washers.

**Step 20** Remove the traverse deck.




## Step 21

Remove the elevation gear, elevation transmission gear and S tray gear (C).


### ■ Removal of the elevation transmission gear

- Release the 2 claws.



## Step 22

Remove the gears, lever, spring and etc, as shown below.




### ■ Removal of the plunger

Remove the 1 screw (e).


Unsolder the plunger lead wires (2 points) on the back side of mechanism chassis ass'y.

## Loading unit component reassembly.



Step 1

Install the gears and levers as shown left.



Step 2

Install the mode control spring to the boss A, and then align the portion **a** of spring with the slot. (Refer to figure 1)

Step 3

Install the conversion cam to the boss B, and then install the washer. (Refer to figure 1)

### NOTE

Set the conversion cam so that the round slot is located at direction A. (Refer to figure 2)

Step 4

Install the mode control lever to the boss A. (Refer to figure 1)

### NOTE

Align the portion **b** of mode control spring with the hook of mode control lever. (Refer to figure 1)




Figure 1







Figure 2



**Step 5** Align the bent of movable core with the portion **c** of mode control lever.


**Step 6** Install the plunger, and then tighten the screw **(a)**.



**Step 7** Install the traverse deck to the elevation base ass'y.

- ① Align the shaft of traverse deck with the slot.
- ② Align the cam slot of traverse deck with the clamp rack plate shaft.
- ③ Align the hook of traverse deck with the lower side of slot.

**Step 8** Fix with 2 screws **(b)** and 2 washers.




**Step 9** Install the elevation block to the mechanism chassis ass'y.

**NOTE**

When inserting, take care to interfere the elevation semicircular plate ass'y with the elevation gear. (Engage the tooth of gear.)

**NOTE**

Do not pinch the FFC.

**Step 10** Install the elevation gear holder.

- Assure the claw is latched.


**Step 11** Install the washer, and then tighten screw (C).**• Phase Adjustment**

Figure 1

- Locate the draw lever in the direction of arrow. (Refer to figure 1.)
- Engage the claw of mode lock lever with the tooth of S tray gear (A). (Refer to figure 2.)
- After engagement, the play of draw lever must be less than 1mm.
- If the play is more than 1mm, unlock the draw lever. Then, rotate the S tray gear (A) in the direction of arrow with lifting a small amount and engage the mode lock lever with the block. (Refer to figure 2.)
- Depending on the engagement above, select the appropriate position.

**NOTE**

Take care to engage the tooth of gear. (Refer to figure 3.)




Figure 2





Figure 3




## Step 12

Align the slots of step cam (R) ass'y with the hooks of mechanism chassis ass'y, and then install the step cam (R) ass'y.


## NOTE

The rib of step cam (R) ass'y should be inserted in U-type slot of elevation lever.



## Step 13

Align the hole of elevation cam with the elevation lever pin, and then insert the elevation cam into the boss.




## Step 14


Align the cam slot of load main gear with the pin of mode lock lever, and then insert the load main gear into the boss.

## Step 15

Install the washer.

- Align the marking of load main gear with that of mechanism chassis. (Refer to figure below.)





**Step 16** Install the gear cover.

**NOTE**

The claws (2 points) must be latched.



**Step 17** Tighten the screws (d).

**Step 18** Install the M tray gear.

**NOTE**

Mate the marking toward the front side.  
(Refer to figure below.)


M tray gear





**Step 19** Align the slots of step cam (L) ass'y with the hooks of mechanism chassis ass'y, and then install the step cam (L) ass'y.

**NOTE**


When installing the step cam (L) ass'y to the mechanism chassis ass'y, install it with pressing the switch boss in the direction of arrow.



**Step 20** Temporarily install the stopper spring on the hook of disc stopper.



**Step 21** Align the boss of disc stopper with the hole of mechanism chassis ass'y.



## Step 22

Install the slot of mechanism chassis bracket ass'y into the rib of mechanism chassis ass'y, and then install the mechanism chassis bracket ass'y.

## Step 23

Align the connecting link plate with the boss A of step cam (R) ass'y and boss B of step cam (L) ass'y.

## Step 24

Tighten the screws (e).

## Step 25


Secure the stopper spring temporarily installed with disc stopper.

## Step 26

Align the groove of tray unit with the projection of mechanism chassis ass'y, and then insert the tray unit.


## NOTE

After installing the tray unit, make sure that the 5 sub tray bases are located in the direction of arrow A.




Step 27

Rotate the elevation cam in the direction of arrow (counterclockwise), and then rise the elevation block ass'y.



[Bottom side]






Step 28

Push the tray unit.

Loading components assembling complete

### Manual operation check of loading components.

#### 1. Elevation block operation.




Elevation cam

Elevation block ass'y


Rotate counterclockwise : Up ward  
Rotate clockwise : Down ward

## 2. Main tray and sub tray operation



## ■ Replacement of the Foot

1. Remove the 4 heat melted posts on the Bottom board ass'y with a pair of nippers or similar tool.
2. To replace the foot (RKA0076-N) on the Bottom board ass'y melt the 4 posts with a soldering iron or install it with a screw (XTB3+6J).



## ■ Error Code Display and Servo Adjustment Function


This unit has an error code display function, so that if the unit operates incorrectly, the fault is displayed using an error code on the FL display of the tuner (ST-HD70). It also has a servo adjustment function for displaying the status of servo system functions (focus, tracking, CLV) on the tuner's FL display.

The system control IC and FL display are part of the tuner so make sure the system has been connected properly before using these functions. (This unit can be operated independently, although the error code display and servo adjustment functions cannot be used.)

Use these two functions for guidance during fault diagnosis and repair.

**Note:** Check beforehand for scratching or soiling of the test disc (SZZP1054C), and soiling or other problems with the optical pickup lens.

### ● Error code display and adjustment procedure












### ● Table 1

FL display	Symptom	Cause
H - 15	When CD tray opens, it closes by itself.	Disc tray "Open" detection sensor (Z3) fault.
H - 16	When CD tray closes, it opens by itself	Disc tray "Closed" detection sensor (Z2) fault.
F - 15	Does not play, even when CD play button is pressed.	Pickup rest position detection switch fault.
F - 17	The tray opens.	Traverse deck DOWN detection switch (S1) fault.
F - 26	Does not move even when ▶ (PLAY) is pressed.	System control or servo processor IC (IC401, IC501) fault.
F-27	The selected disc tray does not open.	Positioning detection sensor (Z1) fault.
F-30	The unit try to play without a disc.	Disc IN/OUT detection sensor (Q691, D691) fault.

●Table 2

※ The unit is satisfactory if the error code is **E - 00** or **E - 02**

※ Before testing, check that the test disc is free of scratches and optical pickup is clean.

FL error code display	Symptom	Probable cause	Signal to check		Normal voltage and waveform values	
			Signal name	Location	PLAY	STOP
E - 01	Focus and tracking offset adjustments not completed in the specified time period.	1. Clocks X1 and X2, power supply $V_{DD}$ and reset/RST, all on IC401. 2. MDATA, MCLK, MLD and SENSE signal to/from mechanism controller.	MDATA	IC401 ⑧ pin		0V
			MCLK	IC401 ⑦ pin		4.9V
			MLD	IC401 ⑨ pin		4.9V
			SENSE	IC401 ⑩ pin	—	—
			/RST	IC401 ⑯ pin	4.8V	4.8V
			X1	IC401 ⑦ pin		0.35Vp-p
			X2	IC401 ⑧ pin		0.58Vp-p
E - 03 E - 05 E - 07 E - 09 E - 0B E - 0D E - 0F	Disc play unstable.	1. Scratches or contaminants on disc surface. 2. Focus and tracking servo circuits (check waveforms, voltages, and part values.) 3. Spindle driver circuit. 4. Optical pickup.	FE	IC401 ⑪ pin		2.4V
			TE	IC401 ⑫ pin		2.4V
			FOD	IC401 ⑬ pin	2.4V	2.4V
			TRD	IC401 ⑭ pin	2.4V	2.4V
			KICK	IC401 ⑮ pin	2.4V	2.4V
			/FLOCK	IC401 ⑯ pin	—	—
			/RF DET	IC401 ⑰ pin	0V	4.8V
			RF	IC401 ⑲ pin		2.4V
			STAT	IC401 ⑳ pin	4.8V	0V
			FBAL	IC401 ⑳ pin	2.4V	2.4V
E - 04 E - 06 E - 0C E - 0E	Best "Eye" (PD Balance) adjustment not completed in the specified time period.	1. Scratches or contaminants on disc surface. 2. Focus and Tracking servo circuit (check waveforms, voltages, and part values.) 3. Optical pickup.	RF	IC401 ⑳ pin		2.4V
			FE	IC401 ⑪ pin		2.4V
			/TLOCK	IC401 ⑫ pin	—	—
			OFT	IC401 ⑮ pin	0V	0V
			FE	IC401 ⑪ pin		2.4V
E - 08 E - 0A	Focus or Tracking gain adjustment not completed in the specified time period.	1. Scratches or contaminants on disc surface. 2. Focus and Tracking servo circuit (check waveforms, voltages, and part values.) 3. Optical pickup.	TE	IC401 ⑫ pin		2.4V
			/TLOCK	IC401 ⑫ pin	—	—
			OFT	IC401 ⑮ pin	0V	0V

## ■ Measurements and Adjustments

### Cautions:

- It is very dangerous to look at or touch the laser beam. (Laser radiation is invisible.)  
With the unit turned "on", laser radiation is emitted from the pickup lens.
- Avoid exposure to the laser beam, especially when performing adjustments.

This unit SL-HD70 is designed to operate on power supplied from the Amplifier SE-HD70 through the Tuner ST-HD70. When connecting the unit to other system components, do not connect to the Amplifier SE-HD70 directly. Be sure to connect this unit through the Tuner ST-HD70. When operating the unit SL-HD70 alone for testing and servicing, without having power supplied from the Amplifier SE-HD70, use the following method.

### Power Supply to This Unit alone

Apply 11V AC power to the section between **AC IN** of the coil (L101) and the jumper (J253) **GND** as well as the section between **AC IN** of the coil (L102) and the jumper (J101) **GND**. (Shown in Fig. 1)

### To Check Signals

Connect the oscilloscope or the speaker with built-in amplifier to the section between LINE OUT (Lch) of the resistor R127 and the **GND** point of the jumper (J101) as well as the section between LINE OUT (R ch) of the resistor R126 and the **GND** point of the jumper (J253) and check if the signals are outputting from this unit. (Shown in Fig. 1)






Fig. 1


## ■ Block Diagram




- Signal line  : CD signal




● Signal line → : CD signal





## ■Wiring Connection Diagram



## ■ Schematic Diagram (Parts list on pages 46~48.)

- This schematic diagram may be modified at any time with the development of new technology.

	Page
<b>A PHOTO TR CIRCUIT</b>	34
<b>B MAIN CIRCUIT</b>	34~37
<b>C SENSOR CIRCUIT</b>	34
<b>D OPERATION CIRCUIT</b>	36
















### Notes:

- S1** : Mechanism position detect switch.
- S201**: Disc select (DISC1) switch.
- S202**: Disc select (DISC2) switch.
- S203**: Disc select (DISC3) switch.
- S204**: Disc select (DISC4) switch.
- S205**: Disc select (DISC5) switch.
- S206**: Disc tray open/close (▲ OPEN/CLOSE) switch.
- S207**: Play (▶) switch.
- S208**: Pause (■) switch.
- S209**: Stop (■) switch.
- S210**: F. skip/ search (▶▶ / ▶▶) switch
- S211**: R. skip/ search (◀◀ / ◀◀) switch.
- S212**: AI edit switch (AI EDIT)
- S213**: Repeat switch (REPEAT)
- S214**: Random play switch (RANDOM)
- Indicated voltage values are the standard values for the unit measured by the DC electronic circuit tester (high-impedance) with the chassis taken as standard. Therefore, there may exist some errors in the voltage values, depending on the internal impedance of the DC circuit tester.

No mark: CD STOP

( ) : CD play [1kHz, L+R, 0dB]

### ● Terminal guide of IC's, transistors and diodes

 <table border="1"> <tr><td>AN8387SE2</td><td>20PIN</td></tr> <tr><td>AN8355SBE1</td><td>28PIN</td></tr> <tr><td>MN6475A-T1</td><td>24PIN</td></tr> <tr><td>NJM2115MTE1</td><td>8PIN</td></tr> <tr><td>NJU3713GTE1</td><td>18PIN</td></tr> </table>		AN8387SE2	20PIN	AN8355SBE1	28PIN	MN6475A-T1	24PIN	NJM2115MTE1	8PIN	NJU3713GTE1	18PIN				
AN8387SE2	20PIN														
AN8355SBE1	28PIN														
MN6475A-T1	24PIN														
NJM2115MTE1	8PIN														
NJU3713GTE1	18PIN														
MN662743CDC1															
															
MA8056MTX MA8075MTX															

- Important safety notice:**  
Components identified by  mark have special characteristics important for safety. Furthermore, special parts which have purpose of fire-retardant (resistors), high-quality sound (capacitors), low-noise (resistors), etc. are used. When replacing any of components, be sure to use only manufacturer's specified parts shown in the parts list.
- The supply part number is described alone in the replacement parts.


Parts No.	Production Part No.	Supply Part No.
IC101	LM2940T5M	LM2940T5
IC603	NJM2115MTE1	NJM2115MT1

- Caution !**  
IC and LSI are sensitive to static electricity. Secondary trouble can be prevented by taking care during repair. Cover the parts boxes made of plastics with aluminum foil. Ground the soldering iron. Put a conductive mat on the work table. Do not touch the legs of IC or LSI with the fingers directly.


### ● Voltage and signal line

 : Positive voltage line    : Negative voltage line  
 : CD signal


## **A** PHOTO TR CIRCUIT (P.C. Board: on page 39)




**B MAIN CIRCUIT (P.C. Board: on page 38)**



## **C** SENSOR CIRCUIT (P.C. Board: on page 39)






**TRAVERSE MOTOR  
SPINDLE MOTOR  
REST SWITCH  
CIRCUIT**




● Signal line → : CD signal


△ OPTICAL PICKUP CIRCUIT



## B MAIN CIRCUIT (P.C. Board: on page 38)







• Signal line → : CD signal



## ■ Printed Circuit Board Diagram

- This printed circuit board diagram may be modified at any time with the development of new technology.



**A PHOTO P.C.B.****D OPERATION P.C.B.****C SENSOR P.C.B.**

## ■ Terminal Guide

### • IC301 (LC66538A4J35): SYSTEM CONTROL

Pin No.	Mark	I/O Division	Function
1	TEST1	I	Test terminal
2	Vss	—	GND terminal
3	OSC1	I	Crystal OSC terminal (f=4.2336MHz)
4	OSC2	O	
5	VDD	I	Power supply input terminal
6	/RST	I	Reset signal input terminal
7	DISK	O	Disc detect input terminal
8	TRTIME	I	Time constant input terminal
9	TEST	I	Test terminal
10	HOLD	I	Not used, connected to VDD
11	LCLR	O	Clear output terminal
12	PLUNGER	O	Plunger(solenoid) control output terminal
13	SVRST	O	Reset signal output terminal
14	DACRST	O	Reset signal output terminal
15	HALF	O	Loading motor control output terminal
16	HALF2	O	Loading motor control output terminal (Not used, open)
17	CS	O	Communication chip select signal output terminal
18	REQ	I	Communication request signal input terminal
19	DTI	I	Communication data signal input/output terminal
20	DTO	O	
21	CLK	O	Communication clock signal output terminal
22	PLUNGER2	O	Plunger(solenoid) control output terminal
23	LSTB	O	Strobe signal output terminal
24	LCLK	O	Command clock output terminal

Pin No.	Mark	I/O Division	Function
25	LDATA	O	Command data output terminal
26	NC	—	Not used, open
27	/MLD	O	Command load signal output terminal
28	MDATA	O	Command data signal output terminal
29	MCLK	O	Command clock signal output terminal
30	SENSOR	O	LED sensor drive output terminal
31	KEY1	I	Key switch detect input terminal
32	KEY2	I	
33	REST SW	I	Rest position det. input terminal
34	STAT	I	Status signal input terminal
35	CW	O	Loading motor drive output terminal
36	CCW	O	
37	PCUT	O	Power control output terminal
38	XCNT	O	Crystal OSC control output terminal
39	POSITION	I	Sub tray position detect input terminal
40	DOWN	I	Sub tray "DOWN" det. input terminal
41	OPEN	I	Disc tray "OPEN" det. input terminal
42	CLOSE	I	Disc tray "CLOSE" det. input terminal
43	SUBQ	I	Sub-code Q data input terminal
44	DMUTE	O	Muting signal output terminal
45	SQCK	O	Sub-code Q register clock output terminal
46	BLKCK	I	Sub-code block clock input terminal (f = 75Hz)
47	TGAIN	I	Not used, connected to external resistor
48	TEST2	I	Test terminal

● IC401 (MN662743CDC1): SERVO PROCESSOR / DIGITAL SIGNAL PROCESSOR / DIGITAL FILTER / D/A CONVERTER

Pin No.	Mark	I/O Division	Function
1	BLK	O	Bit clock output for serial data
2	LRCK	O	L/R identification signal output ("H": L-ch audio data, "L": R-ch audio data)
3	SRDATA	O	Serial data output
4	DVDD1	I	Power supply input (for digital circuit)
5	DVss1	—	GND terminal (for digital circuit)
6	TX	O	Digital audio interface signal output
7	MCLK	I	Microprocessor command clock signal input (Latches data at first transition)
8	MDATA	I	Microprocessor command data signal input
9	MLD	I	Microprocessor command load signal input ("L": load)
10	SENSE	O	Sense signal output (OFT, FESL, NACEND, NAJEND, POSAD, SFG, NWTEND) (Not used, open)
11	/FLOCK	O	Focus servo feeding signal output ("L": Feed) (Not used, open)
12	/TLOCK	O	Tracking servo feeding signal output ("L": Feed) (Not used, open)
13	BLKCK	O	Sub-code block clock signal output (f=75 Hz)
14	SQCK	I	External clock signal input for sub-code Q register
15	SUBQ	O	Sub-code Q code output
16	DMUTE	I	Muting signal input ("H": MUTE)
17	STAT	O	Status signal output (CRC, CUE, CLVS, TTSTVP, FCLV, SQCK, FLAG6, SENSE, /FLOCK, /TLOCK)
18	/RST	I	Reset signal input ("L": reset) at IOSEL="L": (472ns and over="L")
19	SMCK	O	Clock signal output at MSEL="H" (8.4672 MHz) at MSEL="L" (16.9344 MHz) (Not used, open)
20	PMCK	O	Clock signal output (88.2kHz) (Not used open)
21	SPARI	I	Test terminal (normally "L")
22	SPARO	O	Test terminal (normally "open")
23	/QVEL	O	Quadruple speed status signal output ("L": quadruple speed)(Not used, open)
24	TESTMI	I	Test terminal (pull-down terminal) (normally "L")
25	PRUN	O	Optical pickup tracking detection signal output (Not used, open)
26	TRV	O	Traverse forced feed signal output (Not used, open)
27	TVD	O	Traverse drive signal output

Pin No.	Mark	I/O Division	Function
28	PC	O	Spindle motor ON signal output ("L": ON, default)
29	ECM	O	Spindle motor drive signal output (forced mode output)
30	ECS	O	Spindle motor drive signal output (Servo error signal output)
31	KICK	O	Kick pulse output
32	TRD	O	Tracking drive signal output
33	TESTX	I	Test terminal (normally "L")
34	FOD	O	Focus drive signal output
35	DIRC	O	Optical pickup tracking direction detection signal (Not used, open)
36	VREF	I	Reference voltage input of D/A(drive) output (TVD,ECS,TRD,FOD,FBAL,TBAL,TOFS)
37	FBAL	O	Focus balance adjustment signal output
38	DVDD2	I	Power supply input (for digital circuit)
39	TBAL	O	Tracking balance adjustment signal output
40	DVss2	—	GND terminal (for digital circuit)
41	FE	I	Focus error signal input (analog input)
42	TE	I	Tracking error signal input (analog input)
43	RFENV	I	RF envelope signal input (analog input)
44	VDET	I	Vibration detection signal input ("H": detectoion)
45	OFT	I	Off-track signal input ("H": off track)
46	TRCRS	I	Track cross signal input
47	/RFDET	I	RF detection signal input ("L": detection)
48	BDO	I	Dropout signal input ("H": Dropout)
49	LDON	O	Laser on signal output ("H": ON)
50	EXTROM	I	Test terminal (normally "L")
51	TES	O	Tracking error shunt signal output ("H": shunt) (Not used, open)
52	PLAY	O	Play signal out ("H": PLAY) (Not used, open)
53	/WVEL	O	Double speed status signal output ("L": Double speed) (Not used, open)
54	ARF	I	RF signal input
55	IREF	I	Reference current input terminal

Pin No.	Mark	I/O Division	Function
56	DRF	I	DSL bias terminal (Not used, open)
57	DSL	I/O	DSL loop filter terminal
58	PLL	I/O	PLL loop filter terminal
59	TESTR	I	Test terminal (EXIREF)(normally "L")
60	EXPLL	O	Test terminal (normally "open")
61	VCOF	I/O	VCO loop filter terminal (Not used, connected to GND)
62	EXPCK	O	Test terminal (normally "open")
63	AVDD2	I	Power supply input for analog circuit (DSL,PLL,DA OUTPUT,AD)
64	AVss2	—	GND terminal for analog circuit (DSL,PLL,DA OUTPUT,AD)
65	BUFOUT	O	Test terminal (normally "open")
66	EFM	O	at IOSEL="H"; EFM signal output at IOSEL="L"; Clock signal output (16.9344 MHz) (Not used, open)
67	DSLOUT	O	Test terminal (normally "open")
68	PCK	O	PLL extraction clock signal output (IPCK=4.321 MHz) (Not used, open)
69	TOFS	O	Tracking offset adjustments signal output
70	SUBC	O	Sub-code serial data output (Not used, open)
71	SBCK	I	Clock signal input for sub-code serial data (Not used, connected to GND)
72	Vss	—	GND terminal (for oscillating circuit)
73	X1	I	Crystal oscillating circuit output (f=33.8688 MHz)
74	X2	O	Crystal oscillating circuit output (f=33.8688 MHz)
75	VDD	I	Power supply input (for oscillating circuit)
76	BYTCK	O	at IOSEL="H" Byte clock signal output at IOSEL="L" Traverse stop signal output (H": stop mode) (Not used, open)
77	TESTC	I	Test terminal (EXPCKIN) (normally "L")
78	/CLDCK	O	Sub-code frame clock signal output (CLDCK=7.35kHz) (Not used, open)
79	TESTE	I	Test terminal (EXEFMIN) (normally "L")
80	FCLK	O	Crystal frame clock signal output (FCLK=7.35kHz) (Not used, open)

Pin No.	Mark	I/O Division	Function
81	IPFLAG	O	Interpolation flag signal output (H": Interpolation) (Not used, open)
82	FLH	O	Speed detection result output (3-state output) (Not used, open)
83	FLAG	O	Flag signal output (Not used, open)
84	NC6(PL)	O	Test terminal (normally "open")
85	NC&(PH)	O	Test terminal (normally "open")
86	CLVS	O	Spindle servo phase synchronizing signal output (Not used, open) (H": CLV, "L": rough servo)
87	CRC	O	Sub-code CRC checked result output (H": OK, "L": NG) (Not used, open)
88	DEMPH	O	De-emphasis detection signal output (H": ON)
89	RESY	O	at IOSEL="H"; Frame sync. resynchronization signal output "H": pull in "L": pull out at IOSEL="L"; Error correction deinterleaving RAM address reset signal FLAG6 output "L": address reset generation (Not used, open)
90	IOSEL	I	Mode switching terminal
91	/TEST	I	Test terminal (normally "L")
92	AVDD1	I	Power supply terminal for analog circuit [for audio output(use as L-ch and R-ch)]
93	OUTL	O	Left channel audio signal output
94	AVss1	—	GND terminal for analog circuit [for audio output(use as L-ch and R-ch)]
95	OUTR	O	Right channel audio signal output
96	RSEL	I	RF signal polarity assignment terminal (at "H" level: RSEL= "H") (at "L" level: RSEL= "L")
97	CSEL	I	Crystal oscillating frequency designation input ("H": 33.8688MHz)
98	PSEL/ SRDATAIN	I	at IOSEL="H" Test terminal (normally "L") at IOSEL="L" SRDATA input terminal
99	MSEL/ LRCKIN	I	at IOSEL="H" Output frequency switching of SMCK terminal "H": SMCK=8.4672MHz "L": SMCK=16.9344MHz at IOSEL="L" LRCK input terminal "H": L-ch data, "L": R-ch data (SMCK terminal output=16.9344MHz)
100	SSEL/ BCLKIN	I	at IOSEL="H" Output mode switching of SUBQ terminal "H": Q code buffer mode at IOSEL="L" BCLK input terminal "H": L-ch data, "L": R-ch data (SUB Q terminal output mode=Q code buffer mode)

● IC601 (AN8389SE1): LOADING MOTOR / TRAVERSE MOTOR DRIVE

Pin No.	Mark	I/O Division	Function
1	Vcc	I	Power supply terminal
2	VREF	I	Reference voltage input terminal
3	IN4	I	Traverse motor driver (4) input
4	IN3	I	Traverse motor driver (3) input
5	GND	I	GND terminal (Connected to negative voltage)
6	NC	I	Not used, connected to negative voltage
7	/RST	O	Reset terminal (Not used, open)
8	GND	I	GND terminal (Connected to negative voltage)
9	IN2	O	Loading motor driver (2) input
10	PC2	I	Loading motor drive signal ("L" : ON)
11	IN1	I	Loading motor driver (1) input
12	PC1	I	Loading motor drive signal ("L" : ON)

Pin No.	Mark	I/O Division	Function
13	PVcc1	I	Driver power supply terminal (1)
14	PGND1	I	Driver GND terminal (1) (Connected to negative voltage)
15	D1-	O	Motor driver (1) output terminal (-) (Not used, open)
16	D1+	O	Loading motor driver (1) output terminal (+)
17	D2-	O	Motor driver (2) output terminal (-) (Not used, open)
18	D2+	O	Motor driver (2) output terminal (+)
19	D3-	O	Traverse motor driver (3) output terminal (-)
20	D3+	O	Traverse motor driver (3) output terminal (+)
21	D4-	O	Traverse motor driver (4) output terminal (-)
22	D4+	O	Traverse motor driver (4) output terminal (+)
23	PGND2	I	Driver GND terminal (2) (Connected to negative voltage)
24	PVcc2	I	Driver power supply (2)

● IC502 (AN8387SE2): FOCUS COIL/TRACKING COIL DRIVE

Pin No.	Mark	I/O Division	Function
1	SVcc	I	Power supply terminal
2	IN1	I	Tracking coil drive input terminal
3	PC1	I	Power control input terminal (Not used, connected to GND)
4	VREF	I	Reference voltage input terminal
5	PGND	—	GND terminal
6	PGND	—	GND terminal
7	SGND	—	GND terminal
8	PC2	I	Power control input terminal (Not used, connected to GND)
9	IN2	I	Focus coil drive input terminal
10	SVcc	I	Power supply terminal

Pin No.	Mark	I/O Division	Function
11	VLIM2	I	Voltage limit terminal
12	PVcc	I	Power supply terminal
13	D2+	O	Focus coil drive output terminal (+)
14	D2-	O	Focus coil drive output terminal (-)
15	PGND	—	GND terminal
16	PGND	—	GND terminal
17	D1-	O	Tracking coil drive output terminal (-)
18	D1+	O	Tracking coil drive output terminal (+)
19	PVcc	I	Power supply terminal
20	VLIM1	I	Voltage limit terminal

## ● IC501 (AN8835SBE1): SERVO AMP

Pin No.	Mark	I/O Division	Function
1	PDA	I	Focus signal input terminal (1) (Ach)
2	PDB	I	Focus signal input terminal (2) (Bch)
3	Vcc	I	Power supply terminal
4	LPD	I	APC amp input terminal
5	LD	O	APC amp output terminal
6	RF	O	RF summing output terminal
7	RF IN	I	AGC input terminal
8	CAGC	I	AGC detection capacitor input
9	ARF	O	RF signal output terminal
10	CSBRT	I	Capacitor connection terminal for OFTR
11	CEA	I	Capacitor connection terminal for H.P.F. amp
12	BDO	O	Dropout signal output terminal ("H" : Dropout)
13	LDON	I	APC control input terminal ("H" : ON, "L" : OFF)
14	GND	—	GND terminal

Pin No.	Mark	I/O Division	Function
15	/RFDET	O	RF det. signal output terminal ("L" : Det.)
16	CROSS	O	Track cross signal output terminal
17	OFTR	O	Off track signal output terminal ("H" : Off track)
18	VDET	O	Vibration det. signal output terminal ("H" : Det.)
19	ENV	O	RF envelope signal output terminal
20	TEBPF	I	Oscillation detect input terminal (Not used, open)
21	CCRS	I	CROSS capacitor connection terminal
22	TE	O	Tracking error amp output terminal
23	FE	O	Focus error amp output terminal
24	TBAL	I	Tracking balance adj. input terminal
25	FBAL	I	Focus balance adj. input terminal
26	VREF	O	Reference voltage output terminal
27	PDE	I	Tracking signal input terminal (1) (E ch)
28	PDF	I	Tracking signal input terminal (2) (F ch)

## ● IC402 (MN6475A-T1): DIGITAL FILTER AND D/A CONVERTER

Pin No.	Mark	I/O Division	Function
1	LRCK	I	L/R channel discrimination input terminal
2	BCLK	I	Bit clock input terminal
3	SRDATA	I	Serial data input terminal
4	COT1	I	Signal selection output terminal (COT1: L / COT2: L ; Normal, stereo signal output)
5	COT2	I	
6	TEST	I	Test terminal (Normal "L")

Pin No.	Mark	I/O Division	Function
7	DVDD	I	Power supply terminal
8	X2	O	Crystal OSC terminal (f = 33.8688MHz)
9	X1	I	
10	DVss	—	GND terminal
11	AVDDL	I	Power supply (L channel) terminal
12	OUTL	O	L channel analog signal output terminal

Pin No.	Mark	I/O Division	Function
13	AVssL	—	GND (L channel) terminal
14	AVssR	—	GND (L channel) terminal
15	OUTR	O	R channel analog signal output terminal
16	AVddR	I	Power supply (R channel) terminal
17	RSTB	I	Reset signal input terminal
18	PWL	—	Not used, open

Pin No.	Mark	I/O Division	Function
19	TP	—	Not used, connected to GND
20	WVEL	—	Not used, connected to GND
21	DEMPH	I	De-emphasis on/off control terminal (De-emphasis on: H)
22	CSEL	I	Frequency select(COUT) input terminal (1/4f: "L", 1/2f: "H")
23	COUT	O	Frequency(192fs) clock output terminal (Not used, open)
24	XOUT	O	Frequency(384fs) clock output terminal (Not used, open)

● IC602 (NBC3903MT1): SPINDLE MOTOR DRIVE

Pin No.	Mark	I/O Division	Function
1	NC	—	Not used, open
2	NC	—	Not used, open
3	A3	O	Spindle motor drive output terminal
4	NC	—	Not used, open
5	A2	O	Spindle motor drive output terminal
6	A1	O	Spindle motor drive output terminal
7	GND	—	GND terminal
8	H1+	I	Hall element detect (+) input terminal
9	H1-	I	Hall element detect (-) input terminal
10	NC	—	Not used, open
11	NC	—	Not used, open
12	H2+	I	Hall element detect (+) input terminal
13	H2-	I	Hall element detect (-) input terminal
14	H3+	I	Hall element detect (+) input terminal

Pin No.	Mark	I/O Division	Function
15	H3-	I	Hall element detect (-) input terminal
16	VH	O	Hall element bias output terminal
17	CNF	I	Time constant control terminal
18	NC	—	Not used, open
19	ECR	I	Torque sense amp (-) input terminal
20	EC	I	Torque sense amp (+) input terminal
21	PS	I	Power control input terminal
22	NC	—	Not used, open
23	Vcc	I	Power supply terminal
24	NC	—	Not used, open
25	NC	—	Not used, open
26	VM	I	Power supply terminal
27	NC	—	Not used, open
28	RNF	I	Current sense amp (-) and coil driver input terminal

## ■ Replacement Parts List (Electrical)

**Notes:**

- \* Important safety notice:  
Components identified by  $\Delta$  mark have special characteristics important for safety.
- Furthermore, special parts which have purposes of fire-retardant (resistors), high-quality sound (capacitors), low-noise (resistors), etc. are used.
- When replacing any of components, be sure to use only manufacturer's specified parts shown in the parts list.
- \* Warning: This product uses a laser diode. Refer to caution statements on page 2.
- \* ACHTUNG: Die Lasereinheit darf nur gegen eine vom Hersteller spezifizierte Einheit ausgetauscht werden.
- \* [M] indicates in Remarks columns parts that are supplied by MESA.

Ref. No.	Part No.	Part Name & Description	Remarks	Ref. No.	Part No.	Part Name & Description	Remarks
		INTEGRATED CIRCUIT(S)		D112, 113	RL1N4003BD80	DIODE	[M]
IC101	LM2940T5	IC	[M] $\Delta$	D201-205	AABG4607K740	L. E. D.	[M]
IC102	BA4558FHTT1	IC	[M]	D206	SPR-305MDTF	L. E. D.	[M]
IC103	TOTX178	IC	[M]	D301-303	MA111TX	DIODE	[M]
IC201	NJU3713GTE1	IC	[M]	D401	MA111TX	DIODE	[M]
IC301	LC66538A4J35	IC	[M]	D501	MA111TX	DIODE	[M]
IC401	MN662743CDC1	IC	[M]	D601	MA112TX	DIODE	[M]
IC402	MN6475A-T1	IC	[M]	D691	LN57AU	L. E. D.	[M]
IC501	AN8835SBE1	IC	[M]			PHOTO INTERRUPTER(S)	
IC502	AN8387SE2	IC	[M]	Z1	GP1S93	PHOTO INTERRUPTER	[M]
IC601	AN8389SE1	IC	[M]	Z2, 3	GP1S94	PHOTO INTERRUPTER	[M]
IC602	NBC3903MT1	IC	[M]			COIL(S)	
IC603	NJM2115MT1	IC	[M]	L101, 102	RLBN300AV-W	COIL	[M] $\Delta$
		TRANSISTOR(S)				OSCILLATOR(S)	
Q101	2SD2374PQAU	TRANSISTOR	[M] $\Delta$	X301	EFOEC4234T3	OSCILLATOR	[M]
Q102	2SB1548PQAU	TRANSISTOR	[M] $\Delta$	X402	RSXC33M8R01	OSCILLATOR	[M]
Q103	2SB766-QRSTX	TRANSISTOR	[M] $\Delta$			SWITCH(ES)	
Q104	2SD874QRSTX	TRANSISTOR	[M] $\Delta$	S1	RSH2B003-U	SW	[M]
Q105	2SB1417PQTA	TRANSISTOR	[M] $\Delta$	S201-205	EVQPJH05K	SW	[M]
Q106	2SD1819ASTX	TRANSISTOR	[M] $\Delta$	S206-214	EVQ21405R	SW	[M]
Q111-113	2SD2137PQTA	TRANSISTOR	[M] $\Delta$			CONNECTOR(S) AND SOCKET(S)	
Q301	UN5214TX	TRANSISTOR	[M]	CN301	RJU099W10	SOCKET(10P)	[M]
Q303-305	2SD1819ASTX	TRANSISTOR	[M]	CN501	RJS2A4716M	CONNECTOR(16P)	[M]
Q401, 402	UN5214TX	TRANSISTOR	[M]	CN601	RJS2A4714M	CONNECTOR(14P)	[M]
Q501	2SB709QRSTX	TRANSISTOR	[M]	CN602	RJS2A4716M	CONNECTOR(16P)	[M]
Q601	2SB956RTX	TRANSISTOR	[M]	CP201	RJT099W10-1	CONNECTOR(10P)	[M]
Q602	UN5214TX	TRANSISTOR	[M]	JK101	RJT065K19	CONNECTOR(19P)	[M]
Q603	UN5112TX	TRANSISTOR	[M]			EARTH PLATE(S)	
Q604	2SB956RTX	TRANSISTOR	[M]	E101	SNE1004-2	EARTH PLATE	[M]
Q605	UN5214TX	TRANSISTOR	[M]			FLAT CABLE(S)	
Q691	PT381TB	TRANSISTOR	[M]				
Q692	2SB709QRSTX	TRANSISTOR	[M]	W601	REZ0961	FLAT CABLE(3P)	[M]
		DIODE(S)					
D101-104	RL1N4003N02	DIODE	[M] $\Delta$				
D105	MA8075	DIODE	[M] $\Delta$				
D106, 107	MA111TX	DIODE	[M]				
D108	MA8075	DIODE	[M] $\Delta$				
D109, 110	MA111TX	DIODE	[M]				
D111	MA8056MTX	DIODE	[M] $\Delta$				

## ■ Resistors and Capacitors

**Notes:** \* Capacity values are in microfarads (uF) unless specified otherwise, P=Pico-farads (pF) F=Farads (F)  
 \* Resistance values are in ohms, unless specified otherwise, 1K=1,000 (OHM), 1M=1,000k (OHM)  
 \* [M] indicates in Remarks columns parts that are supplied by MESA.

Ref. No.	Part No.	Values & Remarks	Ref. No.	Part No.	Values & Remarks	Ref. No.	Part No.	Values & Remarks
			R308	ERJ6GEYJ103V	1/10W 10K [M]	R603	ERJ6GEYJ103V	1/10W 10K [M]
		RESISTORS	R310	ERJ6GEYJ103V	1/10W 10K [M]	R604, 605	ERJ6GEYJ221V	1/10W 220 [M]
R101	ERJ6GEYJ471V	1/10W 470 [M]	R311	ERJ6GEYJ223V	1/8W 22K [M]	R607, 608	ERJ6GEYJ103V	1/10W 10K [M]
R102	ERJ6GEYJ101V	1/10W 100 [M]	R312	ERJ6GEYJ473V	1/10W 47K [M]	R610	ERJ6GEYJ153V	1/10W 15K [M]
R103	ERJ6GEYJ223V	1/10W 22K [M]	R313	ERJ6GEYJ103V	1/10W 10K [M]	R612	ERJ6GEYJ153V	1/10W 15K [M]
R104	ERJ6GEYJ820V	1/10W 82 [M]	R314, 315	ERJ6GEYJ472V	1/10W 4.7K [M]	R614	ERJ6GEYJ101V	1/10W 100 [M]
R105	ERJ6GEYJ471V	1/10W 470 [M]	R316	ERJ6GEYJ473V	1/10W 47K [M]	R615-617	ERJ6GEYJ1R5V	1/10W 1.5 [M]
R106	ERJ6GEYJ101V	1/10W 100 [M]	R317, 318	ERJ6GEYJ472V	1/10W 4.7K [M]	R618	ERJ6GEYJ330V	1/10W 33 [M]
R107	ERJ6GEYJ223V	1/10W 22K [M]	R319, 320	ERJ6GEYJ102V	1/10W 1K [M]	R620	ERJ6GEYJ154V	1/10W 150K [M]
R108	ERJ6GEYJ820V	1/10W 82 [M]	R321-323	ERJ6GEYJ101V	1/10W 100 [M]	R621	ERJ6GEYJ563V	1/10W 56K [M]
R110	ERJ6GEYJ471V	1/10W 470 [M]	R324	ERJ6GEYJ101V	1/8W 100 [M]	R622	ERJ6GEYJ103V	1/10W 10K [M]
R111	ERJ6GEYJ101V	1/10W 100 [M]	R327, 328	ERJ6GEYJ471V	1/8W 470 [M]	R623	ERJ6GEYJ472V	1/10W 4.7K [M]
R112, 113	ERJ6GEYJ102V	1/10W 1K [M]	R330, 331	ERJ6GEYJ103V	1/8W 10K [M]	R624	ERJ6GEYJ472V	1/8W 4.7K [M]
R114, 115	ERJ6GEYJ104V	1/10W 100K [M]	R334	ERJ6GEYJ103V	1/10W 10K [M]	R625, 626	ERJ6GEYJ103V	1/10W 10K [M]
R116-119	ERJ6GEYJ472V	1/10W 4.7K [M]	R335	ERJ6GEYJ472V	1/8W 4.7K [M]	R628	ERJ6GEYJ472V	1/10W 4.7K [M]
R120, 121	ERJ6GEYJ273V	1/10W 27K [M]	R336	ERJ6GEYJ104V	1/8W 100K [M]	R631	ERJ6GEYJ103V	1/10W 10K [M]
R122, 123	ERJ6GEYJ332V	1/10W 3.3K [M]	R337	ERJ6GEYJ471V	1/10W 470 [M]	R632, 633	ERJ6GEYJ221V	1/10W 220 [M]
R124, 125	ERJ6GEYJ473V	1/10W 47K [M]	R338	ERJ6GEYJ101V	1/10W 100 [M]	R634	ERJ6GEYJ333V	1/10W 33K [M]
R126, 127	ERJ6GEYJ221V	1/10W 220 [M]	R339	ERJ6GEYJ471V	1/10W 470 [M]	R635	ERJ6GEYJ333V	1/8W 33K [M]
R128	ERJ6GEYJ101V	1/10W 100 [M]	R340	ERJ6GEYJ562V	1/10W 5.6K [M]	R691	ERJ6GEYJ271V	1/10W 270 [M]
R129	ERJ6GEYJ470V	1/10W 47 [M]	R341	ERJ6GEYJ473V	1/10W 47K [M]	R692	ERJ6GEYJ103V	1/10W 10K [M]
R130	ERJ6GEYJ472V	1/10W 4.7K [M]	R342, 343	ERJ6GEYJ104V	1/8W 100K [M]	R693	ERJ6GEYJ471V	1/10W 470 [M]
R131-133	ERJ6GEYJ1R0V	1/10W 1.0 [M]	R345	ERJ6GEYJ103V	1/10W 10K [M]			CHIP JUMPERS
R134	ERJ6GEYJ471V	1/10W 470 [M]	R401	ERJ6GEYJ102V	1/10W 1K [M]			
R135, 136	ERJ6GEYJ820V	1/10W 82 [M]	R403	ERJ6GEYJ683V	1/10W 68K [M]			
R137	ERJ6GEYJ471V	1/10W 470 [M]	R404	ERJ6GEYJ221V	1/10W 220 [M]	R142	ERJ6GEYOR00V	CHIP JUMPER [M]
R138, 139	ERJ6GEYJ820V	1/10W 82 [M]	R405	ERJ6GEYJ154V	1/10W 150K [M]	R222	ERJ6GEYOR00V	CHIP JUMPER [M]
R140	ERJ6GEYJ471V	1/10W 470 [M]	R406	ERJ6GEYJ155V	1/10W 1.5M [M]	R326	ERJ6GEYOR00V	CHIP JUMPER [M]
R141	ERJ6GEYJ470V	1/10W 47 [M]	R421	ERJ6GEYJ104V	1/10W 100K [M]	R346	ERJ6GEYOR00V	CHIP JUMPER [M]
R201-203	ERJ8GEYJ101V	1/8W 100 [M]	R422	ERJ6GEYJ331V	1/10W 330 [M]	R349	ERJ6GEYOR00V	CHIP JUMPER [M]
R204	ERJ6GEYJ331V	1/10W 330 [M]	R423	ERJ6GEYJ470V	1/10W 47 [M]	R501	ERJ6GEYOR00V	CHIP JUMPER [M]
R205-209	ERJ6GEYJ151V	1/10W 150 [M]	R424	ERJ6GEYJ105	1/10W 1M [M]	RJ601-611	ERJ6GEYOR00V	CHIP JUMPER [M]
R210	ERJ6GEYJ152V	1/10W 1.5K [M]	R425, 426	ERJ6GEYJ101V	1/10W 100 [M]	RJ701-705	ERJ6GEYOR00V	CHIP JUMPER [M]
R211	ERJ6GEYJ122V	1/10W 1.2K [M]	R427	ERJ6GEYJ103V	1/10W 10K [M]	RJ801-807	ERJ6GEYOR00V	CHIP JUMPER [M]
R212	ERJ6GEYJ102V	1/10W 1K [M]	R502	ERJ6GEYJ220	1/10W 22 [M]	RJ901-905	ERJ6GEYOR00V	CHIP JUMPER [M]
R213, 214	ERJ6GEYJ821V	1/10W 820 [M]	R503	ERJ6GEYJ4R7V	1/10W 4.7 [M]			
R215	ERJ6GEYJ102V	1/10W 1K [M]	R505	ERJ6GEYJ823	1/10W 82K [M]			CAPACITORS
R216	ERJ6GEYJ122V	1/10W 1.2K [M]	R506	ERJ6GEYJ102V	1/10W 1K [M]			
R217	ERJ6GEYJ152V	1/10W 1.5K [M]	R507	ERJ6GEYJ103V	1/10W 10K [M]	C101, 102	ECUV1H103KBN	50V 0.01U [M]
R218	ERJ6GEYJ182V	1/10W 1.8K [M]	R508	ERJ6GEYJ102V	1/10W 1K [M]	C103-105	ECA1EM102B	25V 1000U [M]△
R219	ERJ6GEYJ222V	1/10W 2.2K [M]	R509	ERJ6GEYJ103V	1/10W 10K [M]	C106	RCE1CKS470BV	16V 47U [M]
R220	ERJ6GEYJ332V	1/10W 3.3K [M]	R510	ERJ6GEYJ474V	1/10W 470K [M]	C107	ECUV1H102KBN	50V 1000P [M]
R221	ERJ6GEYJ472V	1/10W 4.7K [M]	R511	ERJ6GEYJ224V	1/10W 220K [M]	C108	ECEA1AKS221	10V 220U [M]
R223-227	ERJ6GEYJ271V	1/10W 270 [M]	R513	ERJ6GEYJ682V	1/10W 6.8K [M]	C109	RCE1CKS470BV	16V 47U [M]
R301	ERJ6GEYJ103V	1/10W 10K [M]	R514	ERJ6GEYJ154V	1/10W 150K [M]	C110	ECUV1H102KBN	50V 1000P [M]
R302	ERJ8GEYJ105V	1/8W 1M [T]	R515-517	ERJ6GEYJ103V	1/10W 10K [M]	C111	ECEA1AKS221	10V 220U [M]
R303	ERJ8GEYJ102V	1/8W 1K [M]	R518	ERJ6GEYJ682V	1/10W 6.8K [M]	C112	ECEA0JKA221B	6.3V 220U [M]
R304	ERJ6GEYJ104V	1/10W 100K [M]	R601	ERJ6GEYJ151V	1/10W 150 [M]	C113	RCE1AKA470BG	10V 47U [M]
			R602	ERJ6GEYJ221V	1/10W 220 [M]	C114	ECEA0JKA221B	6.3V 220U [M]

Ref. No.	Part No.	Values & Remarks	Ref. No.	Part No.	Values & Remarks	Ref. No.	Part No.	Values & Remarks
C115, 116	ECEA1AKA220B	10V 22U [M]	C404	ECUV1H561KBN	50V 560P [M]	C512	ECUV1E104ZFN	25V 0.1U [M]
C117, 118	ECUV1H122KBN	50V 1200P [M]	C405	ECUV1H102KBN	50V 1000P [M]	C513	ECUV1E273KBN	25V 0.027U [M]
C119, 120	ECUV1H561KBN	50V 560P [M]	C406	ECUV1E104ZFN	25V 0.1U [M]	C514	ECUV1E104ZFN	25V 0.1U [M]
C121, 122	RCE1AKA470BG	10V 47U [M]	C407	ECUV1E223KBN	25V 0.022U [M]	C515	ECUV1H272KBN	50V 2700P [M]
C123, 124	ECEA1AKA220B	10V 22U [M]	C408	ECUV1E123KBN	25V 0.012U [M]	C516	ECUV1E104ZFN	25V 0.1U [M]
C125, 126	ECUV1H102KBN	50V 1000P [M]	C409	ECUV1C224KBN	16V 0.22U [M]	C517, 518	ECUV1H103KBN	50V 0.01U [M]
C127	ECUV1H103KBN	50V 0.01U [M]	C411	ECUV1H104ZFM	50V 0.1U [M]	C519	ECUV1C104KBN	16V 0.1U [M]
C128, 129	ECUV1H222KBN	50V 2200P [M]	C414	ECUV1E104ZFN	25V 0.1U [M]	C520	ECUV1H472KBN	50V 4700P [M]
C130	ECUV1H102KBN	50V 1000P [M]	C421	ECUV1H101JCN	50V 100P [M]	C521	ECUV1E273KBN	25V 0.027U [M]
C131	RCE1AKA470BG	10V 47U [M]	C423	ECEAOJKA101B	6.3V 100U [M]	C522	ECUV1C473KBN	16V 0.047U [M]
C132, 133	ECUV1H103KBN	50V 0.01U [M]	C424	ECUV1H104ZFM	50V 0.1U [M]	C523	ECUV1H332KBN	50V 3300P [M]
C201-203	ECUV1H101JCN	50V 100P [M]	C425	ECUV1H103KBN	50V 0.01U [M]	C524	ECUV1H222KBN	50V 2200P [M]
C204	ECUV1H103KBN	50V 0.01U [M]	C426, 427	ECUV1H060DCN	50V 6P [M]	C525	ECUV1H471KBN	50V 470P [M]
C301	ECUV1H104ZFM	50V 0.1U [M]	C428	ECEAOJKA331B	6.3V 330U [M]	C605	ECUV1E104ZFN	25V 0.1U [M]
C303	ECUV1H102KBN	50V 1000P [M]	C429, 430	ECUV1H103KBN	50V 0.01U [M]	C613-615	ECUV1H103KBN	50V 0.01U [M]
C304	RCE1HKA3R3BG	50V 3.3U [M]	C431	ECUV1H102KBN	50V 1000P [M]	C616	ECEA1HKA2R2B	50V 2.2U [M]
C305	ECEAOJKA470B	6.3V 47U [M]	C501-505	ECUV1E104ZFN	25V 0.1U [M]	C617, 618	ECUV1E104ZFN	25V 0.1U [M]
C306	ECUV1H101JCN	50V 100P [M]	C506	ECUV1H103KBN	50V 0.01U [M]	C619	ECUV1C104KBN	16V 0.1U [M]
C307-309	ECUV1H102KBN	50V 1000P [M]	C508	ECUV1H681KBN	50V 680P [M]	C620	ECUV1E333KBN	25V 0.033U [M]
C401	ECUV1E104ZFN	25V 0.1U [M]	C509	ECEA1CKA330B	16V 33U [M]	C621	ECUV1E104ZFN	25V 0.1U [M]
C402	ECEAOJKA101B	6.3V 100U [M]	C510	ECEAOJKA101B	6.3V 100U [M]			
C403	ECUV1E104ZFN	25V 0.1U [M]	C511	ECUV1H104ZFM	50V 0.1U [M]			

## ■ Replacement Parts List (Cabinet)


**Notes:** \* Warning: This product uses a laser diode. Refer to caution statements on page 2.  
 \* ACHTUNG: Die Lasereinheit nicht zerlegen.  
 Die Lasereinheit darf nur gegen eine vom Hersteller spezifizierte Einheit ausgetauscht werden.

\* [M] indicates in Remarks columns parts that are supplied by MESA.

Ref. No.	Part No.	Part Name & Description	Remarks	Ref. No.	Part No.	Part Name & Description	Remarks
		CABINET AND CHASSIS		15	RMG0455-K	FLOATING RUBBER	[M]
1	RGK0817-M	SIDE PANEL (L)	[M]	16	RMN0410	MECHANISM SPACER (L)	[M]
2	RGK0818-M	SIDE PANEL (R)	[M]	17	RMN0411	MECHANISM SPACER (R)	[M]
3	RHD30073-K	SCREW	[M]	18	RMN0421	MECHANISM SPACER (C)	[M]
4	RKM0327-S	CABINET	[M]	19	RMZ0420	INSULATION SHEET	[M]
5	RQLA0384	CAUTION GUIDE	[M]	20	RMR1040-K	L. E. D. HOLDER	[M]
6	XTBS3+8JFZ1	SCREW	[M]	21	RFKGLHD70E-N	FRONT PANEL ASS'Y	[M]
7	RMR1038-K	SENSOR HOLDER (D691)	[M]	22	RGK0819-N	SIDE ORNAMENT (L)	[M]
8	RMR1039-K	SENSOR HOLDER (Q691)	[M]	23	RGK0820-N	SIDE ORNAMENT (R)	[M]
9	RFKNLHD70EAN	TRAY ORNAMENT ASS'Y	[M]	24	RGL0346-Q	DISC INDEX	[M]
10	RGR0250B-A	REAR PANEL	[M]	25	RGL0347-Q	L. E. D. INDEX	[M]
11	RHD26027-K	SCREW	[M]	26	RGU1484-S	OPERATION BUTTON (A)	[M]
12	RFKJLHD70E-N	BOTTOM CHASSIS ASS'Y	[M]	27	RGU1485-S	OPERATION BUTTON (B)	[M]
12-1	RKA0076-N	FOOT	[M]	28	RGU1486-S	DISC BUTTON	[M]
13	RMB0518	FLOATING SPRING (A)	[M]	29	XQN26+AJ6FZ	SCREW	[M]
14	RMB0519	FLOATING SPRING (B)	[M]	30	SHE170-2	P. C. B. HOLDER	[M]
				31	XTB3+12JFZ	SCREW	[M]
				32	XTB3+6JFZ	SCREW	[M]

1 2 3 4 5


### ■ Cabinet Parts Location



1 2 3 4 5

## ■ Loading Mechanism Parts Location

The parts enclosed in the dotted boxes and  $\ast$  mark are supplied as a block assembly. Therefore, they are not supplied separately except parts indicated with Ref. No.



## ■ Replacement Parts List (Loading Mechanism)

**Notes:**

- Important safety notice:  
Components identified by  $\Delta$  mark have special characteristics important for safety.  
Furthermore, special parts which have purposes of fire-retardant (resistors), high-quality sound (capacitors), low-noise (resistors), etc. are used.  
When replacing any of components, be sure to use only manufacturer's specified parts shown in the parts list.
- Warning: This product uses a laser diode. Refer to caution statements on page 2.
- ACHTUNG: Die Lasereinheit nicht zerlegen.  
Die Lasereinheit darf nur gegen eine vom Hersteller spezifizierte Einheit ausgetauscht werden.
- [M] indicates in Remarks columns parts that are supplied by MESA.

Ref. No.	Part No.	Part Name & Description	Remarks	Ref. No.	Part No.	Part Name & Description	Remarks
		LOADING MECHANISM		130	XQN2+A22FZ	SCREW	[M]
101	RAE0161Z	TRAVERSE DECK	[M] $\Delta$	131	XQN2+BJ5	SCREW	[M]
101-1	RAF0140A	OPTICAL PICKUP	[M]	132	XYN2+C6	SCREW	[M]
101-2	RFKPQTC500NP	SPINDLE MOTOR ASS' Y	[M]	133	RDG0358	ELEVATION GEAR	[M]
101-3	XQN17+CF6	SCREW	[M]	134	RDG0360	MOTOR REDUCTION GEAR(A)	[M]
101-4	XQN17+CF8	SCREW	[M]	135	RDG0361	ELEVATION TRANSMISSION GEAR	[M]
101-5	XQN17+CG45	SCREW	[M]	136	RDG0362	MODE REDUCTION GEAR	[M]
101-6	XQN17+CM25	SCREW	[M]	137	RDG0363	CONVER. REDUCTION GEAR(A)	[M]
102	RFKNQTC500NA	ELEVATION BASE ASS' Y	[M]	138	RDG0364	CONVER. REDUCTION GEAR(B)	[M]
103	RFKNQTC500NB	CLAMP TRIGGER ASS' Y	[M]	139	RDG0365	LOAD GEAR(A)	[M]
104	RFKNQTC500NC	E. SEMICIRCULAR PLATE ASS' Y	[M]	140	RDG0366	LOAD GEAR(B)	[M]
105	RXK0208-2	MECHANISM CHASSIS ASS' Y	[M]	141	RDG0367	M TRAY GEAR	[M]
106	RFKNQTC500NE	CLAMP RACK PLATE ASS' Y	[M]	142	RDG0368	S TRAY GEAR(A)	[M]
107	RFKNQTC500NF	CLAMPER ASS' Y	[M]	143	RDG0369	S TRAY GEAR(B)	[M]
108	RMC0304-1	TRAVERSE SPRING PLATE	[M]	144	RDG0370	S TRAY GEAR(C)	[M]
109	RHD20040	SCREW	[M]	145	RDG0371	MOTOR REDUCTION GEAR(B)	[M]
110	RMC0305-1	CLAMP RACK HOLDER	[M]	146	RDG0372	MODE SELECT GEAR	[M]
111	RMB0480	TRIGGER SPRING	[M]	147	RDK0028	LOAD MAIN GEAR	[M]
112	RMQ0604	SUB TRAY GUIDE(L)	[M]	148	RDK0029	ELEVATION CAM	[M]
113	RMQ0605	SUB TRAY GUIDE(R)	[M]	149	RDK0030	CONVERSION CAM	[M]
114	XQN2+A2	SCREW	[M]	150	RHR33312B	BUSH	[M]
115	XQN2+A25	SCREW	[M]	151	RHW12008	WASHER	[M]
116	XWA2B	WASHER	[M]	152	RHW15002	WASHER	[M]
117	XWE2	WASHER	[M]	153	RHW26008	WASHER	[M]
118	XQN2+AF3	SCREW	[M]	154	RMA0956	ELEVATION GEAR HOLDER	[M]
119	XWA2B	WASHER	[M]	155	RME0213	CONVERSION LEVER SPRING	[M]
120	RXL0137	CONVERSION LEVER UNIT	[M]	156	RME0214	MODE CONTROL SPRING	[M]
121	RXL0138	ELEVATION LEVER UNIT	[M]	157	RME0219	MODE LOCK LEVER SPRING	[M]
122	RMR0996-C	SUB TRAY	[M]	158	RME0222	STOPPER SPRING	[M]
123	RMQ0607	DISC HOLDER	[M]	159	RXQ0500	STEP CAM(L) ASS' Y	[M]
124	RMC0303	SUB TRAY SPRING PLATE	[M]	160	RXQ0499	STEP CAM(R) ASS' Y	[M]
125	RML0448	MAIN TRAY HOOK	[M]	161	RML0445	SUB TRAY HOOK	[M]
126	RMR0995-H	MAIN TRAY	[M]	162	RML0446	MODE CONTROL LEVER	[M]
127	RMR0998-H	MAIN TRAY COVER	[M]	163	RML0447	MODE LOCK LEVER	[M]
128	REM0065	LOADING MOTOR ASS' Y	[M]	164	RML0459	DISC STOPPER	[M]
128-1	RMQ0603	MOTOR ANGLE	[M]	165	RMQ0608	GEAR COVER	[M]
128-2	XYN2+C3	SCREW	[M]	166	RSJ0016-I	PLUNGER	[M]
129	RMM0157-1	CONNECTING LINK PLATE	[M]	167	RFKNLHD70EBN	MECH CHASSIS BRACKET ASS' Y	[M]
				168	RFKNLHD70ECN	DISC SPACER ASS' Y	[M]

## ■ Replacement Parts List (Packing Material / Test Disc / Service Kit)

Notes: \* [M] indicates in Remarks columns parts that are supplied by MESA.

Ref. No.	Part No.	Part Name & Description	Remarks	Ref. No.	Part No.	Part Name & Description	Remarks
		PACKING MATERIAL				<GREASE OR JIG/TOOL>	
P1	RPG3181	PACKING CASE	[M]	SA1	RFKZ0078	SERVICE KIT	[M]
P2	RPN1055	CUSHION	[M]			TEST DISC	
P3	RPQ0742	PAD	[M]	SA2	SZZP1054C	PLAYABILITY TEST DISC	[M]
P4	SPP740	PROTECTION BAG (UNIT)	[M]				

## ■ Packaging

