

AV RECEIVER/AV AMPLIFIER

RX-V559/HTR-5950/DSP-AX559

SERVICE MANUAL

IMPORTANT NOTICE

This manual has been provided for the use of authorized YAMAHA Retailers and their service personnel. It has been assumed that basic service procedures inherent to the industry, and more specifically YAMAHA Products, are already known and understood by the users, and have therefore not been restated.

WARNING: Failure to follow appropriate service and safety procedures when servicing this product may result in personal injury, destruction of expensive components, and failure of the product to perform as specified. For these reasons, we advise all YAMAHA product owners that any service required should be performed by an authorized YAMAHA Retailer or the appointed service representative.

IMPORTANT: The presentation or sale of this manual to any individual or firm does not constitute authorization, certification or recognition of any applicable technical capabilities, or establish a principle-agent relationship of any form.

The data provided is believed to be accurate and applicable to the unit(s) indicated on the cover. The research, engineering, and service departments of YAMAHA are continually striving to improve YAMAHA products. Modifications are, therefore, inevitable and specifications are subject to change without notice or obligation to retrofit. Should any discrepancy appear to exist, please contact the distributor's Service Division.

WARNING: Static discharges can destroy expensive components. Discharge any static electricity your body may have accumulated by grounding yourself to the ground buss in the unit (heavy gauge black wires connect to this buss).

IMPORTANT: Turn the unit OFF during disassembly and part replacement. Recheck all work before you apply power to the unit.

■ CONTENTS

TO SERVICE PERSONNEL	2-3
FRONT PANELS	3-4
REAR PANELS	5-8
REMOTE CONTROL PANELS	9
SPECIFICATIONS / 参考仕様	10-12
INTERNAL VIEW	13
DISASSEMBLY PROCEDURES / 分解手順	14-17
SELF DIAGNOSIS FUNCTION (DIAG) / 自己診断機能(ダイアグ)	18-42
AMP ADJUSTMENT / アンプ部調整	43

DISPLAY DATA	44-47
IC DATA	48-57
PIN CONNECTION DIAGRAM	58-59
BLOCK DIAGRAMS	61-63
PRINTED CIRCUIT BOARDS	64-80
SCHEMATIC DIAGRAMS	81-88
REPLACEMENT PARTS LIST	89-114
REMOTE CONTROL	115
ADVANCED SETUP	116



このサービスマニュアルは、エコマーク認定の再生紙を使用しています。
This Service Manual uses recycled paper.

100997

© 2006 YAMAHA CORPORATION All rights reserved.
This manual is copyrighted by YAMAHA and may not be copied or
redistributed either in print or electronically without permission.



YAMAHA


YAMAHA CORPORATION
P.O.Box 1, Hamamatsu, Japan

06.02

RX-V559/HTR-5950/
DSP-AX559

TO SERVICE PERSONNEL

- 1. Critical Components Information
Components having special characteristics are marked and must be replaced with parts having specifications equal to those originally installed.
- 2. Leakage Current Measurement (For 120V Models Only)
When service has been completed, it is imperative to verify that all exposed conductive surfaces are properly insulated from supply circuits.
- Meter impedance should be equivalent to 1500 ohms shunted by 0.15μF.



- Leakage current must not exceed 0.5mA.
- Be sure to test for leakage with the AC plug in both polarities.



“CAUTION”
“F3000, 3001: FOR CONTINUED PROTECTION AGAINST RISK OF FIRE, REPLACE ONLY WITH SAME TYPE 8A, 125V FUSE.”

CAUTION
F3000, 3001: REPLACE WITH SAME TYPE 8A, 125V FUSE.

ATTENTION
F3000, 3001: UTILISER UN FUSIBLE DE RECHANGE DE MEME TYPE DE 8A, 125V.

WARNING: CHEMICAL CONTENT NOTICE!

The solder used in the production of this product contains LEAD. In addition, other electrical/electronic and/or plastic (where applicable) components may also contain traces of chemicals found by the California Health and Welfare Agency (and possibly other entities) to cause cancer and/or birth defects or other reproductive harm.

DO NOT PLACE SOLDER, ELECTRICAL/ELECTRONIC OR PLASTIC COMPONENTS IN YOUR MOUTH FOR ANY REASON WHATSOEVER!

Avoid prolonged, unprotected contact between solder and your skin! When soldering, do not inhale solder fumes or expose eyes to solder/flux vapor!


If you come in contact with solder or components located inside the enclosure of this product, wash your hands before handling food.

About Lead Free Solder / 無鉛ハンダについて

The P.C.B.s installed in this unit are soldered using the following solder.

本機に搭載されている基板のハンダ付けに使用されているハンダは下記の通りです。

	SIDE A / A面	SIDE B / B面
DSP P.C.B.	lead free solder / 無鉛ハンダ	lead free solder / 無鉛ハンダ
FUNCTION P.C.B.	—	lead free solder / 無鉛ハンダ
OPERATION P.C.B.	—	lead free solder / 無鉛ハンダ
MAIN P.C.B.	—	lead free solder / 無鉛ハンダ
VIDEO P.C.B.	lead free solder / 無鉛ハンダ	lead free solder / 無鉛ハンダ



Among some types of lead free solder currently available, it is recommended to use one of the following types for the repair work.

- Sn + Ag + Cu (tin + silver + copper)
- Sn + Cu (tin + copper)
- Sn + Zn + Bi (tin + zinc + bismuth)

Caution:

1. As the melting point temperature of the lead free solder is about 30°C to 40°C (50°F to 70°F) higher than that of the lead solder, be sure to use a soldering iron suitable to each solder.
2. If lead solder must be used, be sure to remove lead free solder from each terminal section of the parts to be replaced and from the area around it completely before soldering, or make sure that the lead free solder and lead solder melt together fully.

無鉛ハンダにはいくつかの種類がありますが、修理時には下記のような無鉛ハンダの使用を推奨します。


- ・ Sn+Ag+Cu(錫+銀+銅)
- ・ Sn+Cu(錫+銅)
- ・ Sn+Zn+Bi(錫+亜鉛+ビスマス)

注意：


1. 無鉛ハンダの融点温度は通常の鉛入りハンダに比べ30～40℃程度高くなっていますので、それぞれのハンダに合ったハンダごてをご使用ください。
2. 鉛入りハンダを使わざるを得ない場合は、あらかじめ交換する部品端子部やその周辺部の無鉛ハンダをすべて取り除くか、あるいは無鉛ハンダと鉛入りハンダが十分に溶けた状態となるようにハンダ付けしてください。

FRONT PANELS


RX-V559 (U, C models)




RX-V559 (R, T, K, A, G, E, L models)




HTR-5950 (U, C models)






HTR-5950 (T, A models)




DSP-AX559 (J model)




RX-V559 (U, C models)




RX-V559 (K model)




RX-V559 (A model)




RX-V559 (G, E models)




RX-V559 (L model)




HTR-5950 (U, C models)




HTR-5950 (T model)



HTR-5950 (A model)




DSP-AX559 (J model)




■ REMOTE CONTROL PANELS

RAV322



RX-V559 (U, C models)
HTR-5950 (U, C models)

RAV323



RX-V559 (R, T, K, A, G, E, L models)
HTR-5950 (T, A models)
DSP-AX559 (J model)

SPECIFICATIONS / 参考仕様

■ Audio Section / オーディオ部

Minimum RMS Output Power (Power Amp. Section) / 定格出力 (パワーアンプ部)

[RX-V559]

(20 Hz to 20 kHz, 0.06 % THD, 8 ohms)

FRONT L/R	95 W + 95 W
CENTER	95 W
SURROUND L/R	95 W + 95 W
SURROUND BACK	95 W

[HTR-5950]

(1 kHz, 0.7 % THD, 8 ohms)

FRONT L/R	110 W + 110 W
CENTER	110 W
SURROUND L/R	110 W + 110 W
SURROUND BACK	110 W

[DSP-AX559] (J model)

(20 Hz to 20 kHz, 0.09 % THD, 6 ohms)

FRONT L/R	95 W + 95 W
CENTER	95 W
SURROUND L/R	95 W + 95 W
SURROUND BACK	95 W

Maximum Power / 実用最大出力 (EIAJ) (1 kHz, 10 % THD)

[RX-V559/HTR-5950] (R, T, K, L models)

FRONT L/R (8 ohms)	135 W
CENTER (8 ohms)	135 W
SURROUND L/R (8 ohms)	135 W
SURROUND BACK (8 ohms)	135 W

[DSP-AX559] (J model)

FRONT L/R (6 ohms)	135 W
CENTER (6 ohms)	135 W
SURROUND L/R (6 ohms)	135 W
SURROUND BACK (6 ohms)	135 W

Maximum Power Per Channel / MAXパワー (SP IMPEDANCE SET: 8 ohms Minimum/1 kHz, 0.7 % THD 4ohms)

[RX-V559/HTR-5950] (G, E models)

FRONT L/R	145 W + 145 W
CENTER	145 W
SURROUND L/R	145 W + 145 W
SURROUND BACK	145 W

IEC Power / IECパワー (1 kHz, 0.06 % THD 8ohms)

[RX-V559/HTR-5950] (G, E, L models)

FRONT L/R	105 W + 105 W
-----------------	---------------

Dynamic Power Per Channel / ダイナミックパワー (IHF)

[RX-V559/HTR-5950]

FRONT L/R (8/6/4/2 ohms)	130/165/195/240 W
--------------------------------	-------------------

[DSP-AX559] (J model)

FRONT L/R (-/6/4/2 ohms)	-/135/165/210 W
--------------------------------	-----------------

Dynamic Headroom / ダイナミックヘッドルーム (8 ohms)

[RX-V559/HTR-5950] (U, C models)

.....	1.6 dB
-------	--------

Damping Factor / ダンピングファクタ

FRONT L/R (20 Hz to 20 kHz, SPEAKER-A)	120 or more
--	-------------

Input Sensitivity/Input Impedance / 入力感度/入力インピーダンス

CD, etc.	200 mV / 47 k-ohms
---------------	--------------------

MULTI CH IN

FRONT L/R, CENTER, SURROUND L/R, SUBWOOFER	200 mV / 47 k-ohms
--	--------------------

Maximum Input Signal Level / 最大許容入力 (1 kHz, 0.5% THD)

CD, etc. (Effect On)	2.2 V or more
----------------------------	---------------

Output Level/Output Impedance / 出力電圧/出力インピーダンス

REC OUT	200 mV / 1.2 k-ohms
---------------	---------------------

SUBWOOFER (2ch STEREO & FRONT SP: Small)

.....	4 V / 1.2 k-ohms
-------	------------------

[RX-V559/DSP-AX559]

ZONE2 OUT	200 mV / 1.2 k-ohms
-----------------	---------------------

Headphone Jack Rated Output/Impedance / ヘッドフォン出力/出力インピーダンス

CD, etc. (1 kHz, 50 mV, 8 ohms)	150 mV / 100 ohms
---------------------------------------	-------------------

Frequency Response / 周波数特性

CD, etc. to FRONT L/R (10 Hz to 100 kHz)	+0/-3.0 dB
--	------------

Total Harmonic Distortion / 全高調波歪率 (50 W, 8 ohms)

CD, etc. (2ch STEREO) to FRONT L/R SP OUT	0.06 % or less
--	----------------

Signal to Noise Ratio / 信号対雑音比 (IHF-A Network)

CD, etc. (Input shorted) SP OUT	
---------------------------------	--

250 mV	100 dB or more
--------------	----------------

Residual Noise / 残留ノイズ (IHF-A Network)

FRONT L/R SP OUT	150 μ V or less
------------------------	---------------------

Channel Separation / チャンネルセパレーション

CD, etc. (Input 5.1 k-ohms shorted, 1 kHz/10 kHz)

..... 60 dB or more/45 dB or more

Tone Control Characteristics / トーンコントロール特性

BASS

Boost/Cut

TREBLE

Boost/Cut

Filter Characteristics / フィルター特性

FRONT L/R, CENTER, SURROUND L/R, SURROUND BACK SP

Small (H.P.F.)

..... fc= 40/60/80/90/100/110/120/160/200 Hz / 12 dB/oct.

SUBWOOFER (L.P.F.)

..... fc= 40/60/80/90/100/110/120/160/200 Hz / 24 dB/oct.

■ Video Section / ビデオ部

Video Signal Type (Gray Back) / ビデオ信号方式 (グレイバック)

U, C, R, K, J models

T, A, G, E, L models

Video Signal Type (Video Conversion) / ビデオ信号方式 (ビデオコンバージョン)

U, C, R, T, K, A, G, E, L, J models

Composite Video Signal Level / コンポジットビデオ信号

..... 1 Vp-p / 75 ohms

S-Video Signal Level / Sビデオ信号

Y

C

Component Signal Level / コンポーネントビデオ信号

Y

Cb/Cr

D4-Video Signal Level / D4端子ビデオ信号 (J model)

Y

Cb/Cr

Video Maximum Input Level / ビデオ最大許容入力

VIDEO CONV. OFF

Signal to Noise Ratio / 信号対雑音比

..... 50 dB or more

Monitor Out Frequency Response / モニターアウト周波数帯域

(VIDEO CONV. OFF)

Component video signal level

D4-video signal level (J model)

■ FM Section / FM部

Tuning Range / 受信周波数範囲

U, C models

R, L models

T, K, A, G, E models

J model

50 dB Quieting Sensitivity / 50 dB SN感度 (IHF) (1 kHz, 100 % Mod.)

Mono / Stereo

Usable Sensitivity / 実用感度 (IHF)

Mono

Selectivity / 選択度 (at 400 kHz)

..... 70 dB

Signal to Noise Ratio / 信号対雑音比 (IHF)

Mono / Stereo

Harmonic Distortion / 歪率 (1 kHz)

Mono/Stereo

Stereo Separation / ステレオセパレーション

1 kHz

Frequency Response / 周波数特性

20 Hz to 15 kHz

Antenna Input / アンテナ入力

..... 75 ohms unbalanced

■ AM Section / AM部

Tuning Range / 受信周波数範囲

U, C models

R, L models

T, K, A, G, E, J models

Usable Sensitivity / 実用感度

..... 300 μ V/m

Antenna / アンテナ入力

..... Loop antenna

■ General / 総合

Power Supply / 電源電圧	
R, C models	AC 120 V, 60 Hz
T model	AC 110/120/220/230/240 V, 50/60 Hz
K model	AC 220 V, 50 Hz
A model	AC 220 V, 60 Hz
G, E models	AC 230 V, 50 Hz
L model	AC 220/230-240 V, 50/60 Hz
J model	AC 100V, 50/60 Hz
Power Consumption / 消費電力	
U, C models	350 W / 440 VA
R, T, K, A, G, E, L models	360 W
J model	250 W
Standby Power Consumption (reference data) / 待機時消費電力 (参考値)	
.....	0.1 W
Maximum Power Consumption (R model)	
6ch Drive, 10 % THD	100 W max. total
2 Switched Outlets	50 W max. total
U, C, T, J models	100 W max.
R, G, E, L models	100 W max.
A model	100 W max.
Dimensions / 寸法 (W x H x D)	
[RX-V559/DSP-AX559]	 435 x 171 x 393.2 mm (17-1/8" x 6-3/4" x 15-1/2")
[HTR-5950]	 435 x 161 x 393.2 mm (17-1/8" x 6-5/16" x 15-1/2")
Weight / 質量	
[RX-V559/DSP-AX559]	 11.0 kg (24 lbs. 4 oz.)
[HTR-5950]	 10.5 kg (23 lbs. 2 oz.)
Finish / 仕上げ	
[RX-V559]	Gold color
Black color	 R, T, K models
Titanium color	 U, C, R, A, G, E models
[HTR-5950]	Gold color
Black color	 T model
Silver color	 U, C models
[DSP-AX559]	Gold color
Accessories / 付属品	
Remote control x 1, Batteries x 2, Indoor FM antenna x 1, AM loop antenna x 1	 J model

* Specifications are subject to change without notice due to product improvements.

※ 参考仕様および外観は予告なく変更されることがあります。

U	U.S.A. model	C	Canadian model
R	General model	T	Chinese model
K	Korean model	E	Australian model
G	European model	J	South European model
L	Singapore model		



Manufactured under license from Dolby Laboratories. "Dolby", "Pro Logic", and the double-D symbol are trademarks of Dolby Laboratories.

ドルビーラトリリーズからの実施権により製造されています。「ドルビー」、「PRO LOGIC」、「Surround EX」およびダブルD記号は、ドルビーラトリリーズの商標です。



Manufactured under license from Digital Theater Systems, Inc. "DTS", "DTS-ES", "NEO6", and "DTS 96/24" are trademarks of Digital Theater Systems, Inc. Copyright 1996, 2003 Digital Theater Systems, Inc. All right reserved. DTS, DTS-ES Extended Surround, NEO.6およびDTS96/24はデジタルシアターシステムズの登録商標です。

"iPod" is a trademark of Apple Computer, Inc., registered in the U.S. and other countries.

iPodは、米国およびその他の国々で登録されたApple Computer, Inc.の商標または登録商標です。



"SILENT CINEMA" is a trademark of YAMAHA CORPORATION. 「サイレントシネマ SILENT CINEMA」はヤマハ株式会社の登録商標です。



READY The XM name and related logos are registered trademarks of XM Satellite Radio Inc.




Neural Surround™ name and related logos are trademarks owned by Neural Audio Corporation.



AACロゴマークはドルビーラトリリーズの商標です。


• DIMENSIONS / 寸法図




BASIS SETUP				
CATEGORY	MAIN MENU	SUB MENU	SELECT MENU	
MANUAL SETUP	1 SOUND MENU	A) SPEAKER SET	FRONT	: LARGE
			CENTER	: SML
			SURROUND L/R	: SML
			SURROUND BACK	: SML
			PRESENCE	: NONE
		B) SPEAKER LEVEL	FRONT L	: 10.0ft
			FRONT R	: 10.0ft
			CENTER	: 10.0ft
			SURR L	: 10.0ft
			SURR R	: 10.0ft
C) SP DISTANCE	UNIT	: feet / meters		
	FRONT L	: 10.0ft		
	FRONT R	: 10.0ft		
	CENTER	: 10.0ft		
	SURR L	: 10.0ft		
2 INPUT MENU	A) I/O ASSIGNMENT	CMPT-V INPUT [A]	: DTV / DTV/CBL / V-AUX / VCR / DVR	
		CMPT-V INPUT [B]	: DTV / DTV/CBL / V-AUX / VCR / DVR	
		CMPT-V INPUT [C]	: DTV / DTV/CBL / V-AUX / VCR / DVR	
		OPTICAL OUT (1)	: PHONO / CD / [MD/CD-R] / DVD / DTV/CBL / V-AUX / VCR / DVR	
		OPTICAL IN (2)	: PHONO / CD / [MD/CD-R] / DVD / DTV/CBL / V-AUX / VCR / DVR	
	B) INPUT MODE	OPTICAL IN (3)	: PHONO / CD / MD/CD-R / [DVD] / DTV/CBL / V-AUX / VCR / DVR	
		OPTICAL IN (4)	: PHONO / CD / MD/CD-R / DVD / [DTV/CBL] / V-AUX / VCR / DVR	
		COAXIAL IN (5)	: PHONO / [CD] / MD/CD-R / DVD / DTV/CBL / V-AUX / VCR / DVR	
		[LAST]		
		C) INPUT RENAME		
3 OPTION MENU	A) DISPLAY SET	DIMMER	: 0	
		VIDEO CONV.	: ON	
		OSD SHIFT	: 0	
		GRAY BACK	: AUTO	
		MEMORY GUARD	: OFF	
	B) MEMORY GUARD	[OFF] / NO		
		STEREO / MUSIC / ENTERTAINMENT / MOVIE THEATER / STANDARD		
		[FRONT] / ZONE B		
		[10S] / 30S / OFF		
		0% to 100 % / [NONE]		
BASIS SETUP	ROOM	S / [M] / L	VALUE [INITIAL]	
	SUBWOOFER	[YES] / NONE		
	SPEAKER	2spk / 3spk / 4 spk / 5spk / [6spk]		
	SETUP	OK / CANCEL		
	CHECK OK?	YES / NO		

■ INTERNAL VIEW


• RX-V559, DSP-AX559



- ❶ OPERATION (4) P.C.B.
- ❷ FUNCTION (2) P.C.B.
- ❸ FUNCTION (3) P.C.B. (R, L models)
- ❹ DSP P.C.B.
- ❺ MAIN (5) P.C.B.
- ❻ MAIN (4) P.C.B.
- ❼ VIDEO P.C.B.
- ❽ Tuner
- ❾ FUNCTION (1) P.C.B.
- ❿ MAIN (1) P.C.B.
- ⓫ FUNCTION (4) P.C.B.
- ⓬ MAIN (2) P.C.B.
- ⓭ Power Transformer
- ⓮ OPERATION (5) P.C.B.
- ⓯ OPERATION (1) P.C.B.
- ⓰ OPERATION (6) P.C.B.
- ⓱ OPERATION (3) P.C.B.
- ⓲ OPERATION (2) P.C.B.



• HTR-5950



- ❶ OPERATION (4) P.C.B.
- ❷ FUNCTION (2) P.C.B.
- ❸ DSP P.C.B.
- ❹ MAIN (5) P.C.B.
- ❺ MAIN (4) P.C.B.
- ❻ VIDEO P.C.B.
- ❼ Tuner
- ❽ FUNCTION (1) P.C.B.
- ❾ MAIN (1) P.C.B.
- ❿ FUNCTION (4) P.C.B.
- ⓫ OPERATION (5) P.C.B.
- ⓬ OPERATION (6) P.C.B.
- ⓭ MAIN (2) P.C.B.
- ⓮ OPERATION (1) P.C.B.
- ⓯ Power Transformer
- ⓰ OPERATION (3) P.C.B.

RX-V559/DSP-AX559**DISASSEMBLY PROCEDURES / 分解手順**

(Remove parts in the order as numbered.)

Disconnect the power cable from the AC outlet.

(番号順に部品を取り外してください。)

AC電源コンセントから、電源コードを抜いてください。

1. Removal of Top Cover

- a. Remove 4 screws (①), 5 screws (②) and 1 screw (③). (Fig. 1)
- b. Slide the Top Cover rearward to remove it. (Fig. 1)

1. トップカバーの外し方

- a. ①のネジ4本、②のネジ5本、③のネジ1本を外します。(Fig. 1)
- b. トップカバーを後方へスライドさせ、取り外します。(Fig. 1)

2. Removal of Front Panel Unit

- a. Remove 2 Knobs. (Fig. 1)
- b. Remove 1 screw (④) and then remove the Support Top. (Fig. 1)
- c. Remove 6 screws (⑤). (Fig. 1)
- d. Remove the Front Panel Unit. (Fig. 1)

2. フロントパネルユニットの外し方

- a. ノブを2個取り外します。(Fig. 1)
- b. ④のネジ1本を外し、サポートトップを取り外します。(Fig. 1)
- c. ⑤のネジ6本を外します。(Fig. 1)
- d. フロントパネルユニットを取り外します。(Fig. 1)

3. Removal of Plate Side

- a. Remove 2 push rivets (⑥). (Fig. 1)
- b. Remove the Plate Side L/R. (Fig. 1)

3. プレートサイドL/Rの外し方


- a. ⑥のプッシュリベット2本を外します。(Fig. 1)
- b. プレートサイドL/Rを取り外します。(Fig. 1)

4. Removal of Sub Chassis Unit

- a. Remove 2 screws (⑦) and then slide the Sub Chassis Unit forward. (Fig. 1)
- b. Remove a push rivet (⑧). (Fig. 1)
- c. Remove the Barrier/FFC. (Fig. 1)
- d. Remove CB5, CB203, CB205 and CB312. (Fig. 1)
- e. Remove the Sub Chassis Unit. (Fig. 1)

4. サブシャーシユニットの外し方

- a. ⑦のネジ2本を外し、サブシャーシユニットを前方に引き出します。(Fig. 1)
- b. ⑧のプッシュリベット1本を外します。(Fig. 1)
- c. バリアー/FFCを取り外します。(Fig. 1)
- d. CB5、CB203、CB205、CB312を外します。(Fig. 1)
- e. サブシャーシユニットを取り外します。(Fig. 1)

**Fig. 1**

5. Removal of FUNCTION (1) P.C.B.

- Remove 2 screws (⑧). (Fig. 2)
- Remove 8 screws (⑩). (Fig. 4)
- Remove CB200-202, CB204, CB206 and CB207. (Fig. 2)
- Remove the FUNCTION (1) P.C.B.. (Fig. 2)

5. FUNCTION(1) P.C.B.の外し方

- ⑧のネジ2本を外します。(Fig. 2)
- ⑩のネジ8本を外します。(Fig. 4)
- CB200～202、CB204、CB206、CB207を外します。(Fig. 2)
- FUNCTION(1) P.C.B.を取り外します。(Fig. 2)

6. Removal of DSP P.C.B.

- Remove 2 screws (⑪). (Fig. 2)
- Remove 7 screws (U, C models) / 6 screws (R, T, K, A, G, E, L, J models) (⑫). (Fig. 4)
- Remove CB2-4, CB9 and CB57. (Fig. 2)
- Remove the DSP P.C.B.. (Fig. 2)

6. DSP P.C.B.の外し方

- ⑪のネジ2本を外します。(Fig. 2)
- ⑫のネジ6本を外します。(Fig. 4)
- CB2～4、CB9、CB57を外します。(Fig. 2)
- DSP P.C.B.を取り外します。(Fig. 2)

7. Removal of VIDEO P.C.B.

- Remove 1 push rivet (⑬). (Fig. 3)
- Remove 6 screws (⑭). (Fig. 4)
- Remove CB401 and CB402. (Fig. 3)
- Remove the VIDEO P.C.B.. (Fig. 3)

7. VIDEO P.C.B.の外し方

- ⑬のプッシュリベット1本を外します。(Fig. 3)
- ⑭のネジ6本を外します。(Fig. 4)
- CB401、CB402を外します。(Fig. 3)
- VIDEO P.C.B.を取り外します。(Fig. 3)

Fig. 2




Fig. 2




Fig. 3

8. Removal of FUNCTION (2) P.C.B.

- Remove 1 push rivet (⑮). (Fig. 3)
- Remove 5 screws (⑯). (Fig. 4)
- Remove the FUNCTION (2) P.C.B.. (Fig. 3)

8. FUNCTION(2) P.C.B.の外し方

- ⑮のプッシュリベット1本を外します。(Fig. 3)
- ⑯のネジ5本を外します。(Fig. 4)
- FUNCTION(2) P.C.B.を取り外します。(Fig. 3)

9. Removal of TUNER

- Remove 3 screws (⑰). (Fig. 4)
- Remove the TUNER. (Fig. 5)

9. TUNERの外し方

- ⑰のネジ3本を外します。(Fig. 4)
- TUNERを取り外します。(Fig. 5)

10. Removal of MAIN (1), (2), (4) and (5) P.C.B.s

- Remove the Airbase/P.C.B.. (Fig. 5)
- Remove 2 screws (⑱), 1 screw (⑲), 2 screws (⑳) and 1 screw (㉑). (Fig. 5)
- Remove 5 screws (㉒). (Fig. 4)
- Remove CB103, CB104 and CB105 (U, C models). (Fig. 3)
- Remove MAIN (1), (2), (4) and (5) P.C.B.s together with the Heat Sink. (Fig. 5)

10. MAIN(1), (2), (4), (5) P.C.B.の外し方

- アールベース/PCBを取り外します。(Fig. 5)
- ⑱のネジ2本、⑲のネジ1本、⑳のネジ2本、㉑のネジ1本を外します。(Fig. 5)
- ㉒のネジ5本を外します。(Fig. 4)
- CB103、CB104を外します。(Fig. 3)
- MAIN(1)、(2)、(4)、(5) P.C.B.をヒートシンクと一緒に取り外します。(Fig. 5)




Fig. 4




Fig. 5

When checking the P.C.B.:

- Put a Cloth over the equipment. Put the P.C.B.s together with the Heat Sink upright on the Cloth and check them. (Fig. 6)
- Reconnect all cables (connectors) that have been disconnected.
- When connecting the flat cable, use care for the polarity.
- The P.C.B. removed from the chassis does not work because its grounding is loose. Be sure to connect the ground of Rear Panel, MAIN (1) P.C.B. (G1001) and OPERATION (4) P.C.B. (G3001) to the chassis with a ground lead or the like. (Fig. 6)

P.C.B.チェックする場合

- 布を敷きます。その上にP.C.B.をヒートシンクと一緒に立ててチェックします。(Fig. 6)
- 外したケーブル(コネクタ)をすべて接続してください。
- フラットケーブルを接続する際、極性に注意してください。
- シャーシから外したP.C.B.はアースが浮いて動作しませんので、MAIN(1)P.C.B.(G1001)、OPERATION(4)P.C.B.(G3001)のアースをリード線等でシャーシまたはGNDに接続してください。(Fig. 6)




Fig. 6

HTR-5950

DISASSEMBLY PROCEDURES

(Remove parts in the order as numbered.)

Disconnect the power cable from the AC outlet.

1. Removal of Top Cover

- Remove 4 screws (1), 5 screws (2) and 1 screw (3). (Fig. 1)
- Slide the Top Cover rearward to remove it. (Fig. 1)

2. Removal of Front Panel Unit

- Remove 6 screws (4). (Fig. 1)
- Remove a push rivet (5). (Fig. 1)
- Remove the Barrier/FFC. (Fig. 1)
- Remove CB5, CB203, CB205 and CB310. (Fig. 1)
- Remove the Front Panel Unit. (Fig. 1)




Fig. 1




Fig. 2

4. Removal of DSP P.C.B.

- Remove 2 screws (⑥). (Fig. 2)
- Remove 7 screws (U, C models) / 6 screws (T, A models) (③). (Fig. 4)
- Remove CB2-4, CB9 and CB57. (Fig. 2)
- Remove the DSP P.C.B.. (Fig. 2)

5. Removal of VIDEO P.C.B.

- Remove 1 push rivet (⑩). (Fig. 3)
- Remove 6 screws (⑪). (Fig. 4)
- Remove CB401 and CB402. (Fig. 3)
- Remove the VIDEO P.C.B.. (Fig. 3)

6. Removal of FUNCTION (2) P.C.B.

- Remove 1 push rivet (⑫). (Fig. 3)
- Remove 5 screws (⑬). (Fig. 4)
- Remove the FUNCTION (2) P.C.B.. (Fig. 3)

7. Removal of TUNER

- Remove 3 screws (⑭). (Fig. 4)
- Remove the TUNER. (Fig. 5)




Fig. 3




Fig. 4

8. Removal of MAIN (1), (2), (4) and (5) P.C.B.s

- Remove the Airbase/P.C.B.. (Fig. 5)
- Remove 2 screws (⑮), 1 screw (⑯), 2 screws (⑰) and 1 screw (⑱). (Fig. 5)
- Remove 5 screws (⑲). (Fig. 4)
- Remove CB103, CB104 and CB105 (U, C models). (Fig. 3)
- Remove MAIN (1), (2), (4) and (5) P.C.B.s together with the Heat Sink. (Fig. 5)




Fig. 5

When checking the P.C.B.:

- Put a Cloth over the equipment. Put the P.C.B.s together with the heat sink upright on the Cloth and check them. (Fig. 6)
- Reconnect all cables (connectors) that have been disconnected.
- When connecting the flat cable, use care for the polarity.
- The P.C.B. removed from the chassis does not work because its grounding is loose. Be sure to connect the ground of Rear Panel, MAIN (1) P.C.B. (G1001) and OPERATION (4) P.C.B. (G3001) to the chassis with a ground lead or the like.




Fig. 6

■ SELF DIAGNOSIS FUNCTION (DIAG)/自己診断機能 (ダイアグ)

This unit has self diagnosis functions that are intended for inspection, measurement and location of faulty point.

There are 23 DIAG menu items, each of which has sub-menu items.

Listed in the table below are menu items and sub-menu items.

Note that not all menu items listed will apply to the models covered in this service manual.

本機には、検査、測定、不良箇所の発見を目的にした自己診断機能(ダイアグ)があります。

ダイアグメニューは23個あり、それぞれにサブメニューがあります。(ダイアグのメニュー操作は本体で行います。) 下表はメニュー一覧です。

下表の全メニュー項目が、このサービスマニュアル記載のモデルに適用されるとは限りません。


No.	MAIN MENU	SUB MENU
1	BYPASS	1. ANALOG BYPASS 2. DSP BYPASS
2	RAM THR	1. RAM MARGIN 2. RAM FULL BIT
3	PRO LOGIC	1. Pro Logic
4	SPEAKERS SET	1. FRONT : SMALL 0dB 2. CENTER : NONE 3. LFE/B : FRNT 4. Pres Mix : 5ch 5. Front GAIN 1 6. Front GAIN 2 7. SURR B Check
5	XCH-INPUT	1. XCH INPUT 6 2. XCH INPUT 8 3. LIMIT SET (Not applied to these models / このモデルには適用されません)
6	MIC CHECK (Not applied to these models / このモデルには適用されません)	1. MIC CHECK --dB
7	DISPLAY CHECK	1. STRAIGHT (Initial display) 2. VFD DISP OFF / OSD OFF 3. VFD DISP ALL / OSD CHARACTER PATTERN 4. VFD DIMMER / OSD CHARACTER PATTERN 5. CHECK PATTERN / OSD CHARACTER PATTERN
8	MANUAL TEST	1. TEST ALL 2. TEST FRNT L 3. TEST CENTER 4. TEST FRNT R 5. TEST SURR R 6. TEST SB R (Not applied to these models / このモデルには適用されません) 7. TEST SBL 8. TEST SURR L 9. TEST PRES L (Not applied to these models / このモデルには適用されません) 10. TEST PRES R (Not applied to these models / このモデルには適用されません) 11. TEST LFE 1. PRESET INHI (memory initialization inhibited) 2. PRESET RSRV (memory initialized) 1. PS1/PS2 2. DC/TH 3. IMP SW/POWER LIMITER DISP 4. PANEL KEY
9	FACTORY PRESET	1. I2C Read Check 2. DIGITAL THR CVBS 3. DIGITAL THR Y/C 4. ANALOG BYPASS
10	AD DATA CHECK	5. TEST PATTERN 6. LOOP BACK CVBS (Not applied to these models / このモデルには適用されません) 7. LOOP BACK Y/C (Not applied to these models / このモデルには適用されません)
11	VIDEO	1. 1k -1dB / 44.1k 2. 1k -61dB / 44.1k 3. Mute / 44.1k 4. XM Tone / 44.1k 5. ISO Tone / 44.1k 6. 1k -1dB / 32k 7. 1k -61dB / 32k 8. Mute / 32k
12	XM STATUS (U/C models)	

No.	MAIN MENU	SUB MENU
		9. XM Tone / 32k 10. ISO Tone / 32k 11. XM / DT Bus Power : OFF
13	iPod	1. DOCK : OK/NG
16	IF STATUS	1. DSP STATUS (5Byte) 2. DECODE MODE (2Byte) (Not applied to these models / このモデルには適用されません) 3. DIR INFO (5Byte) (Not applied to these models / このモデルには適用されません) 4. Pc (2Byte) (Not applied to these models / このモデルには適用されません) 5. CHS 1 (5Byte) (Not applied to these models / このモデルには適用されません) 6. CHS 2 (1Byte) (Not applied to these models / このモデルには適用されません) 7. DEC INFO (5Byte) (Not applied to these models / このモデルには適用されません) 8. BSI 1 (5Byte) (Not applied to these models / このモデルには適用されません) 9. BSI 2 (5Byte) (Not applied to these models / このモデルには適用されません) 10. BSI 3 (5Byte) (Not applied to these models / このモデルには適用されません) 11. BSI 4 (5Byte) (Not applied to these models / このモデルには適用されません) 12. BSI 5 (5Byte) (Not applied to these models / このモデルには適用されません) 13. BSI 6 (5Byte) (Not applied to these models / このモデルには適用されません) 14. BSI 7 (5Byte) (Not applied to these models / このモデルには適用されません) 15. BSI 8 (1Byte) (Not applied to these models / このモデルには適用されません) 16. Mute Trigger (5Byte) (Not applied to these models / このモデルには適用されません) 17. Digital Info (5Byte) (Not applied to these models / このモデルには適用されません)
17	DSP BUS CHECK	1. TI (DSP) BUS CHECK 2. RDS IC CHECK
18	SWFR CUT OFF (Not applied to these models / このモデルには適用されません)	1. L CUT OFF 2. H CUT OFF
19	PROTECTION SETTING (Not applied to these models / このモデルには適用されません)	1. PS L 2. PS H 3. DC L 4. DC H 5. TEMP 6. PL J 8 L 7. PL J 8 H 8. PL U 8 L 9. PL U 8 H 10. PL U N L 11. PL U N H 12. PL G 8 L 13. PL G 8 H 14. PL G N L 15. PL G N H
20	PROTECTION HISTORY	1. HISTORY 1 2. HISTORY 2 3. HISTORY 3 4. HISTORY 4
21	SOFT SW	1. SW MODE : PCB/MODEL/FNC 2. MODEL : 759SE-5935 3. DEST. : JUC/R/T/K/A/BGE/L 4. TUNER DEST : JUC/ATK/BG/RL 5. TUNER TYPE : NRW/RDS/XM 6. VIDEO FORMAT : NTSC/PAL 7. ZONE2 EXIST : EXIST/NOT 8. AAC EXIST : EXIST/NOT 9. TUNER EXIST : EXIST/NOT 10. ZONE2 AMP EXIST : EXIST/NOT 11. OSD EXIST : EXIST/NOT 12. YPAO EXIST : EXIST/NOT
22	ROM VER / SUM / PORT	1. MICROPROCESSOR VERSION 2. SUM ALL / PROGRAM 3. OPE / DSP / XM VERSION 4. PORT 5. TI (DSP) FLASH VERSION 6. TI (DSP) FLASH SUM 7. EEPROM SUM
23	TI (DSP) BOOT (Not applied to these models / このモデルには適用されません)	1. TI (DSP) FLASH BOOT

• Starting DIAG

Press the “MASTER ON/OFF” (RX-V559/DSP-AX559 models) / “STANDBY/ON” (HTR-5950 model) key while simultaneously pressing those two keys of the main unit as indicated in the figure below.

Keys of main unit / 本体キー



Turn on the power while pressing these keys.
これらのキーを同時に押しながら、パワーオンする。



RX-V559/DSP-AX559 models

HTR-5950 model

• Starting DIAG in the protection cancel mode

If the protection function works and causes hindrance to trouble diagnosis, cancel the protection function as described below, and it will be possible to enter the DIAG mode. (The protection functions other than the excess current detect function will be disabled.)

Press the “MASTER ON/OFF” (RX-V559/DSP-AX559 models) / “STANDBY/ON” (HTR-5950 model) key while simultaneously pressing those two keys indicated in the figure above. At this time, keep pressing those two keys for 3 seconds or longer.

In this mode, the “SLEEP” segment of the FL display of the main unit flashes to indicate that the mode is DIAG mode with the protection functions disabled.

CAUTION!

Using this product with the protection function disabled may cause damage to itself. Use special care for this point when using this mode.

• Canceling DIAG

- ① Before canceling DIAG, execute setting for FACTORY PRESET of DIAG menu No.9 (Memory initialization inhibited or Memory initialized).
 - * In order to keep the user memory stored, be sure to select PRESET INHIBITED (Memory initialization inhibited).
- ② Turn off the power by pressing the “MASTER ON/OFF” (RX-V559/DSP-AX559 models) / “STANDBY/ON” (HTR-5950 model) key of the main unit.

● ダイアグの起動

本体の下図に示すキーを同時に押しながら “MASTER ON/OFF” キーを押すと、ダイアグが起動します。

● プロテクション解除モードでの起動

プロテクションが動作することにより、故障箇所の診断に支障をきたすような場合は、次の方法によりプロテクションを解除した状態でダイアグモードに入ることができます。(過電流検出以外のプロテクション動作を解除する)

上図のキーを同時に押しながら “MASTER ON/OFF” キーを押します。このとき、上図のキーを3秒以上押し続けてください。このモードでは本体FLの “SLEEP” セグメントが点滅し、プロテクションを解除した状態でのダイアグモードであることを知らせます。

注意！

プロテクションを解除した状態でのダイアグモードは、危険な状態でもプロテクションが作動しないため、動作させると、機器を破壊することがあります。このモードを使用する場合は十分注意してください。

● ダイアグの解除

- ① ダイアグを解除する前に、ダイアグメニューNo.9の FACTORY PRESET (メモリーの初期化禁止/またはメモリーの初期化)の設定をします。
 - ※ ユーザーメモリーを保持したい場合は、必ずPRESET INHIBITED (メモリー初期化禁止)を選択してください。
- ② 本体の “MASTER ON/OFF” キーを押し、パワーオフにします。

● Display provided when DIAG started

When the monitor is connected, DIAGNOSTIC MENU appears on its screen as shown in the figure.

On the FL display of the main unit, an opening message (including the version and the protection history) appears for a few seconds followed by the diagnostic menu display (1. ANALOG BYPASS).

1.BYPASS	13.DOCK TEST
2.RAM THR	[14.Net]
3.PRO LOGIC	[15.DAB]
4.SP SET	16.IF STATUS
5.XCH INPUT	17.DSP BUS
6.MIC CHECK	18.SWF C. OFF
7.VFD CHECK	19.PRT SET
8.MAN'L TEST	20.PRT HIST
9.PRESET	21.SOFT SW
10.AD CHECK	22.VER/SUM/P
11.VC STATUS	23.TI BOOT
12.XM TEST	


● ダイアグ起動時の表示

モニターを接続してある場合は、モニターの画面に図のようにダイアグメニューが表示されます。

本体FLディスプレイには、オープニング(プロテクション履歴／バージョン)が表示され、数秒後にダイアグメニュー表示(1. ANALOG BYPASS)となります。

When there is no history of protection function:

プロテクション履歴が無い場合：



When there is a history of protection function:

プロテクション履歴がある場合：

The FL display appears as shown below depending on the type of the protection function.

プロテクションの種類によって下記の表示が現れます。

The protection function worked due to excessive current through the amplifier. Causes could be a short at the speaker terminal or a defect in the amplifier. The protection function activates immediately to turn off the power, with no history display at turn-on, if the amplifier is defective.

I PROTECT A

スピーカーをショートさせた時などが原因で、プロテクションが働いたことを示します。

The protection function worked due to a defect or overload in the power supply. If the power is turned on with the abnormality unsolved, the protection function works in about 1 second to turn off the power.

PS1 PRT:000 A
or
PS2 PRT:000 A

電源電圧による原因で、プロテクションが働いたことを示します。異常状態のままパワーオンすると、約1秒後にプロテクションが掛かり、電源が切れます。

The protection function worked due to a DC voltage appearing at the speaker terminal. A cause could be a defect in the amplifier. If the power is turned on with the abnormality unsolved, the protection function works in about 3 seconds to turn off the power.

DC PRT:000 A

アンプの故障でスピーカーに直流電圧が掛かるなどが原因で、プロテクションが働いたことを示します。異常状態のままパワーオンすると、約3秒後にプロテクションが掛かり、電源が切れます。

The protection function worked due to the temperature limit being exceeded. Causes could be poor ventilation or a defect related to the thermal sensor. If the power is turned on with the abnormality unsolved, the protection function works in about 1 second to turn off the power.

TMP PRT:000 A

温度制限を越えた原因で、プロテクションが働いたことを示します。異常状態のままパワーオンすると、約1秒後にプロテクションが掛かり、電源が切れます。

For detection of each protection function (except I-PROTECT) , refer to DIAG MENU No.10 AD DATA.

各プロテクションの検出に関しては、後述のダイアグメニュー No. 10 AD DATAを参照してください。

History of protection function

When the protection function has worked, its history is stored in memory with a backup. Even if no abnormality is noted while servicing the unit, an abnormality which has occurred previously can be defined as long as the backup data has been stored.

The history of the protection function is cleared when DIAG is cancelled by selecting PRESET RESERVED (Memory initialized) of DIAG menu No.9 or when the backup data is erased.

プロテクションの履歴

プロテクションが働いた場合、履歴をバックアップして記憶しています。サービスのときに異常が認められなくても、バックアップが残っていれば、お客様のところで起きた異常を区別できます。

ダイアグメニュー No.9 で PRESET RESERVED (メモリーの初期化) を選んでダイアグを解除した場合、またはバックアップが消えた場合に、プロテクションの履歴はクリアされます。

• Display during menu operation

During the DIAG operation, the menu list described in the section of the startup screen appears on the monitor screen and the function at work is indicated on the FL indicator. The contents displayed during the function operation are described later in the “Details of DIAG menu” section.

● メニュー動作中の表示

ダイアグ中、モニター画面には起動画面の項で説明したメニュー一覧が表示されます。本体のFL ディスプレイには動作中の機能が表示されます。機能動作中の表示内容については、後述の機能詳細で記述します。

• Operation procedure of DIAG menu and SUB-MENU

There are 23 MENU items, each of which has some SUB-MENU items.

DIAG menu selection

Main unit: Select the menu using the PROGRAM knob (RX-V559/DSP-AX559) or ▷ (Forward) and ◁ (Reverse) keys of PROGRAM (HTR-5950).

SUB-MENU selection

Main unit: Select the sub-menu using ▷ (Forward) and ◁ (Reverse) keys of PRESET/TUNING.

● ダイアグメニューとサブメニューの操作

ダイアグにはNo.1～23のメニューがあり、そのそれぞれにサブメニューがあります。


ダイアグメニューの選択

本体キーでの操作：PROGRAMツマミで選択します。

サブメニューの選択

本体キーでの操作：PRESET/TUNING ▷ (順送り)、◁ (逆送り)キーで選択します。

Keys of main unit / 本体キー



● Functions in DIAG mode

In addition to the DIAG menu items, functions as listed below are available.

- Input selection
 - Center/Rear/Rear Center/Sub-woofer level adjustment
 - Speaker relay control of A and B
 - Muting
 - Power on/off
 - Master volume
- * Functions related to the tuner and the set menu are not available.
- * It is possible to confirm Menu No.16 IF STATUS while keeping the signal process (operation status) of each DIAG menu by using the INPUT MODE key of the main unit.

● ダイアグ中の機能

ダイアグメニューの他に、以下の機能が動作します。

- インプット切り換え
- センター、リア、リアセンター、サブウーファーレベル調整
- スピーカーリレーA/B
- ミューティング
- パワーオン/オフ
- マスターボリューム

※ チューナー関連、セットメニュー関連は機能しません。

※ 本体のINPUT MODEキーにより、各ダイアグメニューの信号処理(動作状態)を維持したままメニューNo.16 "IF STATUS"の確認ができます。

● Initial settings used to start DIAG

The following settings are used when starting DIAG. When DIAG is canceled, these settings are restored to those before starting DIAG.

- Master volume: -20 dB
- Input: DVD (MULTI CH INPUT OFF)
- Effect level: 0 dB
- Audio mute: OFF
- Speaker relay of A and B: ON
- Speaker setting: LARGE / BASS OUT = SWFR
- DIAG menu: BYPASS (1. ANALOG BYPASS)

● ダイアグ開始時の初期設定

ダイアグ開始時に以下のような設定になります。ダイアグ解除時にはダイアグ開始前の状態に戻ります。

- マスターボリューム: -20 dB
- インプット: DVD (MULTI CH INPUT オフ)
- エフェクトレベル: 0 dB
- オーディオミュート: オフ
- スピーカーリレーA/B: ON
- スピーカー設定: LARGE / BASS OUT = SWFR
- ダイアグメニュー: BYPASS (1. ANALOG BYPASS)

● Details of DIAG menu

1. BYPASS

Using the sub-menu, it is possible to select analog bypass output or DSP bypass output.

ANALOG BYPASS

1. ANALOG BYPASS

Reference data

INPUT: DVD ANALOG

SUBWOOFER OUTPUT: 50 Hz, Others: 1 kHz

Input level	Volume	SPEAKERS OUT				SUBWOOFER OUTPUT
		FRONT L/R	CENTER	SURROUND L/R	SURROUND BACK L/R	
Both ch, -20 dBm	+6.0 dB	+13.0 dBm	- ∞	- ∞	- ∞	- ∞

DSP BYPASS

DSP BYPASS

1. DSP BYPASS


Reference data

INPUT: DVD ANALOG

SUBWOOFER OUTPUT: 50 Hz, Others: 1 kHz


Input level	Volume	SPEAKERS OUT				SUBWOOFER OUTPUT
		FRONT L/R	CENTER	SURROUND L/R	SURROUND BACK L/R	
Both ch, -20 dBm	+6.0 dB	+13.5 dBm	- ∞	- ∞	- ∞	- ∞

ANALOG BYPASS



(Shaded items not used in this example)

DSP BYPASS



(Shaded items not used in this example)

2. RAM THROUGH

Using the sub-menu, it is possible to select margin output or full-bit output.

RAM MARGIN

Following head margin is reserved.

FRONT	CENTER	SURROUND	SURROUND BACK	SUBWOOFER
+15.0 dB	+13.5 dB	+9.0 dB	+7.5 dB	+21.0 dB

2. RAM MARGIN

Reference data

INPUT: DVD ANALOG

SUBWOOFER OUTPUT: 50 Hz, Others: 1 kHz

Input level	Volume	SPEAKERS OUT				SUBWOOFER OUTPUT
		FRONT L/R	CENTER	SURROUND L/R	SURROUND BACK L/R	
Both ch, -20 dBm	+6.0 dB	+13.5 dBm	+13.5 dBm	+13.5 dBm	+13.5 dBm	+2.0 dBm

RAM FULL BIT

No head margin is reserved except SW.

FRONT	CENTER	SURROUND	SURROUND BACK	SUBWOOFER
0 dB	0 dB	0 dB	0 dB	+21.0 dB


2. RAM FULL BIT

Reference data

INPUT: DVD ANALOG

SUBWOOFER OUTPUT: 50 Hz, Others: 1 kHz

Input level	Volume	SPEAKERS OUT				SUBWOOFER OUTPUT
		FRONT L/R	CENTER	SURROUND L/R	SURROUND BACK L/R	
Both ch, -20 dBm	+6.0 dB	+13.5 dBm	+13.5 dBm	+13.5 dBm	+13.5 dBm	+2.0 dBm



(Shaded items not used in this example)

When input source is stereo, signal is assigned as below.

2ch信号入力時、以下のように信号を振り分けて出力します。

- Front L → Center / Surround L / Surround Back L, R
- Front R → Surround R
- Front L +10 dB → SWFR

3. PRO LOGIC

Dolby PRO LOGIC is applied to input stereo source.

3. PRO LOGIC

入力2ch信号にDolby PRO LOGIC処理を行います。


3. PRO LOGIC

Reference data

INPUT: DVD ANALOG

SUBWOOFER OUTPUT: 50 Hz, Others: 1 kHz

Input level	Volume	SPEAKERS OUT				SUBWOOFER OUTPUT
		FRONT L/R	CENTER	SURROUND L/R	SURROUND BACK L/R	
Each ch, -20 dBm	+6.0 dB	+13.5 dBm	- ∞	- ∞	- ∞	- ∞
Both ch, -20 dBm	+6.0 dB	-20.0 dBm	+16.5 dBm	- ∞	- ∞	- ∞



(Shaded items not used in this example)

4. SPEAKERS SET

The analog switch settings for each sub-menu are as shown in the table below.

4. SPEAKERS SET

各サブメニューにおけるアナログスイッチの設定は以下の通りです。

Sub-menu	FRONT L/R	CENTER	SUR. L/R	SUR.B L/R	LFE/BASS
1 FRNT: SML 0 dB	SMALL	LARGE	LARGE	LARGE	SWFR
2 CENTER: NONE	LARGE	NONE	LARGE	LARGE	SWFR
3 LFE/B: FRNT	LARGE	SMALL	SMALL	SMALL	FRONT
4 Pre Mix: 5ch	—	—	—	—	—
5 Front GAIN 1	—	—	—	—	—
6 Front GAIN 2	—	—	—	—	—
7 SURR B Check	—	—	—	—	—

LARGE: This mode is used with a speaker with high bass reproduction performance (a large unit). Full bandwidth signals are output.

SMALL: This mode is used with a speaker with low bass reproduction performance (a small unit). The signals of 80 Hz or less are mixed into the channel specified by LFE/BASS.

NONE: This mode is used with no center speaker. The center content is reduced by 3 dB and distributed to FRONT L/R.

SWFR: LFE of 5.1ch signal or LFE/BASS lower than 90Hz is output through SUBWOOFER OUT.

FRONT: LFE of 5.1ch signal or LFE/BASS lower than 90Hz is distributed to FRONT L/R.


LARGE : 低音再生能力の高い(ユニットの大きい)スピーカーを使用するモードです。全帯域が出力されます。

SMALL : 低音再生能力の低い(ユニットの小さい)スピーカーを使用するモードです。80 Hz以下がLFE/BASSで指定したチャンネルにミックスされます。

NONE : スピーカーを使用しないモードです。センター成分は-3 dBされて、FRONT L/R に振り分けられます。

SWFR : 5.1ch信号のLFEまたは90Hz以下のLFE/BASSがSUBWOOFER OUTに出力されます。

FRONT : 5.1ch信号のLFEまたは90Hz以下のLFE/BASSをFRONT L/Rに振り分けます。



Reference data
INPUT: DVD ANALOG (Both ch)
SUBWOOFER OUTPUT: 50 Hz, Others: 1 kHz

	Sub-menu	Input level	Volume	SPEAKER OUT				SUBWOOFER OUTPUT
				FRONT L/R	CENTER	SURROUND L/R	SURROUND BACK L/R	
1	FRONT: SML 0dB	Both ch, -20 dBm	+6.0 dB	+13.5 dBm	+13.5 dBm	+13.5 dBm	+13.5 dBm	+5.5 dBm
2	CENTER: NONE	Both ch, -20 dBm	+6.0 dB	+10.5 dBm	- ∞	+13.5 dBm	+13.5 dBm	+2.0 dBm
3	LFE/B: FRNT (1 kHz)	Both ch, -20 dBm	+6.0 dB	- ∞	+13.5 dBm	+13.5 dBm	+13.5 dBm	- ∞
	LFE/B: FRNT (50 Hz)	Both ch, -20 dBm	+6.0 dB	+25.0 dBm	+13.5 dBm	+13.5 dBm	+13.5 dBm	- ∞
4	Pres Mix: 5ch	Both ch, -20 dBm	+6.0 dB	- ∞	+13.5 dBm	+18.5 dBm	- ∞	-0.5 dBm
5	Front Gain 1	Both ch, -20 dBm	+6.0 dB	+20.5 dBm	+13.5 dBm	+13.5 dBm	+13.5 dBm	+2.0 dBm
6	Front Gain 2	Both ch, -20 dBm	+6.0 dB	+20.5 dBm	+13.5 dBm	+13.5 dBm	+13.5 dBm	+2.0 dBm
7	SURR B check	Both ch, -20 dBm	+6.0 dB	- ∞	- ∞	- ∞	+13.5 dBm	- ∞

RX-V559/HTR-5950/
DSP-AX559

5. XCH INPUT

The signal input through the multi ch input is output.
The speaker impedance can be selected.

XCH INPUT_6 (ohms)

5.XCH INPUT_6

Reference data

INPUT: MULTI CH INPUT

SUBWOOFER OUTPUT: 50 Hz, Others: 1 kHz

Input level	Volume	SPEAKERS OUT				SUBWOOFER OUTPUT
		FRONT L/R	CENTER	SURROUND L/R	SURROUND BACK L/R	
Both ch, -20 dBm	+6.0 dB	+13.5 dBm	+13.5 dBm	+13.5 dBm	- ∞	-10.0 dBm

5. XCH INPUT

マルチCH入力された信号が出力されます。
6オーム、8オームが選択されます。

XCH INPUT_6(ohms)**XCH INPUT_8 (ohms)**

5.XCH INPUT_8

Reference data

INPUT: MULTI CH INPUT

SUBWOOFER OUTPUT: 50 Hz, Others: 1 kHz

Input level	Volume	SPEAKERS OUT				SUBWOOFER OUTPUT
		FRONT L/R	CENTER	SURROUND L/R	SURROUND BACK L/R	
Both ch, -20 dBm	+6.0 dB	+13.5 dBm	+13.5 dBm	+13.5 dBm	- ∞	-10.0 dBm

XCH INPUT_8(ohms)**LIMIT SET**

Not applied to these models.

LIMIT SET

このモデルには適用されません。

XXXXXXXXXXXXXX_

6. MIC CHECK

Not applied to these models.

6. MIC CHECK


このモデルには適用されません。

6.MIC CHK --dB

7. DISPLAY CHECK

This program is used to check the FL display section and video control section. The display condition varies as shown below according to the sub-menu operation. The signal route is STRAIGHT.

Checking FL display section / FL表示部のチェック




Segment conditions of the FL driver and the FL tube are checked by turning ON and OFF all segments. Next, the operation of the FL driver is checked by using the dimmer control. Then a short between segments next to each other is checked by turning ON and OFF all segments alternately (in lattice). (In the above example, the segments in the second row from the top are shorted.)

7. DISPLAY CHECK

FL表示部と映像制御部のチェックプログラムです。サブメニュー操作により、表示状態が以下のように変わります。信号処理はSTRAIGHTです。

Checking OSD section (Monitor Out) / 映像制御部のチェック (モニターアウト)



全セグメント消灯・全セグメント点灯によりFLドライバー、FL管のセグメントの不良を確認します。

次に、ディマーコントロールによってFLドライバーの動作チェックを行います。

さらに全セグメントを交互(格子状)に点灯/消灯することで、隣り合うセグメントのショートをチェックします。

(上図の例では、上から2行目のセグメントがショートしていません。)

8. MANUAL TEST


The test noise based THX is output to the channel specified by the sub-menu from the DSP.

The noise frequency for LFE is 35 to 250 Hz. Other than that, the center frequency is 800 Hz.

8. MANUAL TEST

DSPからサブメニューで指定したチャンネルへTHX準拠のテストノイズを出力します。

LFE用のノイズ周波数は35～250 Hz、それ以外は中心周波数800 Hzとなります。




9. FACTORY PRESET

This menu is used to reserve/inhibit initialization of the backup RAM (Parameters and set menu contents, etc. of the sound field program).

9. FACTORY PRESET

バックアップ用RAM（音場プログラムのパラメーターやセットメニュー内容など）の初期化を予約/禁止します。



PRESET INHIBIT (Initialization inhibited) / PRESET INHIBIT (初期化禁止)

RAM initialization is not executed. Select this sub-menu to protect the values set by the user.

Note: The protection history will not be erased using PRESET INHIBIT.

RAMの初期化は行われません。ユーザーの設定値を保護するときは、こちらを選択してください。

PRESET RESERVED (Initialization reserved) / PRESET RESERVED (初期化予約)

Initialization of the back-up RAM is reserved. (Actually, initialization is executed the next time that the power is turned on.) Select this sub-menu to reset to the original factory settings or to reset the RAM. Use PRESET RESERVED to erase the protection history.

バックアップRAMの初期化が予約されます。(実際に初期化されるのは、次の電源投入時です。) 工場出荷時やRAMをリセットしたいときは、こちらを選択してください。

CAUTION: Before setting to the PRESET RESERVED, write down the existing preset memory. Content of the Tuner in a table as shown below. (This is because setting to the PRESET RESERVED will cause ALL user memory contents to be erased.)

注意：PRESET RESERVEDを選んで初期化をする前に、チューナーのユーザーメモリー内容を下表に書き写してください。(初期化をすると、ユーザーメモリーの内容は消えてしまいます。)

Preset group	P1	P2	P3	P4	P5	P6	P7	P8
A								
B								
C								
D								
E								

• PRESET STATIONS / プリセット局

STATION		FM FACTORY PRESET DATA (MHz)			
PAGE	NO.	U, C	R, T, K, A, G, E, L	J	
A/C/E	1	87.5	87.50	76.0	
	2	90.1	90.10	83.0	
	3	95.1	95.10	84.0	
	4	98.1	98.10	86.0	
	5	107.9	108.00	90.0	
	6	88.1	88.10	78.0	
	7	106.1	106.10	88.0	
	8	107.9	108.00	82.1	

STATION		AM FACTORY PRESET DATA (kHz)			
PAGE	NO.	U, C, R, T, K	A, G, E, L	J	
B/D	1	630	630	630	
	2	1080	1080	1080	
	3	1440	1440	1440	
	4	530	531	531	
	5	1710	1611	1611	
	6	900	900	900	
	7	1350	1350	1350	
	8	1400	1404	1404	

10. AD DATA CHECK

This menu is used to display the A/D conversion value of the Microprocessor which detects panel keys of the main unit and protection functions in using the sub-menu. During audio signal processing, the condition before execution is maintained.

When K0/K1 menu is selected, keys become non-operable due to detection of the values of all keys. However, it is possible to advance to the next sub-menu by turning the VOLUME of the main unit. When using this function, note that turning the VOLUME more than 1 click would cause the volume value to change.

* The figures in the diagram are given as reference only.

PS1/PS2 (Power supply voltage protection detection)

Power supply voltage protection value (Normal value: PS1: 17 to 66, PS2: 36 to 53)

PS1: Detects +5S and +5.3X (U, C models).

PS2: Detects ±12V, ±5V, +5D, +3.3D and +5i.

* If PS is out of the normal value range, the protection function works to turn off the power.

(Reference voltage: 5 V=100 %)

PS1:039 2:044

DC/TH (protection detection/temperature detection)

DC: DC detect protection value (Normal value: 5 to 36)

* If DC is out of the normal value range, the protection function works to turn off the power.

(Reference voltage: 5 V=100 %)

TH: Detects the temperature of the heat sink.

Temperature detected value

(Normal value: 9 to 177) U, C, T, K, A, G, E, J models

(Normal value: 9 to 167) R, L models

(Reference voltage: 5 V=255)

DC:007 TH098

10. AD DATA CHECK

本機パネルキー、プロテクションなどを検出しているMicroprocessorのA/D変換の値を、サブメニューで表示します。オーディオ信号処理は実行前の状態を維持します。

K0/K1のメニューにすると、全キーの値を検出するためキー操作はできなくなりますが、本機のVOLUMEを回すことにより、次のサブメニューに進めることができます。このとき1クリック以上回すと、ボリューム値が変化するので注意してください。

※ 図中の数値は参考例です。

PS1/PS2 (電源電圧プロテクションの検出)

プロテクションの値(正常値 PS1: 17~66、PS2: 36~53)

PS1 : +5Sを検出しています。

PS2 : ±12V、±5V、+5D、+3.3D、+5iを検出しています。

※ PSは正常値を外れるとプロテクションが働き、電源オフされます。

(基準電圧 : 5V=100%)

DC/TH (プロテクションの検出/温度検出)

DC : DC検出プロテクションの値(正常値5~36)

※ DCは正常値を外れるとプロテクションが働き、電源オフされます。

(基準電圧 : 5V=100%)

TH : ヒートシンクの温度を検出しています。

温度検出値

(正常値: 9~177)

(基準電圧 : 5V=255)

IMP SW/POWER LIMIT (impedance/power limiter detection)

IMP: Not applied to these models.

PL: Power limiter detection value

The voltage value of pin No. 123 of IC2 is displayed, using 5V/256 as standard.

The port (No. 6) output is controlled by using the input voltage value of pin No. 123 of IC2.

IMP:8 PL:245

IMP SW/POWER LIMIT (インピーダンス/パワーリミッターの検出)

IMP: このモデルには適用されません。

PL: パワーリミッター検出の値

IC2 123ピンの入力電圧値を5V/256を基準にして表示します。IC2 123ピンの入力電圧値により、ポート(6ピン)を制御します。

PANEL KEY (K0/K1)

(Panel key of main unit) [Remote control code: -]

A/D of the key fails to function properly when the standard value is deviated by ± 8 . In this case, check the constant of partial pressure resistor, solder condition, etc. Refer to table.

(Reference voltage: 5 V=100 %)

K0:100 K1:100

PANEL KEY (K0/K1)

(本機/パネルキー)

キーのA/Dは基準値から ± 8 を外れると、正常な動きをしません。下表をご覧ください。各キーの分圧抵抗の定数、ハンダ不良等の確認をしてください。

(基準電圧: 5V=100%)

RX-V559/DSP-AX559

Display (%)	K0	K1
0 - 6	MAIN ZONE ON/OFF	ZONE ON/OFF
7 - 13	—	—
14 - 21	—	—
22 - 31	—	ZONE CONTROL
32 - 41	INPUT MODE	MULTI CH INPUT
42 - 53	STRAIGHT	FM/AM
54 - 63	TONE CONTROL	A/B/C/D/E
64 - 72	PRESET/TUNING	◁ PRESET
73 - 80	SPEAKERS B	PRESET ▷
81 - 88	SPEAKERS A	MEMORY
89 - 95	—	TUNING MODE
96 - 100	KEY OFF	KEY OFF

HTR-5950

Display (%)	K0	K1
0 - 6	◁ PROGRAM	—
7 - 13	PROGRAM ▷	—
14 - 21	BASS/TREBLE -	—
22 - 31	BASS/TREBLE +	—
32 - 41	INPUT MODE	MULTI CH INPUT
42 - 53	STRAIGHT	FM/AM
54 - 63	TONE CONTROL	A/B/C/D/E
64 - 72	PRESET/TUNING	◁ PRESET
73 - 80	SPEAKERS B	PRESET ▷
81 - 88	SPEAKERS A	MEMORY
89 - 95	—	TUNING MODE
96 - 100	KEY OFF	KEY OFF

11. VIDEO

The image signal is converted and output as follows.

I2C



Perform the read/write check between the microprocessor and ADV7180 (IC411) as well as ADV7172 (IC412).

11. VIDEO

映像信号が以下のように変換され、出力されます。



I2C

マイコンとADV7180(IC411)、およびADV7172(IC412)間のリード/ライトのチェックを行います。



DIGITAL THR CVBS


DIGITAL THR CVBS



DIGITAL THR Y/C

DIGITAL THR Y/C


DIGITAL Y/C



ANALOG BYPASS

ANALOG BYPASS


ANALOG BYPASS




TEST PATTERN

TEST PATTERN

TEST PATTERN



IC713 TEST Pattern (480i/576i)





LOOP BACK CVBS

Not applied to these models.

LOOP BACK CVBS

このモデルには適用されません。

LPBK CVBS OK





LOOP BACK Y/C

Not applied to these models.

LOOP BACK Y/C

このモデルには適用されません。

LPBK Y/C OK



12. XM STATUS (U, C models)

Perform the output check of XM Radio Antenna connected to the XM terminal.

1k -1dB/44.1k

The test tone (1kHz, -1dB/44.1kHz) is output.

1k - 1dB/44

1k -61dB/44.1k

The test tone (1kHz, -61dB/44.1kHz) is output.

1k -61dB/44

Mute /44.1k

Nothing is output.

Mute /44

XM Tone/44.1k

The XM tone (44.1kHz) is output.

XM Tone/44

ISO Tone/44.1k

The ISO tone (44.1kHz) is output.

ISO Tone/44

1k -1dB/32k

The test tone (1kHz, -1dB/32kHz) is output.

1k - 1dB/32

1k -61dB/32k

The test tone (1kHz, -61dB/32kHz) is output.

1k -61dB/32

12. XM STATUS(U, C models)

XM端子に接続された、XM Radio Antennaの出力チェックを行います。

1k -1dB/44.1k

テストトーン(1kHz、-1dB/44.1kHz)を出力します。

1k -61dB/44.1k

テストトーン(1kHz、-61dB/44.1kHz)を出力します。

Mute /44.1k

何も出力されません。

XM Tone/44.1k

XMトーン(44.1kHz)を出力します。

ISO Tone/44.1k

ISOトーン(44.1kHz)を出力します。

1k -1dB/32k

テストトーン(1kHz、-1dB/32kHz)を出力します。

1k -61dB/32k

テストトーン(1kHz、-61dB/32kHz)を出力します。

Mute /32k
Nothing is output.

Mute /32

Mute /32k
何も出力されません。

XM Tone/32k
The XM tone (32kHz) is output.

XM Tone/32

XM Tone/32k
XMトーン(32kHz)を出力します。

ISO Tone/32k
The ISO tone (32kHz) is output.

ISO Tone/32

ISO Tone/32k
ISOトーン(32kHz)を出力します。

XM/DT Bus Power: OFF
The power of XM module is turned off.


Bus Power:OFF

XM/DT Bus Power: OFF
XMモジュールの電源をOFFします。

13. iPod

This menu is used to test the DOCK connector without the iPod itself. After turning off the power, short between pins No. 14 (TX) and No. 18 (RX), between pins No. 1 (PWR) and No. 17 (ACCPow) and between pins No. 4 (iPDET) and No. 8 (DGND). (Make sure that the power is turned off when shorting pins.) Start the DIAG function and select the menu. The check result is displayed according to the following display specifications.


Note) Be sure to return the shorted locations to their original state.



13. iPod

iPod本体無しで、DOCKコネクタの検査を行うメニューです。パワーオフ状態にしてから、DOCKコネクタの14ピン(TX)と18ピン(RX)、1ピン(PWR)と17ピン(ACCPow)、4ピン(iPDET)と8ピン(DGND)をショートさせます。(ショートさせる時は、必ず電源を切ってください。)ダイグを起動してメニューを選択します。下記表示仕様に従って、チェック結果が表示されます。

注) ショート箇所は、必ず元に戻してください。



Check item / チェック項目	Judgment / 判定	Display / 表示
Is UART loop pack check result OK? / UARTループバックチェック結果はOK?	YES	Y
	NO	N
Is detect function of iPod Accessory Power OK? / iPod Accessory Powerの検出機能はOK?	IC2 (DSP P.C.B.) pin No. 45 state High = YES	Y
	IC2 (DSP P.C.B.) 45pinの状態 Low = No	N
Is detect function of iPod installation to DOCK OK? / DOCKへのiPod装着の検出機能はOK?	IC2 (DSP P.C.B.) pin No. 44 state Low = installed / 装着	Y
	IC2 (DSP P.C.B.) 44pinの状態 High = not installed / 非装着	N

16. IF STATUS (Input function status)

Using the sub-menu, the status data is displayed one after another in the hexadecimal notation.
During signal processing, the status before execution of this menu is maintained.

* Numeric values in the figure example are for reference.


DST: DSP status

16. IF STATUS

サブメニュー操作により、以下のステータス情報を順次16進数で表示します。信号処理は、本メニュー実行前の状態を維持します。

※図中の数値は参考例です。

DST : DSPステータス



<1st byte> Digital input/output setting value
Upper 4 bits: REC OUT selected /
lower 4 bits: INPUT selected

<第1バイト> デジタル入出力設定値
上位4 bit REC OUT選択 /
下位4 bit INPUT選択

Value	Choice	Preset name
0	NONE	—
1	OPT FRONT	—
2	OPT 1	MD/CD-R
3	OPT 2	DVD
4	OPT 3	DTV/CBL
8	COAX 1	CD
9	COAX 2	—

<2nd byte> / <第2バイト>
Fs information of reproduction signal /
再生信号のFs情報

Display	Fs (kHz)
00	Analog
01	32 kHz
02	44.1 kHz
03	48 kHz
04	64 kHz
05	88.2 kHz
06	96 kHz
07	128 kHz
08	176.4 kHz
09	192 kHz
0A	Unknown NRM
0B	Unknown DBL
0C	Unknown QUAD
0D	Unknown
0E	Undefined

<3rd byte> / <第3バイト>
Audio code mode information of
reproduction signal /
再生信号のオーディオコードモード情報

Display	Audio code
00	1+1
01	1/0
02	2/0
03	3/0
04	2/1
05	3/1
06	2/2
07	3/2
08	2/3
09	3/3
0A	3/4
0B	over 6.1
0C	Milti-Mono
0D	Milti-PCE
0E	Unknown
0F	Undefined

<4th byte> / <第4バイト>
Format information of reproduction signal /
再生信号のフォーマット情報

Display	Signal format
00	Analog
01	Err
10	PCM Audio
20	Digital Data
21	IEC1937
22	None PCM
23	Unknown
50	dtc
51	dtc-CD
52	dtc 96/24
54	dtc-ES (Matrix)
58	dtc-ES (Discrete)
5C	dtc-ES (Both)
60	AAC
C0	Dolby Digital
C1	Dolby Digital Karaoke
C4	Dolby Digital EX
FF	Undefined

<5th byte> / <第5バイト>
Signal processing status information /
信号処理ステータス情報

bit	Fs (kHz)
bit 7	Digital mute
bit 6	—
bit 5	6.1 (7.1) processing
bit 4	Analog mute
bit 3	—
bit 2	PCM through
bit 1	—
bit 0	dtc analog mute

DMD: Decoder mode information
Not applied to these models.

DMD: デコーダー情報
このモデルには適用されません。

DMD:03C00000

DIF: DIR information
Not applied to these models.

DIF: DIR情報
このモデルには適用されません。

DIF:0001000600

PC: Preamble C information
Not applied to these models.

PC: Preamble C情報
このモデルには適用されません。

PC :0000

CS1, 2: Channel status information
Not applied to these models.

CS1、2: チャンネルステータス情報
このモデルには適用されません。

CS1:0000000000 ————— CS2:00

DEI: Decoder information
Not applied to these models.

DEI: デコーダー情報
このモデルには適用されません。

DEI:0808000600

BS1-8: Bit stream information
Not applied to these models.

BS1-8: ビットストリーム情報
このモデルには適用されません。

BS1:0000000000 ————— BS8:00

MTT: Mute Trigger
Not applied to these models.

MTT: Mute Trigger
このモデルには適用されません。

MTT:0018001820

DGI: Digital information
Not applied to these models.

DGI: DIGITAL系情報
このモデルには適用されません。

DGI:EE6464F95E

17. DSP BUS CHECK

This menu is used to self-diagnose whether or not the bus connection for the TI (DA70Y) and the external ROM/RAM is made properly.

When no error is detected, "NoEr" appears on display.

TI BUS:NoEr

No error detected.
不良検出なし

or

TI BUS:Boot

When this indication is displayed with in seconds or displayed alternately "NoEr" and "Boot", it is highly possible that there are errors.

数秒間この状態、またはNoErと交互に表示される場合、異常が発生している可能性があります。

RDS IC:OK

No applied to these models.
このモデルは適用されません。

or

RDS IC:NG

18. SWFR CUT OFF

Not applied to these models.

18. SWFR CUT OFF

このモデルには適用されません。

18.LFE LPF 200

18.LFE HPF THR

19. PROTECTION SETTING

Not applied to these models.

19. PROTECTION SETTING

このモデルには適用されません。

PS_Lo: 0043

PL_6_N_H:0154

20. PROTECTION HISTORY

Four protection histories are display.

20. PROTECTION HISTORY

過去のプロテクション履歴を4つまで表示します。

20-1:NoPRT

20-4:NoPRT

21. SOFT SW

Note) Changing the function setting may hinder the proper operation.

This menu is used to switch the function settings on P.C.B. through the software so as to activate the product. The protection function follows the P.C.B. settings. When connected to AC or in the maker preset state, the unit is initialized to the P.C. B. setting. Display of each function after initialization varies depending on settings on P.C.B. The operation mode can be changed by selecting the sub-menu and then using the STRAIGHT key.

SW MODE: PCB, MODEL or FNC can be selected.

21.SW :PCB

MODEL SETTING: 759SE, V659, H5960, V559, H5950, V459 or H5935 can be selected. (SW MODE: Selectable when MODEL has been selected.)

21.MODEL:V559

DESTINATION: J, U, C, R, T, K, A, B, G (E) or L can be selected. (SW MODE: Selectable when MODEL has been selected.)

21.DEST :G

TUNER DESTINATION: J, UC, ABG or RL can be selected. (SW MODE: Selectable when FNC has been selected.)

21.TuDst:ABG

TUNER TYPE: NRM, RDS or XM can be selected. (SW MODE: Selectable when FNC has been selected.)

21.TuDyp:RDS

VIDEO FORMAT: NTSC or PAL can be selected. (SW MODE: Selectable when FNC has been selected.)

21.VIDEO:PAL

21. SOFT SW

注) 機能設定を変更した場合、正常に動作しないことがあります。

P.C.B.上の機能設定をソフト的に切り替えて、製品を動作させる機能です。
プロテクション機能は、P.C.B.の設定にしがいます。AC接続またはメーカープリセットで、P.C.B.の設定に初期化されます。初期化後の各機能の表示は、P.C.B.上の設定によります。操作は、サブメニューを選んだ後、STRAIGHTキーで切り替えます。

SW MODE : PCB、MODELまたはFNCを選択できます。

MODEL SETTING : 759SE、V659、H5960、V559、H5950、V459、H5935のいずれかを選択できます。(SW MODE : MODEL時選択できます。)

DESTINATION : J、U、C、R、T、K、A、B、G(E)、Lのいずれかを選択できます。(SW MODE : MODEL時選択できます。)

TUNER DESTINATION : J、UC、ABG、RLのいずれかを選択できます。(SW MODE : FNC時選択できます。)

TUNER TYPE : NRM、RDS、XMのいずれかを選択できます。(SW MODE : FNC時選択できます。)

VIDEO FORMAT : NTSCまたはPALを選択できます。(SW MODE : FNC時選択できます。)

ZONE2: NOT or EXIST can be selected. (SW MODE: Selectable when FNC has been selected.)

ZONE2 : NOTまたはEXISTを選択できます。(SW MODE : FNC時選択できます。)

21.ZONE2:EXIST

AAC: NOT or EXIST can be selected. (SW MODE: Selectable when FNC has been selected.)

AAC : NOTまたはEXISTを選択できます。(SW MODE : FNC時選択できます。)

21.AAC :NOT

TUNER: NOT or EXIST can be selected. (SW MODE: Selectable when FNC has been selected.)

TUNER : NOTまたはEXISTを選択できます。(SW MODE : FNC時選択できます。)

21.TUNER:EXIST

ZONE2 AMP: NOT or EXIST can be selected. (SW MODE: Selectable when FNC has been selected.)

ZONE2 AMP : NOTまたはEXISTを選択できます。(SW MODE : FNC時選択できます。)

21.Z2AMP:NOT

OSD: NOT or EXIST can be selected. (SW MODE: Selectable when FNC has been selected.)

OSD : NOTまたはEXISTを選択できます。(SW MODE : FNC時選択できます。)

21.OSD :EXIST

YPAO: NOT or EXIST can be selected. (SW MODE: Selectable when FNC has been selected.)

YPAO : NOTまたはEXISTを選択できます。(SW MODE : FNC時選択できます。)

21.YPAO :NOT

22. SOFTWARE VERSION


The version, checksum and the port specified by the microprocessor are displayed. The signal is processed using EFFECT OFF. The checksum is obtained by adding the data at every 16 bits for each program area and expressing the result as a 4-figure hexadecimal data.

* Numeric values in the figure example are for reference.

22. SOFTWARE VERSION

ソフトウェアのバージョン、チェックサム、マイコンの指定ポートを表示します。
信号はエフェクトOFFです。チェックサムは、プログラムエリア別にデータを16ビットごとに加算していき、4桁の16進データで現したものです。

※図中の数値は参考例です。



23. TI (DSP) BOOT

The rewriting mode of TI (DSP) software.
(Not applied to these models.)

23. TI(DSP)BOOT

TI(DSP)のソフトウェア書き換えモードです。
(このモデルには適用されません。)

23.TI BOOT ?

RX-V559/HTR-5950/
DSP-AX559

■ AMP ADJUSTMENT / アンプ部調整

Confirmation of Idling Current of MAIN (1) P. C. B.

- Right after power is turned on, confirm that each measured voltage across the terminals of R1149 (FRONT Lch), R1150 (FRONT Rch), R1153 (CENTER), R1154 (SURROUND Lch), R1152 (SURROUND Rch), R1151 (SURROUND BACK) is between 0.1 mV and 10.0 mV.
- If it exceeds 10.0 mV, open (cutoff) R1104 (FRONT Lch), R1106 (FRONT Rch), R1112 (CENTER), R1114 (SURROUND Lch), R1110 (SURROUND Rch), R1108 (SURROUND BACK) and reconfirm the voltage.

Attention

If the measured voltage exceeds 10.0 mV. after an amplifier repair, first check for a defective component before cutting the bias resistor.

- Confirm that the voltage is 0.2 mV ~ 15.0 mV. after 60 minutes.

メイン(1)基板のアイドリング電流の確認


- 電源投入直後、R1149(FRONT Lch)、R1150(FRONT Rch)、R1153(CENTER)、R1154(SURROUND Lch)、R1152(SURROUND Rch)、R1151(SURROUND BACK)の端子間電圧を測定し、0.1 mVから10.0 mVの間であることを確認してください。

- 電圧が10 mVを超えている場合は、R1104(FRONT Lch)、R1106(FRONT Rch)、R1112(CENTER)、R1114(SURROUND Lch)、R1110(SURROUND Rch)、R1108(SURROUND BACK)をカットし、電圧を再確認してください。

注意

パワーアンプ修理後に10.0 mV.を超えている場合は、抵抗をカットする前に故障箇所を調べてください。


- 60分後、電圧が0.2 mV～15.0 mV.であることを確認してください。



RX-V559/DSP-AX559

■ DISPLAY DATA

● V3000 : HNA-17MM03T (WG474000)







● PIN CONNECTION

Pin No.	69	68	67	66	65	64	63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35
Connection	F2	F2	NP	NP	P1	P2	P3	P4	P5	P6	P7	P8	P9	P10	P11	P12	P13	P14	P15	P16	P17	P18	P19	P20	P21	P22	P23	P24	P25	P26	P27	P28	P29	P30	P31

Pin No.	34	33	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	
Connection	P32	P33	P34	P35	P36	P37	NX	NX	NX	NX	NX	NX	NX	NX	17G	16G	15G	14G	13G	12G	11G	10G	9G	8G	7G	6G	5G	4G	3G	2G	1G	NP	NP	F1	F1

Note : 1) Fn Filament pin 2) nG Grid pin 3) Pn Anode pin 4) NP No pin 5) NX No extended pin

● GRID ASSIGNMENT




● ANODE CONNECTION

	17G	16G	15G	14G	13G~1G
P1		S1	S1	1-1	1-1
P2		▶ DVR	W1	2-1	2-1
P3	MATRIX	▶ V-AUX	W2	3-1	3-1
P4	DISCRETE	▶ DTV/CBL	4g	4-1	4-1
P5		▶ DVD	1a	5-1	5-1
P6		▶ MD/CD-R	1b	1-2	1-2
P7	ENHANCER	▶ TUNER	1c	2-2	2-2
P8		▶ CD	1d	3-2	3-2
P9			1e	4-2	4-2
P10			1f	5-2	5-2
P11		SP	1g	1-3	1-3
P12		A	2a	2-3	2-3
P13		B	2b	3-3	3-3
P14		SILENT CINEMA	2c	4-3	4-3
P15		ZONE2	2d	5-3	5-3
P16		NIGHT	2e	1-4	1-4
P17	NET	DOCK	2f	2-4	2-4
P18	USB		2g	3-4	3-4
P19	VCR	HiFi DSP	3g	4-4	4-4
P20	▶ NET	YPAO	3b	5-4	5-4
P21	▶ USB	AUTO	3a	1-5	1-5
P22	▶ VCR	TUNED	XM	2-5	2-5
P23	R1	STEREO	PHONO	3-5	3-5
P24	R2	MEMORY	▶ XM	4-5	4-5
P25	R3	HD	▶ PHONO	5-5	5-5
P26	R4	DAB	SUR.	1-6	1-6
P27	R5	SECONDARY	MUTE	2-6	2-6
P28	VIRTUAL	DRC	DUAL	3-6	3-6
P29	STANDARD	PRESET	96/24	4-6	4-6
P30	—	PTY HOLD	ft	5-6	5-6
P31	—	HOLD		1-7	1-7
P32	—	PS		2-7	2-7
P33	—	PTY		3-7	3-7
P34	—	RT		4-7	4-7
P35	—	CT		5-7	5-7
P36	—	EON		ms	—
P37	—	SLEEP		dB	—

HTR-5950

■ DISPLAY DATA

● V3000 : 17-BT-26GNK (WG473900)





● PIN CONNECTION

Pin No.	69	68	67	66	65	64	63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35
Connection	F2	NX	NP	NP	P1	P2	P3	P4	P5	P6	P7	P8	P9	P10	P11	P12	P13	P14	P15	P16	P17	P18	P19	P20	P21	P22	P23	P24	P25	P26	P27	P28	P29	P30	P31


Pin No.	34	33	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1
Connection	P32	P33	P34	P35	P36	P37	NX	NX	NX	NX	NX	NX	NX	17G	16G	15G	14G	13G	12G	11G	10G	9G	8G	7G	6G	5G	4G	3G	2G	1G	NP	NP	NX	F1

Note : 1) F1, F2 Filament pin 2) NP No pin 3) NX No extend pin 4) 1G~17G Grid pin

● GRID ASSIGNMENT




(1G~14G)



(16G)

(15G)




(17G)



S20



S21



S2



S26





S27

● ANODE CONNECTION

	1G~13G	14G	15G	16G	
1P	1-1	1-1	S2	S1	
2P	2-1	2-1	S26	S6	
3P	3-1	3-1	S27	S7	MATRIX
4P	4-1	4-1	S22	S8	DISCRETE
5P	5-1	5-1	1a	S9	
6P	1-2	1-2	1b	S10	
7P	2-2	2-2	1c	S11	ENHANCER
8P	3-2	3-2	1d	S12	
9P	4-2	4-2	1e		
10P	5-2	5-2	1f	S20	
11P	1-3	1-3	1g	SP	
12P	2-3	2-3	2a	A	
13P	3-3	3-3	2b	B	
14P	4-3	4-3	2c	SILENT CINEMA	
15P	5-3	5-3	2d	ZONE2	
16P	1-4	1-4	2e	NIGHT	
17P	2-4	2-4	2f	DOCK	NET
18P	3-4	3-4	2g	S21	USB
19P	4-4	4-4	S23	HiFi DSP	VCR
20P	5-4	5-4	S24	YPAO	
21P	1-5	1-5	S25	AUTO	
22P	2-5	2-5		TUNED	
23P	3-5	3-5	PHONO	STEREO	
24P	4-5	4-5	S13	MEMORY	
25P	5-5	5-5	S14	HD	
26P	1-6	1-6			
27P	2-6	2-6	MUTE	SECONDARY	
28P	3-6	3-6	DUAL	DRC	VIRTUAL
29P	4-6	4-6	96/24	PRESET	STANDARD
30P	5-6	5-6	ft	PTY HOLD	
31P	1-7	1-7		HOLD	
32P	2-7	2-7		PS	
33P	3-7	3-7		PTY	
34P	4-7	4-7		RT	
35P	5-7	5-7		CT	
36P	—	mS		EON	
37P	—	dB		SLEEP	

IC DATA

IC2 : M30625MHP-A98GP (DSP P.C.B.)
Microprocessor



IC2 : M30625MHP-A98GP (DSP P.C.B.)
Microprocessor

No.	Port Name	Terminal Name	I/O				Function
			PowerOn	Pure Direct	Standby	Sleep	
1	Vref	Vref	MCU		MCU	MCU	AD reference
2	Avcc	Avcc	MCU		MCU	MCU	AD power supply
3	P97/Adtrg/Sin4	CEFD	O		O	O	FL Driver CE
		MOD0			I		MODEL distinction 0
4	P96/ANEX1/SOUT4	DTFD	SO		O	O	FL Driver TxD
5	P95/ANEX0/CLK4	CKFD	SO		O	O	FL Driver CLOCK
6	P94/DA1/TB4in	LC	DA		O	O	Limiter control output
7	P93/DA0/TB3in	XMPWR	O		O	O	XM/DT BUS POWER CONTROL (U model)
8	P92/TB2in/SOUT3	SDM	SO		O	O	Serial data output to DIR, TI (DA70Y), DAC / DIR: 4M, LSBF/TI: 1M, MSBF
9	P91/TB1in/SIN3	SDD	SI		O	O	Serial data input from DIR, TI (DA70Y)
10	P90/TB0in/CLK3	SCK	SO		O	O	Serial clock output to DIR, TI (DA70Y) DAC
11	P141	/ICCNV	O	O	O	O	Reset I2C device of CONV (RX-V559 model)
12	P140	NW_RST	O		O	O	Reset signal to Net-module (RX-V559 model)
13	BYTE	BYTE	MCU		MCU	MCU	Vss : When single chip mode is used
14	CNVss	CNVss	MCU		MCU	MCU	Vss : When single chip mode is used, Vcc : When flash writing is used
15	P87/Xcin	MUTETI	O		O	O	MUTE of TI decoder DSP DA70Y (HI=MUTE)
16	P86/Xcout	/TIBUSY	I		O	O	TI BUSY detection / CDDA writing DATA input
17	/RESET	/RES	MCU		MCU	MCU	Reset
18	Xout	Xout	MCU		MCU	MCU	Oscillation output
19	Vss	Vss	MCU		MCU	MCU	Ground for microprocessor
20	Xin	Xin	MCU		MCU	MCU	Oscillation input
21	Vcc1	Vcc	MCU		MCU	MCU	Power supply +5V for microprocessor
22	P85/NMI	NMI	MCU		MCU	MCU	No used, connect Vss
23	P84/INT2	/INTTI	IRQ		O	O	Interrupt of TI decoder DSP DA70Y
24	P83/INT1	/INTDIR	IRQ		O	O	Interrupt of DIR
25	P82/INT0	/VSY	IRQ	O	O	O	Interrupt of Vertical sync Pulse (RX-V559/DSP-AX559 models)
26	P81/TA4in/U	/CSDIR	O		O	O	Chip enable of DIR
27	P80/TA4out/U	/CSTI	O		O	O	Chip enable of TI decoder DSP DA70Y
28	P77/TA3in	/CSDAC	O		O	O	Chip enable of DAC (2ch/8ch common)
29	P76/TA3out	/ICDIR	O		O	O	DIR reset
30	P75/TA2in/W	/ICTI	O		O	O	Reset of TI decoder DSP DA70Y
31	P74/TA2out/W	/SPIRDY	I		O	O	TI DA70Y Serial Ready / WCK input for CDDA writing
32	P73/CTS2/RTS2/TA1in/V	/CEEEP	O		O	O	EEPROM CE
33	P72/CLK2/TA1out/V	FET	O		O	O	Control of flash writing
34	P71/RXD2/SCL2/TA0in/TB5in	DRXM	SI		O	O	XMDT IC RxDU (U model)
35	P70/TXD2/SDA2/TA0out	DTXM	SO		O	O	XMDT IC TxDU
36	P67/TXD1/SDA1	SDA	SO	I	I	I	IIC data I/O for VIDEO (RX-V559/DSP-AX559 models)
		TXDF	SO				Data transmission terminal of AF220
37	Vcc1	Vcc	MCU		MCU	MCU	Power supply +5V for microprocessor
38	P66/RXD1/SCL1	SCL	SO	I	I	I	IIC clock I/O for VIDEO, Clock speed: 100kHz (RX-V559/DSP-AX559 models)
		RXDF	SO				Flash ROM RxD
39	Vss	Vss	MCU		MCU	MCU	Ground for microprocessor
40	P65/CLK1	N.C.	O		O	O	
		CLKF	SO				Clock transmission terminal signal output for AF220
41	P64/CTS1/RTS1/CTS0/CLKS1	BSY	O				BUSY signal output for AF220
42	P63/TXD0/SDA0	TXDi	SO		O	O	serial data output for iPod (HTR-5950 model)
		TXDNW	SO		O	O	serial data output for iPod/Net-module (RX-V559/DSP-AX559 models)
43	P62/RXD0/SCL0	RXDi	SI		O	O	Serial data input for iPod (HTR-5950 model)
		RXDNW	SI		O	O	Serial data output for iPod/Net-module (RX-V559/DSP-AX559 models)
44	P61/CLK0	iPDET	I		O	O	iPod detection
45	P60/CTS0/RTS0	iPAP	I		O	O	iPod accessories power detection
46	P137	Z2RY	O		O	O	
		YST	O		O	O	
47	P136	/4ohm	O		O	O	IMPEDANCE control / $\pm B$ voltage control
48	P135	SBRY	O		O	O	SURROUND BACK SP relay output
49	P134	SPC	O		O	O	CENTER and SURROUND SP relay output
50	P57/RDY/CLKout	SPB	O		O	O	FRONT B SP relay output

IC2 : M30625MHP-A98GP (DSP P.C.B.)
Microprocessor

No.	Port Name	Terminal Name	I/O				Function
			PowerOn	Pure Direct	Standby	Sleep	
51	P56/ALE	SPA	O		O	O	FRONT A SP relay output
52	P55/HOLD	/EMP	I				For FLASH writing (LO)
53	P54/HLDA	PRI	I		O	O	Protection overcurrent detection
54	P133	PSV	O		O	O	Power Save
55	P132	PRY	O		O	O	Power relay output
56	P131	MASTER	I		O	O	MASTER ON/OFF
57	P130	/BLK	O		O	O	FL Driver turning off
58	P53/BCLK	ISA	I		O	O	INPUT Selector Rotary A
59	P52/RD	ISB	I		O	O	INPUT Selector Rotary B
60	P51/WRH/BHE	TONEA	I		O	O	Tone Control Rotary A
61	P50/WRL/WR	/CE	I				For FLASH writing (HI)
62	P127	TONEB	I		O	O	Tone Control Rotary B
63	P126	VRA	I		O	O	Volume Rotary A
64	P125	VRB	I		O	O	Volume Rotary B
65	P47/CS3	VIA	O	O	O	O	VIDEO Selector A
66	P46/CS2	VIB	O	O	O	O	VIDEO Selector B
67	P45/CS1	VIC	O	O	O	O	VIDEO Selector C
68	P44/CS0	S/V	O	O	O	O	OSD input S/Composite change (RX-V559/DSP-AX559 models)
69	P43/A19	/CES	O	O	O	O	OSD Enable (RX-V559/DSP-AX559 models)
		MOD1	I				MODEL distinction 1
70	P42/A18	SVIDD	I	O	O	O	S-Video Signal Detector
71	P41/A17	BYPASS	O	O	O	O	VIDEO Bypass/ conversion change
72	P40/A16	/INTCNV	I	O	O	O	Interrupt request of VIDEO DEC/ENC IC (RX-V559/DSP-AX559 models)
73	P37/A15	/VR1	O	O	O	O	VIDEO Rec Out 1 MUTE
74	P36/A14	/VR2	O	O	O	O	
75	P35/A13	/PURD	O		O	I	
76	P34/A12	/MON	O	O	O	O	VIDEO Mon Out MUTE
77	P33/A11	CPNTD	I	O	O	O	Component Signal Detector (DVD)
78	P32/A10	CMP0	O	O	O	O	Component Selector 0
79	P31/A9	CMP1	O	O	O	O	Component Selector 1
80	P124	CBYPASS	O	O	O	O	Component Bypass/Conversion change (RX-V559/DSP-AX559 models)
81	P123	/CNONE	O	O	O	O	Component MonOut MUTE
82	P122	TRIG	O		O	O	DC TRIGGER input
83	P121	TMT	O		O	O	TUNER MUTE
84	P120	SDRN	I		O	O	RDS RxDBG
85	Vcc2	Vcc	MCU		MCU	MCU	Power supply +5V for microprocessor
86	P30/A8	SCKN	O		O	O	RDS IC Clock (G model)
			O	O	O	O	OSD IC Clock (RX-V559/DSP-AX559 models)
87	Vss	Vss	MCU		MCU	MCU	Ground for micro-processor
88	P27/A7	SDTN	O		O	O	RDS IC TxD (G model)
			O	O	O	O	OSD IC TxD (RX-V559/DSP-AX559 models)
89	P26/A6	RDSE	O		O	O	RDS Enable (G model)
		/ICXM	O		O	O	DABIC IC reset (U model)
90	P25/A5	SCKP	O		O	O	PLL IC Clock
91	P24/A4	SDTP	O		O	O	PLL IC TxD
92	P23/A3	CEP	O		O	O	PLL IC Enable
93	P22/A2	SDRP	I+		O	O	PLL IC RxT
94	P21/A1	/ST	I+		O	O	TUNER /ST
95	P20/A0	TUNED	I+		O	O	TUNED
96	P17/D15/INT5	PDET	IRQ		IRQ	O	Power Down DETECT INT
97	P16/D14/INT4	/PSW	IRQ		IRQ	O	Interrupt MASTER / MAIN / Zone2 Power SW
98	P15/D13/INT3	REM	IRQ		IRQ	O	Remote Control input
99	P14/D12	/HP	I		O	O	HEAD PHONE detection
100	P13/D11	/MTHP	O		O	O	HEAD PHONE MUTE input
101	P12/D10	/MTFS	O		O	O	MUTE Front/Surround, PreOUT
102	P11/D9	/MTCT	O		O	O	MUTE Center
103	P10/D8	/MTSW	O		O	O	MUTE SW
104	P07/D7	/MTZ2	O		O	O	Zone 2 MUTER
105	P06/D6	CKEV	O		O	O	Electron volume IC Clock

IC2 : M30625MHP-A98GP (DSP P.C.B.)
Microprocessor

No.	Port Name	Terminal Name	I/O				Function
			PowerOn	Pure Direct	Standby	Sleep	
106	P05/D5	DTEV	O		O	O	Electron volume IC DATA
107	P04/D4	CKZ2	O		O	O	Zone2 Selector (BD3841) Clock (R model)
108	P03/D3	DTZ2	O		O	O	Zone2 Selector (BD3841) DATA (R model)
109	P02/D2	N.C.	O		O	O	
110	P01/D1	N.C.	O		O	O	
111	P00/D0	CKEX	O		O	O	EX. INPUT Selector Clock
112	P117	DTEX	O		O	O	EX. INPUT Selector DATA
113	P116	CKBD	O		O	O	
114	P115	DTBD	O		O	O	
		MOD2			I		MODEL distinction 2
115	P114	DTSEL	O		O	O	
116	P113	CKSEL	O		O	O	
117	P112	CESEL	O		O	O	
		MOD4			I		MODEL distinction (RX-V559/DSP-AX559 models)
118	P111	ICEV	O		O	O	
119	P110	CEEV	O		O	O	
		MOD3			I		MODEL distinction (RX-V559 model)
120	P107/AN7/KI3	PRV2	AD		O	O	
121	P106/AN6/KI2	PRV1	AD		O	O	AD protection power-supply voltage detection
122	P105/AN5/KI1	PRD	AD		O	O	AD protection DC detection
123	P104/AN4/KI0	PLDET	AD		O	O	AD POWER LIMITER detection
124	P103/AN3	THM	AD		O	O	AD temperature detection
125	P102/AN2	ADKEY0	AD		O	O	AD Key 0
126	P101/AN1	ADKEY1	AD		O	O	AD Key 1
127	Avss	Avss	MCU		MCU	MCU	Ground for AD
128	P100/AN0	DEST	AD		O	O	AD model detection

RX-V559/DSP-AX559

Key Input(A-D) Pull-Up Resistance 10 k-Ohms

Ohm	+0.0k	+1.0k	+1.0k	+1.5k	+2.2k	+3.3k	+4.7k	+4.7k	+6.8k	+10.0k	+22.0k
V	~0.3	~0.7	~1.0	~1.5	~2.0	~2.6	~3.1	~3.4	~3.7	~4.0	~4.4
ADKEY0 94pin/AN2	MAIN/ZONE ON/OFF	—	—	—	INPUT MODE	STRAIGHT	TONE CONTROL	PRESET/TUNING	SPEAKER B	SPEAKER A	—
ADKEY1 95pin/AN1	ZONE2 ON/OFF	—	—	ZONE CONTROL	MULTI CH INPUT	FM/AM	A/B/C/D/E	PRESET/TUNING <	PRESET/TUNING >	MEMORY	TUNING MODE

HTR-5950

Key Input(A-D) Pull-Up Resistance 10 k-Ohms

Ohm	+0.0k	+1.0k	+1.0k	+1.5k	+2.2k	+3.3k	+4.7k	+4.7k	+6.8k	+10.0k	+22.0k
V	~0.3	~0.7	~1.0	~1.5	~2.0	~2.6	~3.1	~3.4	~3.7	~4.0	~4.4
ADKEY0 94pin/AN2	PROGRAM <	PROGRAM <	BASS/TREBLE —	BASS/TREBLE +	INPUT MODE	STRAIGHT	TONE CONTROL	PRESET/TUNING	SPEAKER B	SPEAKER A	PURE DIRECT
ADKEY1 95pin/AN1	—	—	—	—	MULTI CH INPUT	FM/AM	A/B/C/D/E	PRESET/TUNING <	PRESET/TUNING >	MEMORY	TUNING MODE

MODEL Distinction Port / モデル判別ポート



Pin	Function	Name	RX-V559/DSP-AX559	HTR-5950
3	P97/Adtrg/Sin4	CEFD/MOD0	0	1
69	P43/A19	CES/MOD1	0	0
114	P115	DTBD/MOD2	1	1
119	P110	CEEV/MOD3	0	0
117	P112	CESEL/MOD4	0	0

Distinction for AD Port / 仕向け先判別ポート

Pull-Up Resistance 10 k-Ohms

Ohm	0.0k	1.2k	2.7k	4.7k	6.8k	10.0k	15.0k	27.0k	47.0k	100.0k	∞
V	0-0.2	0.3-0.8	0.9-1.3	1.4-1.8	1.8-2.2	2.3-2.7	2.8-3.3	3.4-3.8	3.9-4.3	4.4-4.7	4.8-5.0
A-D (5V=255)	0-13	14-40	41-68	69-92	93-115	116-140	141-170	171-198	199-221	222-244	245-255
DEST 129pin	J	U, C	—	R	T	K	A	—	G, E	L	—

IC56 : LC89057W-VF4-E (DSP P.C.B)
Digital Audio Interface Transceiver




IC56 : LC89057W-VF4-E (DSP P.C.B)
Digital Audio Interface Transceiver

No.	Name	I/O	Function
1	RXOUT	O	Input bi-phase selection data output pin
2	RX0	Is	TTL-compatible digital data input pin
3	RX1	I	Coaxial-compatible digital data input pin with built-in amplifier
4	RX2	Is	TTL-compatible digital data input pin
5	RX3	Is	TTL-compatible digital data input pin
6	DGND		Digital GND
7	DVDD		Digital power supply
8	RX4	Is	TTL-compatible digital data input pin
9	RX5/VI	Is	TTL-compatible digital data / Validity flag input pin for modulation
10	RX6/UI	Is	TTL-compatible digital data / User data input pin for modulation
11	DVDD		PLL digital power supply
12	DGND		PLL digital GND
13	LPF	O	PLL loop filter connection pin
14	ACDD		PLL analog power supply
15	AGND		PLL analog GND
16	RMCK	O	R system clock output pin (256fs, 512fs, XIN, VCO)
17	RBCK	O/I	R bit clock input/output pin
18	DGND		Digital GND
19	DVDD		Digital power supply
20	RLRCK	O/I	R LR clock input/output pin (fs)
21	RDATA	O	Serial audio data input pin
22	SBCK	O	S bit clock output pin (32fs, 64fs, 128fs)
23	SLRCK	O	S LR clock output pin (fs/s, fs, 2fs)
24	SDIN	Is	Serial audio data input pin
25	DGND		Digital GND
26	DVDD		Digital power supply
27	XMCK	O	Oscillation amplifier output pin
28	XOUT	O	Crystal resonator connection output pin
29	XIN	I	Crystal resonator connection, external supply clock input pin (24.576 MHz or 12.288 MHz)
30	DVDD		Digital power supply
31	DGND		Digital GND
32	EMPHA/UO	I/O	Emphasis information / U data output / Chip address setting pin
33	AUDIO/VO	I/O	Non-PCM output / V flag output / Chip address setting pin
34	CKST	I/O	Clock switch transition period signal / Demodulation master or slave function switch pin
35	INT	I/O	Microcontroller interrupt output / Modulation or general-purpose I/O switch pin
36	RERR	O	PLL clock error, data error flag output
37	DO	O	Microcontroller I/F read data output pin (3-state)
38	DI	Is	Microcontroller I/F write data input pin
39	CE	Is	Microcontroller I/F chip enable input pin
40	CL	Is	Microcontroller I/F clock input pin
41	XMODE	Is	System reset input pin
42	DGND		Digital GND
43	DVDD		Digital power supply
44	TMCK/PIO0	I/O	Modulation 256fs system clock input / General-purpose I/O input/output pin
45	TMCK/PIO1	I/O	Modulation 64fs bit clock input / General-purpose I/O input/output pin
46	TLRCK/PIO2	I/O	Modulation fs clock input / General-purpose I/O input/output pin
47	TLRCK/PIO3	I/O	Modulation serial audio data input / General-purpose I/O input/output pin
48	TXO/PIOEN	O/I	Modulation data output / General-purpose I/O enable input pin

- 1) Input/output I or O = -0.3 to 3.6V, Is = -0.3 to 5.5V
- 2) Pins 32 and 33 are latch address setting input pins when pin 41 = "L".
- 3) Pin 34 is a demodulation function master or slave setting input pin when pin 41 = "L".
- 4) Pin 35 is a modulation function or general-purpose I/O function switch setting input pin when pin 41 = "L".
- 5) Perform ON/OFF for all power supplies with the same timing as a latch-up countermeasure.

IC60 : D70YE101RFP250 (DSP P.C.B)
Decoder/Post Processor

* No replacement part available. / サービス部品供給なし



RX-V559/HTR-5950/
DSP-AX559

IC60 : D70YE101RFP250 (DSP P.C.B)
Decoder/Post Processor

PIN NO.	SIGNAL NAME	TYPE ⁽¹⁾	PULL ⁽²⁾	GPIO ⁽³⁾	DESCRIPTION
1	Ground(Vss)				
2	AHCLKX0/AHCLKX2	IO	-	Y	McASP0 and McASP2 Transmit Master Clock
3	AMUTE0	IO	-	Y	McASP0 MUTE Output
4	AMUTE1	IO	-	Y	McASP1 MUTE Output
5	AHCLKX1	IO	-	Y	McASP1 Transmit Master Clock
6	Ground(Vss)				
7	ACLKX1	IO	-	Y	McASP1 Transmit Bit Clock
8	Core Supply (CVpp)				
9	ACLKR1	IO	-	Y	McASP1Receive Bit Clock
10	IO Supply (DVpp)				
11	AFSX1	IO	-	Y	McASP1 Transmit Frame Sync (L/R Clock)
12	AFSR1	IO	-	Y	McASP1Receive Frame Sync (L/R Clock)
13	Ground(Vss)				
14	RESET	IO	-	N	Device reset pin
15	Ground(Vss)				
16	Core Supply (CVpp)				
17	CLKIN	IO	-	N	Alternate clock input (3.3-V LVCMOS Input)
18	Ground(Vss)				
19	TMS	IO	IPU	N	Test mode Select
20	Core Supply (CVpp)				
21	TRST	IO	IPU	N	Test Reset
22	OSCVss	PWR	-	N	Oscillator Vss tap point (for filter only)
23	OSCIN	IO	-	N	1.2-V Oscillator Input
24	OSCOUt	O	-	N	1.2-V Oscillator Output
25	OSCVpp	PWR	-	N	Oscillator 1.2-V Vpp tap point (for filter only)
26	Ground(Vss)				
27	PLLHV	PWR	-	N	PLL 3.3-V Supply Input (requires external filter)
28	TDI	IO	IPU	N	Test Data In
29	TDO	OZ	IPU	N	Test Data Out
30	Ground(Vss)				
31	IO Supply (DVpp)				
32	EMU[0]	IO	IPU	N	Emulation Pin 0
33	Core Supply (CVpp)				
34	EMU[1]	IO	IPU	N	Emulation Pin 1
35	TCK	IO	IPU	N	Test Clock
36	Ground(Vss)				
37	EM_CAS	O	-	N	SDRAM Column Address Strobe
38	EM_WE	O	-	N	SDRAM Write Enable
39	EM_WE_DQM[0]	O	-	N	Write Enable or Byte Enable for EM_D[7:0]
40	Ground(Vss)				
41	EM_D[7]	IO	-	N	EMIF Data Bus [lower 16 Bits]
42	IO Supply (DVpp)				
43	EM_D[6]	IO	-	N	EMIF Data Bus [lower 16 Bits]
44	Core Supply (CVpp)				
45	EM_D[5]	IO	-	N	EMIF Data Bus [lower 16 Bits]
46	EM_D[4]	IO	-	N	EMIF Data Bus [lower 16 Bits]
47	Ground(Vss)				
48	EM_D[3]	IO	-	N	EMIF Data Bus [lower 16 Bits]
49	EM_D[2]	IO	-	N	EMIF Data Bus [lower 16 Bits]
50	IO Supply (DVpp)				
51	EM_D[1]	IO	-	N	EMIF Data Bus [lower 16 Bits]
52	EM_D[0]	IO	-	N	EMIF Data Bus [lower 16 Bits]
53	Core Supply (CVpp)				
54	Ground(Vss)				
55	EM_D[15]	IO	-	N	EMIF Data Bus [lower 16 Bits]

IC60 : D70YE101RFP250 (DSP P.C.B)
Decoder/Post Processor

PIN NO.	SIGNAL NAME	TYPE ⁽¹⁾	PULL ⁽²⁾	GPIO ⁽³⁾	DESCRIPTION
56	EM_D[14]	IO	-	N	EMIF Data Bus [lower 16 Bits]
57	Core Supply (CVpp)				
58	EM_D[13]	IO	-	N	EMIF Data Bus [lower 16 Bits]
59	EM_D[12]	IO	-	N	EMIF Data Bus [lower 16 Bits]
60	IO Supply (DVpp)				
61	EM_D[11]	IO	-	N	EMIF Data Bus [lower 16 Bits]
62	Ground(Vss)				
63	EM_D[10]	IO	-	N	EMIF Data Bus [lower 16 Bits]
64	EM_D[9]	IO	-	N	EMIF Data Bus [lower 16 Bits]
65	Core Supply (CVpp)				
66	EM_D[8]	IO	-	N	EMIF Data Bus [lower 16 Bits]
67	EM_WE_DQM[1]	O	-	N	Write Enable or Byte Enable for EM_D[15:8]
68	IO Supply (DVpp)				
69	Ground(Vss)				
70	EM_CLK	O	-	N	SDRAM Clock
71	EM_CKE	O	-	N	SDRAM Clock Enable
72	Ground(Vss)				
73	IO Supply (DVpp)				
74	EM_A[11]	O	-	N	EMIF Address Bus
75	EM_A[9]	O	-	N	EMIF Address Bus
76	EM_A[8]	O	-	N	EMIF Address Bus
77	Core Supply (CVpp)				
78	Ground(Vss)				
79	EM_A[7]	O	-	N	EMIF Address Bus
80	EM_A[6]	O	-	N	EMIF Address Bus
81	IO Supply (DVpp)				
82	Ground(Vss)				
83	EM_A[5]	O	-	N	EMIF Address Bus
84	EM_A[4]	O	-	N	EMIF Address Bus
85	Core Supply (CVpp)				
86	EM_A[3]	O	-	N	EMIF Address Bus
87	Ground(Vss)				
88	EM_A[2]	O	-	N	EMIF Address Bus
89	EM_A[1]	O	-	N	EMIF Address Bus
90	Core Supply (CVpp)				
91	EM_A[0]	O	-	N	EMIF Address Bus
92	IO Supply (DVpp)				
93	EM_A[10]	O	-	N	EMIF Address Bus
94	EM_BA[1]	O	-	N	SDRAM Bank Address and Asynchronous Memory LOW-Order Address
95	Ground(Vss)				
96	EM_BA[0]	O	-	N	SDRAM Bank Address and Asynchronous Memory LOW-Order Address
97	EM_CS[0]	O	-	N	SDRAM Chip Select
98	EM_RAS	O	-	N	SDRAM Row Address Strobe
99	Ground(Vss)				
100	EM_CS[2]	O	-	N	Asynchronous Memory Chip Select
101	Core Supply (CVpp)				
102	EM_RW	O	-	N	Asynchronous Memory Read/not Write
103	IO Supply (DVpp)				
104	EM_OE	O	-	N	SDRAM Output Enable
105	SPI0_ENA/I2C1_SDA	IO	-	Y	SPI0 Enable (Ready) or I2c1 Serial Data
106	Ground(Vss)				
107	SPI0_SCS/I2C1_SCL	IO	-	Y	SPI0 Slave Chip Select or I2c1 Serial Clock
108	SPI0_CLK/I2C0_SCL	IO	-	Y	SPI0 Serial Clock or I2c0 Serial Clock
109	Ground(Vss)				
110	SPI0_SIMO	IO	-	Y	SPI0 Data Pin Slave In Master Out


IC60 : D70YE101RFP250 (DSP P.C.B)
Decoder/Post Processor

PIN NO.	SIGNAL NAME	TYPE ⁽¹⁾	PULL ⁽²⁾	GPIO ⁽³⁾	DESCRIPTION
111	SPI0_SOMI/I2C0_SDA	IO	-	Y	SPI0 Data Pin Slave Out Master In or I2C0 Serial Data
112	IO Supply (DVpp)				
113	AXR0[0]	IO	-	Y	McASP0 Serial Data 0
114	Ground(Vss)				
115	AXR0[1]	IO	-	Y	McASP0 Serial Data 1
116	AXR0[2]	IO	-	Y	McASP0 Serial Data 2
117	AXR0[3]	IO	-	Y	McASP0 Serial Data 3
118	Ground(Vss)				
119	AXR0[4]	IO	-	Y	McASP0 Serial Data 4
120	AXR0[5]/SOI1_SCS	IO	-	Y	McASP0 Serial Data 5 or SPI1 Slave Chip Select
121	AXR0[6]/SPI1_ENA	IO	-	Y	McASP0 Serial Data 6 or SPI1 Enable (Ready)
122	AXR0[7]/SPI1_CLK	IO	-	Y	McASP0 Serial Data 7 or SPI1 Serial Clock
123	Core Supply (CVpp)				
124	Ground(Vss)				
125	IO Supply (DVpp)				
126	AXR0[8]/AXR1[5]/SPI1_SOMI	IO	-	Y	McASP0 Serial Data 8 or McASP1 Serial Data 5 or SPI1 Data Pin Slave Out Master In
127	AXR0[9]/AXR1[4]/SPI1_SIMO	IO	-	Y	McASP0 Serial Data 9 or McASP1 Serial Data 4 or SPI1 Data Pin Slave In Master Out
128	Core Supply (CVpp)				
129	Ground(Vss)	IO	-	Y	
130	AXR0[10]/AXR1[3]	IO	-	Y	McASP0 Serial Data 10 or McASP1 Serial Data 3
131	AXR0[11]/AXR1[2]				McASP0 Serial Data 11 or McASP1 Serial Data 2
132	Core Supply (CVpp)				
133	Ground(Vss)	IO	-	Y	
134	AXR0[12]/AXR1[1]	IO	-	Y	McASP0 Serial Data 12 or McASP1 Serial Data 1
135	AXR0[13]/AXR1[0]				McASP0 Serial Data 13 or McASP1 Serial Data 0
136	IO Supply (DVpp)	IO	-	Y	
137	AXR0[14]/AXR2[1]	IO	-	Y	McASP0 Serial Data 14 or McASP2 Serial Data 1
138	AXR0[15]/AXR2[0]	IO	-	Y	McASP0 Serial Data 15 or McASP2 Serial Data 0
139	ACLKR0				McASP0 Receive bit Clock
140	Ground(Vss)	IO	-	Y	
141	AFSR0	IO	-	Y	McASP0 Receive Frame Sync (L/R Clock)
142	ACLKX0	IO	-	Y	McASP0 Transmit Bit Clock
143	AHCLKR0/AHCLKR1	IO	-	Y	McASP0 and McASP1 Receive Master Clock
144	AFSX0				McASP0 Transmit Frame Sync (L/R Clock)





PIN CONNECTION DIAGRAM

• ICs


BD3816K1




BD3841FS


 TC74HC4051AF
 TC74HC4052AF
 TC74HC4053AF
 NJM2581M
F2602E-01
YAC523-EVR2
 LA7106M-TLM-E
 PCM1780DBQR
 PCM1781DBQR
 PCM1803DBR



BD3816K1




LA73050-TLM-E




LC72722PM




LC89057W-VF4A-E




LM61CIZ THERMAL






M30625MHP-A98GP





M66003-0131FP




NE5532DR OP AMP


 NJM2068LD
 NJM2068MD-TE2
 NJM4556AL

 NJM2388F05 5.0V
 NJM2388F33



NJM2581M VIDEO AMP


 NJM2885DL1-18
 NJM2885DL1-33





NJM4565M (TE1)




NJM7812FA




NJM78M05DL1A (TE1)


 NJM7805FA 5V
 NJM79M05FA
 NJM79M12FA

 NJU7311AM
 NJU7312AM
 NJU7313AM



PCM1680DBQR




R1172S121D-E2-F




RH5RE58AA-T1-FA




SN74AHC1G08DCKR




SN74AHCT08PWR





SN74AHCT1G32DCKR




SN74LV157APWR
SN74LVU04APWR


SN74LV245APWR TRAN

TC4013BP FF
TC74VHCU04FT INVER


W9816G6CH-7 SDRAM




YAC520-EE2




ADV7180



ADV7172



S29AL004D70TF1020



• Diodes





1N4002S
1SS133,176
1SS270A
1SS355
1SS380
1T2
MTZJ13A 13V
MTZJ15A 15V
MTZJ15B 15V
MTZJ2.4B 2.4V
MTZJ27B 27V
MTZJ30A 30V
MTZJ5.1C 5.1V

RB441Q-40 T-77
RB441Q-40 T-77D2SBA20 1.5A 200V
D5SB20 5A 200V


MA8030-L 2.9V
MA8051-M 5.1V
MA8056-M 5.6V
MA8068-L 6.6V
MA8068-M 6.8V
MA8075-H 7.7V
MA8091-M 9.1V
MA8100-M 10V

RB500V-40
RB501V-40
UDZ 3.6BTE-17 3.6V
UDZ5.1B 5.1V

MA8082-H 8.5V



S1NB20 1A 200V
S1NB60 1.0A 600V



• Transistors




2SA1015 Y
2SA933S Q,R
2SA949 O,Y
2SC1740S QRS
2SC1815 Y
2SC1890A D,E
2SC2229 O,Y
2SC2240 GR,BL

2SC3326 A,B
2SC3837K T146 N,P
2SC3906K T146 R,S

2SB1257
2SB1274 Q,R,S

2SA1695 O,P,Y
2SC4468 O,P,Y
2SD1915F S,T
2SD2014
2SK2158-T2B-A
2SK246 Y
2SK3288
2SK3850

2SA1708 S,T
2SA1770 S,T
2SC4488 S,T
2SC4614 S,T
2SD1938F S,T




2SA1037K Q,R,S
2SC2412K Q,R,S
DTA114ES
DTC114EKA
DTC114ES
DTC124EKA
DTC144ES




MEMO

AUDIO BLOCK DIAGRAM




VIDEO BLOCK DIAGRAM



DSP P.C.B. (Side B)
Lead Free Solder Used


RX-V559/DSP-AX559 model



• Semiconductor Location

Ref no.	Location	Ref no.	Location
D1	D5	D216	D6
D2	D5	D217	D6
D3	D5	Q2	C5
D6	C5	Q8	D5
D9	D5	Q9	D5
D10	D5		


Lead Free Solder Used



- Semiconductor Location

FUNCTION (2) P.C.B. (Side B)

Lead Free Solder Used




• Semiconductor Location

Ref no.	Location	Ref no.	Location
D2851	F5	D2863	E5
D2852	F5	D2864	E5
D2853	F5	D2865	E5
D2854	H4	D2866	E5
D2855	H4	D2867	E5
D2856	H4	IC286	D5
D2857	F5	IC287	G4
D2858	F5	IC288	H4
D2859	F5	IC289	F5
D2860	D5	IC290	G5
D2861	D5	IC291	E5
D2862	E5		


RX-V559/DSP-AX559/HTR-5950

RX-V559/DSP-AX559


OPERATION (1) P.C.B. (Side A)



OPERATION (2) P.C.B. (Side A)



OPERATION (3) P.C.B. (Side A)



PHONES
SILENT CINEMA

MASTER
ON OFF

Semiconductor Location

Ref no.	Location
D3001	H3

to TRANSFORMER


OPERATION (6) P.C.B. (Side A)

1

RX-V559/DSP-AX559

OPERATION (1) P.C.B. (Side B)
Lead Free Solder Used

2




3

4

OPERATION (3) P.C.B. (Side B)
Lead Free Solder Used

5



6

7

• Semiconductor Location

Ref no.	Location	Ref no.	Location
D3009	D4	D3023	C6
D3010	D3	D3028	D3
D3011	D3	IC301	F3
D3012	D3	Q3000	F3
D3019	H3	Q3001	F3
D3020	H3	Q3004	F3
D3021	G6	Q3008	G3
D3022	C6	Q3009	G3

2




2



- | Semiconductor | Location | Ref no. | Location |
|---------------|----------|---------|----------|
| D3000 | D5 | D3015 | D5 |
| D3003 | E5 | D3017 | D5 |
| D3004 | E6 | D3024 | G3 |
| D3005 | E5 | D3025 | G3 |
| D3006 | E4 | D3026 | G3 |
| D3007 | E4 | D3027 | G3 |
| D3008 | E4 | Q3002 | D5 |

→ FUNCTION (1) (CB205)






Circuit No.	RX-V559/DSP-AX759 models	HTR-5950model
J1074, 1075	O	X


Semiconductor Location			
Ref no	Location	Ref no	Location
D1000	C4	O1011	D4
D1001	E4	O1014	E5
D1002	D4	O1015	D5
D1003	C4	O1016	E5
D1004	F6	O1017	D5
D1005	F6	O1018	D5
D1006	D6	O1019	G6
D1007	F6	O1020	F6
D1008	F6	O1021	F6
D1009	E6	O1022	C6
D1010	C5	O1023	E6
D1011	C5	O1024	H6
D1012	D5	O1025	F6
D1013	D5	O1026	D6
D1014	G6	O1027	F6
D1015	G6	O1028	C6
D1016	C5	O1029	E6
D1017	F6	O1030	G6
D1018	F6	O1031	C4
D1019	G6	O1032	C5
D1020	D6	O1033	G6
D1021	F6	O1034	G6
D1022	C6	O1035	D6
D1023	E6	O1036	D6
D1024	H6	O1037	F6
D1025	H6	O1038	F6
D1032	F4	O1039	C6
D1033	C3	O1040	E6
D1034	C3	O1041	E6
D1035	H5	O1042	E6
D1036	H5	O1043	H6
D1037	D3	O1044	H6
D1038	D3	O1045	C5
D1039	H3	O1046	C5
D1040	G3	O1047	C4
D1041	G3	O1048A	G6
D1042	G3	O1048C	G6
D1043	E3	O1049A	D6
D1044	G3	O1049C	D6
D1045	G3	O1050A	F6
D1046	H4	O1050C	F6
D1047	D3	O1051A	C6
D1048	H4	O1051C	E6
D1049	D3	O1052A	C6
D1050	H5	O1052C	E6
D1053	D6	O1053A	H6
D1054	D6	O1053C	H6
D1055	F6	O1060	G6
D1056	G6	O1061	D5
D1057	E6	O1062	F5
D1058	H6	O1063	E5
D1060	H3	O1064	E5
D1061	F4	O1065	H5
D1061	F4	O1066	E4
D1001	E4	O1068	F4
D1002	D4	O1069	C2
D1003	E4	O1070	D3
D1004	C4	O1071	D3
D1005	D4	O1072	D3
D1007	E4	O1073	H3
D1008	E4	O1074	E3
D1009	E4	O1075	D3
D1010	C4	O1076	C3

VIDEO P.C.B.

Lead Free Solder Used




DSP



● 電圧は、内部抵抗10MΩの電圧計で測定したものです。
● 1. 印のある部品は、各特性値が示されています。部品の交換が必要な場合、
● 本図は、各特性値が示されています。部品の交換が必要な場合、
● 本図は、各特性値が示されています。部品の交換が必要な場合、










★ All voltages are measured with a 10MΩ VDC electronic volt meter.
★ Components having special characteristics are marked with a star.
★ Schematic diagram is subject to change without notice.



- ★ All voltages are measured with a 10M Ω DC electronic volt meter.
- ★ Components having special characteristics are marked !, and must be replaced with parts having specifications equal to those originally installed.
- ★ Schematic diagram is subject to change without notice.
- 電圧は、内部抵抗10M Ω の電圧計で測定したものです。
- 印のある部品は、安全特性確保のために、部品の交換が必要で、場合、パワースイッチに記号されている部品を使用しない要です。
- 本図面には標準部品が記載されています。元の部品と異なることがあります。

CAPACITOR		PARTS NAME
REMARKS	NO MARKS	ELECTROLYTIC CAPACITOR
⊗		TANTALUM CAPACITOR
⊗		CERAMIC CAPACITOR
⊗		CERAMIC TUBULAR CAPACITOR
⊗		POLYESTER FILM CAPACITOR
⊗		POLYSTYRENE FILM CAPACITOR
⊗		MICA CAPACITOR
⊗		POLYPROPYLENE FILM CAPACITOR
⊗		SEMICONDUCTIVE CERAMIC CAPACITOR

REMARKS	PARTS	NAME
NO MARK	CARBON FILM RESISTOR	(P=5)
☒	CARBON FILM RESISTOR	(P=10)
☒	METAL OXIDE FILM RESISTOR	
☒	METAL FILM RESISTOR	
☒	METAL PLATE RESISTOR	
☒	FIRE PROOF CARBON FILM RESISTOR	
☒	CEMENT MOLDED RESISTOR	
☒	SEMI VARIABLE RESISTOR	
☒	CHIP RESISTOR	



- ★ All voltages are measured with a 10M Ω V DC electronic volt meter.
- ★ Components having special characteristics are marked ∇ , and must with parts having specifications equal to those originally installed.
- ★ Schematic diagram is subject to change without notice.

- 電圧は、内部抵抗10MΩの電圧計で測定したものです。
- ▲印のある部品は、安全性確保部品を示しています。部品の交換が必要です。
- パーツリストに記載されている部品を使用してください。
- 本回路図は標準回路図です。改良のため予告なく変更することがあります。





OPERATION HTR-5950

[illegible]



NOTICE (model1)

(J)..... JAPAN
(U)..... U.S.A
(C)..... CANADA
(R)..... GENERAL
(Y)..... CHINA
(K)..... KOREA
(A)..... AUSTRALIA
(B)..... BRITISH
(G)..... EUROPE
(L)..... SINGAPORE
(E)..... SOUTH EUROPE
(V)..... TAIWAN


RESISTOR		CAPACITOR	
REMARKS	PARTS NAME	REMARKS	PARTS NAME
NO MARK	CARBON FILM RESISTOR	NO MARK	ELECTROLYTIC CAPACITOR
Δ	METAL OXIDE FILM RESISTOR	NO MARK	CERAMIC CAPACITOR
Δ	METAL OXIDE FILM RESISTOR	NO MARK	CHEMICAL CAPACITOR
Δ	METAL FILM RESISTOR	○	NON-POLYMER FILM CAPACITOR
Δ	WIRE WOUND RESISTOR	○	POLYESTER FILM CAPACITOR
Δ	FLUX CROCK RESISTOR	○	MICA CAPACITOR
Δ	CEMENT WOUND RESISTOR	○	POLYPROPYLENE FILM CAPACITOR
Δ	CHIP RESISTOR	○	POLYBUTYLENE FILM CAPACITOR



Interchangeable Parts at		Manufacturer's Logo	
Part Number	Part Name	Part Number	Part Name
1	2003-2006	2003-2006	2003-2006
2	2003-2006	2003-2006	2003-2006
3	2003-2006	2003-2006	2003-2006
4	2003-2006	2003-2006	2003-2006
5	2003-2006	2003-2006	2003-2006
6	2003-2006	2003-2006	2003-2006
7	2003-2006	2003-2006	2003-2006
8	2003-2006	2003-2006	2003-2006
9	2003-2006	2003-2006	2003-2006
10	2003-2006	2003-2006	2003-2006
11	2003-2006	2003-2006	2003-2006
12	2003-2006	2003-2006	2003-2006
13	2003-2006	2003-2006	2003-2006
14	2003-2006	2003-2006	2003-2006
15	2003-2006	2003-2006	2003-2006
16	2003-2006	2003-2006	2003-2006
17	2003-2006	2003-2006	2003-2006
18	2003-2006	2003-2006	2003-2006
19	2003-2006	2003-2006	2003-2006
20	2003-2006	2003-2006	2003-2006
21	2003-2006	2003-2006	2003-2006
22	2003-2006	2003-2006	2003-2006
23	2003-2006	2003-2006	2003-2006
24	2003-2006	2003-2006	2003-2006
25	2003-2006	2003-2006	2003-2006
26	2003-2006	2003-2006	2003-2006
27	2003-2006	2003-2006	2003-2006
28	2003-2006	2003-2006	2003-2006
29	2003-2006	2003-2006	2003-2006
30	2003-2006	2003-2006	2003-2006
31	2003-2006	2003-2006	2003-2006
32	2003-2006	2003-2006	2003-2006
33	2003-2006	2003-2006	2003-2006
34	2003-2006	2003-2006	2003-2006
35	2003-2006	2003-2006	2003-2006
36	2003-2006	2003-2006	2003-2006
37	2003-2006	2003-2006	2003-2006
38	2003-2006	2003-2006	2003-2006
39	2003-2006	2003-2006	2003-2006
40	2003-2006	2003-2006	2003-2006
41	2003-2006	2003-2006	2003-2006
42	2003-2006	2003-2006	2003-2006
43	2003-2006	2003-2006	2003-2006
44	2003-2006	2003-2006	2003-2006
45	2003-2006	2003-2006	2003-2006
46	2003-2006	2003-2006	2003-2006
47	2003-2006	2003-2006	2003-2006
48	2003-2006	2003-2006	2003-2006
49	2003-2006	2003-2006	2003-2006
50	2003-2006	2003-2006	2003-2006
51	2003-2006	2003-2006	2003-2006
52	2003-2006	2003-2006	2003-2006
53	2003-2006	2003-2006	2003-2006
54	2003-2006	2003-2006	2003-2006
55	2003-2006	2003-2006	2003-2006
56	2003-2006	2003-2006	2003-2006
57	2003-2006	2003-2006	2003-2006
58	2003-2006	2003-2006	2003-2006
59	2003-2006	2003-2006	2003-2006
60	2003-2006	2003-2006	2003-2006
61	2003-2006	2003-2006	2003-2006
62	2003-2006	2003-2006	2003-2006
63	2003-2006	2003-2006	2003-2006
64	2003-2006	2003-2006	2003-2006
65	2003-2006	2003-2006	2003-2006
66	2003-2006	2003-2006	2003-2006
67	2003-2006	2003-2006	2003-2006



VIDEO



■ REPLACEMENT PARTS LIST

• ELECTRICAL COMPONENT PARTS

WARNING

- Components having special characteristics are marked $\triangle$ and must be replaced with parts having specifications equal to those originally installed.
- $\triangle$ 印のある部分は、安全確保部品を示しています。部品の交換が必要な場合、パーツリストに記載されている部品を使用してください。
- 部品価格ランクは、予告なく変更することがあります。

ABBREVIATIONS IN THIS LIST ARE AS FOLLOWS:

C.A.EL.CHP	: CHIP ALUMI.ELECTROLYTIC CAP	L.EMIT	: LIGHT EMITTING MODULE
C.CE	: CERAMIC CAP	LED.DSPLY	: LED DISPLAY
C.CE.ARRAY	: CERAMIC CAP ARRAY	LED.INFRD	: LED, INFRARED
C.CE.CHP	: CHIP CERAMIC CAP	MODUL.RF	: MODULATOR, RF
C.CE.ML	: MULTILAYER CERAMIC CAP	PHOT.CPL	: PHOTO COUPLER
C.CE.M.CHP	: CHIP MULTILAYER CERAMIC CAP	PHOT.INTR	: PHOTO INTERRUPTER
C.CE.SAFETY	: RECOGNIZED CERAMIC CAP	PHOT.RFLCT	: PHOTO REFLECTOR
C.CE.TUBLR	: CERAMIC TUBULAR CAP	PIN.TEST	: PIN, TEST POINT
C.CE.SMI	: SEMI CONDUCTIVE CERAMIC CAP	PLST.RIVET	: PLASTIC RIVET
C.EL	: ELECTROLYTIC CAP	R.ARRAY	: RESISTOR ARRAY
C.MICA	: MICA CAP	R.CAR.	: CARBON RESISTOR
C.ML.FLM	: MULTILAYER FILM CAP	R.CAR.CHP	: CHIP RESISTOR
C.MP	: METALLIZED PAPER CAP	R.CAR.FP	: FLAME PROOF CARBON RESISTOR
C.MYLAR	: MYLAR FILM CAP	R.FUS	: FUSABLE RESISTOR
C.MYLAR.ML	: MULTILAYER MYLAR FILM CAP	R.MTL.CHP	: CHIP METAL FILM RESISTOR
C.PAPER	: PAPER CAPACITOR	R.MTL.FLM	: METAL FILM RESISTOR
C.PLS	: POLYSTYRENE FILM CAP	R.MTL.OXD	: METAL OXIDE FILM RESISTOR
C.POL	: POLYESTER FILM CAP	R.MTL.PLAT	: METAL PLATE RESISTOR
C.POLY	: POLYETHYLENE FILM CAP	RSNR.CE	: CERAMIC RESONATOR
C.PP	: POLYPROPYLENE FILM CAP	RSNR.CRYS	: CRYSTAL RESONATOR
C.TNTL	: TANTALUM CAP	R.TW.CEM	: TWIN CEMENT FIXED RESISTOR
C.TNTL.CHP	: CHIP TANTALUM CAP	R.CEMENT	: CEMENT RESISTOR
C.TRIM	: TRIMMER CAP	SCR.BND.HD	: BIND HEAD B-TIGHT SCREW
CN	: CONNECTOR	SCR.BW.HD	: BW HEAD TAPPING SCREW
CN.BS.PIN	: CONNECTOR, BASE PIN	SCR.CUP	: CUP TIGHT SCREW
CN.CANNON	: CONNECTOR, CANNON	SCR.TERM	: SCREW TERMINAL
CN.DIN	: CONNECTOR, DIN	SCR.TR	: SCREW, TRANSISTOR
CN.FLAT	: CONNECTOR, FLAT CABLE	SUPRT.PCB	: SUPPORT, P.C.B.
CN.POST	: CONNECTOR, BASE POST	SURG.PRTCT	: SURGE PROTECTOR
COIL.MX.AM	: COIL, AM MIX	SW.TACT	: TACT SWITCH
COIL.AT.FM	: COIL, FM ANTENNA	SW.LEAF	: LEAF SWITCH
COIL.DT.FM	: COIL, FM DETECT	SW.LEVER	: LEVER SWITCH
COIL.MX.FM	: COIL, FM MIX	SW.MICRO	: MICRO SWITCH
COIL.OUTPT	: OUTPUT COIL	SW.PUSH	: PUSH SWITCH
DIOD.ARRAY	: DIODE ARRAY	SW.RT.ENC	: ROTARY ENCODER
DIODE.BRG	: DIODE BRIDGE	SW.RT.MTR	: ROTARY SWITCH WITH MOTOR
DIODE.CHP	: CHIP DIODE	SW.RT	: ROTARY SWITCH
DIODE.VAR	: VARACTOR DIODE	SW.SLIDE	: SLIDE SWITCH
DIOD.Z.CHP	: CHIP ZENER DIODE	TERM.SP	: SPEAKER TERMINAL
DIODE.ZENR	: ZENER DIODE	TERM.WRAP	: WRAPPING TERMINAL
DSCR.CE	: CERAMIC DISCRIMINATOR	THRMST.CHP	: CHIP THERMISTOR
FER.BEAD	: FERRITE BEADS	TR.CHP	: CHIP TRANSISTOR
FER.CORE	: FERRITE CORE	TR.DGT	: DIGITAL TRANSISTOR
FET.CHP	: CHIP FET	TR.DGT.CHP	: CHIP DIGITAL TRANSISTOR
FL.DSPLY	: FLUORESCENT DISPLAY	TRANS	: TRANSFORMER
FLTR.CE	: CERAMIC FILTER	TRANS.PULS	: PULSE TRANSFORMER
FLTR.COMB	: COMB FILTER MODULE	TRANS.PWR	: POWER TRANSFORMER ASS'Y
FLTR.LC.RF	: LC FILTER, EMI	TUNER.AM	: TUNER PACK, AM
GND.MTL	: GROUND PLATE	TUNER.FM	: TUNER PACK, FM
GND.TERM	: GROUND TERMINAL	TUNER.PK	: FRONT-END TUNER PACK
HOLDER.FUS	: FUSE HOLDER	VR	: ROTARY POTENTIOMETER
IC.PRTCT	: IC PROTECTOR	VR.MTR	: POTENTIOMETER WITH MOTOR
JUMPER.CN	: JUMPER CONNECTOR	VR.SW	: POTENTIOMETER WITH ROTARY SW
JUMPER.TST	: JUMPER, TEST POINT	VR.SLIDE	: SLIDE POTENTIOMETER
L.DTCT	: LIGHT DETECTING MODULE	VR.TRIM	: TRIMMER POTENTIOMETER

RX-V559/DSP-AX559

HTR-5950

P.C.B. DSP

Ref. No.	Part No.	Description		Remarks	Markets	部 品 名		Rank
	WG681000	P. C. B.	DSP	559	J	P C B	D S P	
	WG681100	P. C. B.	DSP	559	UC	P C B	D S P	
	WG681200	P. C. B.	DSP	559	R	P C B	D S P	
	WG681300	P. C. B.	DSP	559	T	P C B	D S P	
	WG681400	P. C. B.	DSP	559	K	P C B	D S P	
	WG681500	P. C. B.	DSP	559	A	P C B	D S P	
	WG681700	P. C. B.	DSP	559	GE	P C B	D S P	
	WG681800	P. C. B.	DSP	559	L	P C B	D S P	
	WG682000	P. C. B.	DSP	5950	UC	P C B	D S P	
	WG956300	P. C. B.	DSP	5950	T	P C B	D S P	
	WG682100	P. C. B.	DSP	5950	A	P C B	D S P	
CB1	VQ047900	CN	29P			F F C コネクター		03
CB2	VP082900	CN. BS. PIN	25P			F F C コネクター		02
CB3	VB390400	CN. BS. PIN	8P			ベースピン		01
CB4	VB390200	CN. BS. PIN	6P			コネクタベースポスト		01
CB5	VM689000	CN. BS. PIN	23P			F F C コネクター		02
CB7	VQ044400	CN. BS. PIN	9P			F F C コネクター		01
CB9	VB390300	CN. BS. PIN	7P			ベースピン		01
CB52	WE161800	CN. BS. PIN	4P		UC	シリアルバスコネクタ		
CB56	VQ047500	CN. BS. PIN	20P			F F C コネクター		01
CB57	VB390600	CN. BS. PIN	10P			コネクタベースポスト		01
C1	US064100	C. CE. CHP	0.01uF 50V B			チップセラコン		01
C2	US062100	C. CE. CHP	100pF 50V B			チップセラコン		01
C3	UR868100	C. EL	100uF 50V			ケミコン		01
C4	US063100	C. CE. CHP	1000pF 50V B			チップセラコン		01
C5-7	US062100	C. CE. CHP	100pF 50V B			チップセラコン		01
C8	US135100	C. CE. CHP	0.1uF 16V			チップセラコン		01
C9	UR867100	C. EL	10uF 50V			ケミコン		01
C10	UR837100	C. EL	10uF 16V			ケミコン		01
C11	UR818220	C. EL	220uF 6.3V			ケミコン		01
C12	WB165500	C. EL	0.33F 5.5V			ゴールドキャパシタ		
C13	UR818220	C. EL	220uF 6.3V			ケミコン		01
C14	UR837330	C. EL	33uF 16V			ケミコン		01
C15	UR838100	C. EL	100uF 16V			ケミコン		01
C16-21	US135100	C. CE. CHP	0.1uF 16V			チップセラコン		01
C22-31	US063100	C. CE. CHP	1000pF 50V B			チップセラコン		01
C32-36	UR866220	C. EL	2.2uF 50V			ケミコン		01
C37-39	US135100	C. CE. CHP	0.1uF 16V			チップセラコン		01
C40-48	US064100	C. CE. CHP	0.01uF 50V B			チップセラコン		01
C50-63	US135100	C. CE. CHP	0.1uF 16V			チップセラコン		01
C201	US061220	C. CE. CHP	22pF 50V B			チップセラコン		01
C202-205	US135100	C. CE. CHP	0.1uF 16V			チップセラコン		01
C208	US135100	C. CE. CHP	0.1uF 16V			チップセラコン		01
C209	UR847220	C. EL	22uF 25V			ケミコン		01
C210	UR238100	C. EL	100uF 16V			ケミコン		
C211	WG251600	C. CE. CHP	4.7uF 6.3V			チップセラ		
C212	UR237470	C. EL	47uF 16V			ケミコン		
C215	US060500	C. CE. CHP	5pF 50V B		UC	チップセラコン		01
C216-217	US035100	C. CE. CHP	0.1uF 16V B		UC	チップセラコン		01
C218	US060500	C. CE. CHP	5pF 50V B		UC	チップセラコン		01
C219	US135100	C. CE. CHP	0.1uF 16V		UC	チップセラコン		01
C220	US035100	C. CE. CHP	0.1uF 16V B		UC	チップセラコン		01
C221	WG251600	C. CE. CHP	4.7uF 6.3V			チップセラ		
C222	US135100	C. CE. CHP	0.1uF 16V			チップセラコン		01
C223	UR019220	C. EL	2200uF 6.3V			ケミコン		
C224	UR238100	C. EL	100uF 16V			ケミコン		
C225	WG251600	C. CE. CHP	4.7uF 6.3V			チップセラ		
C226-227	US135100	C. CE. CHP	0.1uF 16V		UC	チップセラコン		01
C228	US135330	C. CE. CHP	0.33uF 16V			チップセラコン		01
C229	UR038100	C. EL	100uF 16V			ケミコン		

* New Parts * 新規部品

RX-V559/DSP-AX559

HTR-5950

P.C.B. DSP

Ref. No.	Part No.	Description			Remarks	Markets	部 品 名	Rank
C230-231	US135100	C. CE. CHP	0.1uF	16V		UC	チップセラコン	01
C232-233	US135100	C. CE. CHP	0.1uF	16V			チップセラコン	01
C234	VE326000	C. MYLAR	0.1uF	50V		UC	マイラーコン	01
C235	UA654220	C. MYLAR	0.022uF	50V J			マイラーコン	01
C236-238	US135100	C. CE. CHP	0.1uF	16V			チップセラコン	01
C239	US062100	C. CE. CHP	100pF	50V B			チップセラコン	01
C241	US135100	C. CE. CHP	0.1uF	16V			チップセラコン	01
C242	UR238100	C. EL	100uF	16V			ケミコン	01
C243	US062100	C. CE. CHP	100pF	50V B			チップセラコン	01
C244	UR238100	C. EL	100uF	16V			ケミコン	01
C245-246	US135100	C. CE. CHP	0.1uF	16V			チップセラコン	01
C247	US062100	C. CE. CHP	100pF	50V B			チップセラコン	01
C248	UR238100	C. EL	100uF	16V			ケミコン	
C249-250	US061180	C. CE. CHP	18pF	50V B			チップセラコン	01
C251	UR238100	C. EL	100uF	16V			ケミコン	
C252	UR867100	C. EL	10uF	50V			ケミコン	01
C253	US126100	C. CE. CHP	1uF	10V			チップセラコン	01
C254	US035100	C. CE. CHP	0.1uF	16V B			チップセラコン	01
C255-283	US135100	C. CE. CHP	0.1uF	16V			チップセラコン	01
C284	UR837470	C. EL	47uF	16V			ケミコン	01
C285-286	US135100	C. CE. CHP	0.1uF	16V			チップセラコン	01
C287-289	US063100	C. CE. CHP	1000pF	50V B			チップセラコン	01
C290	US035100	C. CE. CHP	0.1uF	16V B		チップセラコン	01	
C291	US135100	C. CE. CHP	0.1uF	16V		チップセラコン	01	
C292-294	US063100	C. CE. CHP	1000pF	50V B		チップセラコン	01	
C295-299	US135100	C. CE. CHP	0.1uF	16V		チップセラコン	01	
C300	US135100	C. CE. CHP	0.1uF	16V		チップセラコン	01	
C301-313	US061470	C. CE. CHP	47pF	50V B		チップセラコン	01	
C314	US064100	C. CE. CHP	0.01uF	50V B		チップセラコン	01	
C315	UR837100	C. EL	10uF	16V		ケミコン	01	
C316-317	US064100	C. CE. CHP	0.01uF	50V B		チップセラコン	01	
C318	US135100	C. CE. CHP	0.1uF	16V		チップセラコン	01	
C319	UR238100	C. EL	100uF	16V		ケミコン	01	
C320	US126100	C. CE. CHP	1uF	10V		チップセラコン	01	
C321	US135330	C. CE. CHP	0.33uF	16V		チップセラコン	01	
C322	US062100	C. CE. CHP	100pF	50V B		チップセラコン	01	
C323	US035100	C. CE. CHP	0.1uF	16V B		チップセラコン	01	
C324	UR837100	C. EL	10uF	16V		ケミコン	01	
C325-326	US126100	C. CE. CHP	1uF	10V		チップセラコン	01	
C327	UR837100	C. EL	10uF	16V	559	UC	ケミコン	01
C328	US135100	C. CE. CHP	0.1uF	16V	559	UC	チップセラコン	01
C329	US135100	C. CE. CHP	0.1uF	16V			チップセラコン	01
C330	UR238100	C. EL	100uF	16V			ケミコン	01
C331	UR838100	C. EL	100uF	16V	559	UC	ケミコン	01
C332	UR837100	C. EL	10uF	16V			ケミコン	01
C333	US135100	C. CE. CHP	0.1uF	16V			チップセラコン	01
C334	UR837100	C. EL	10uF	16V			ケミコン	01
C335	US135100	C. CE. CHP	0.1uF	16V			チップセラコン	01
C336	UR238100	C. EL	100uF	16V			ケミコン	01
C337-340	US135100	C. CE. CHP	0.1uF	16V			チップセラコン	01
C341-347	UR837100	C. EL	10uF	16V			ケミコン	01
C348-349	UR837470	C. EL	47uF	16V	559	UC	ケミコン	01
C350-351	UA654100	C. MYLAR	0.01uF	50V J			マイラーコン	01
C352-354	US062680	C. CE. CHP	680pF	50V B			チップセラコン	01
C355	UA654470	C. MYLAR	0.047uF	50V J			マイラーコン	01
C356-358	US062680	C. CE. CHP	680pF	50V B			チップセラコン	01
C359-360	US163100	C. CE. CHP	1000pF	50V	559	UC	チップセラコン	01
C361-362	UR837100	C. EL	10uF	16V			ケミコン	01
C363-364	US163100	C. CE. CHP	1000pF	50V	559	UC	チップセラコン	01
C365-367	US062100	C. CE. CHP	100pF	50V B			チップセラコン	01

* New Parts * 新規部品

RX-V559/DSP-AX559

HTR-5950

P.C.B. DSP

Ref. No.	Part No.	Description	Remarks	Markets	部 品 名	Rank
C368	UA653390	C. MYLAR	3900pF 50V J		マイラーコン	01
C369-371	US062100	C. CE. CHP	100pF 50V B		チップセラコン	01
C373-390	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C391-392	US135100	C. CE. CHP	0.1uF 16V	559	チップセラコン	01
C393-398	UR237470	C. EL	47uF 16V	UC	ケミコン	01
C399	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C400-402	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C403-408	US062220	C. CE. CHP	220pF 50V B		チップセラコン	01
C409-410	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C411-412	US064100	C. CE. CHP	0.01uF 50V B		チップセラコン	01
C413	US062680	C. CE. CHP	680pF 50V B		チップセラコン	01
C416	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
D1-2	VT332900	DIODE	1SS355		ダイオード	01
D3	VV833200	DIODE	1SS380		ダイオード	01
D4-5	VU992600	DIODE. ZENR	MA8051-M 5.1V		ツェナーダイオード	01
D6	VT332900	DIODE	1SS355		ダイオード	01
D7-9	VU992600	DIODE. ZENR	MA8051-M 5.1V		ツェナーダイオード	01
D10	VT332900	DIODE	1SS355		ダイオード	01
D201-203	WE674800	DIODE	AVRL161A1R1NTB	UC	チップバリスタ	01
D204	VT332900	DIODE	1SS355		ダイオード	01
D206	VT332900	DIODE	1SS355		ダイオード	01
D208-210	VT332900	DIODE	1SS355		ダイオード	01
D212-215	WB081800	DIODE	SB01-05Q		ショットキーダイオード	01
D216-217	VT332900	DIODE	1SS355		ダイオード	01
IC1	X5886A00	IC	RH5RE58AA-T1-FA		電源IC	04
* IC2	X7361A00	IC. CPU	M30625MHP-A98GP	MASK ROM	IC CPU	
IC4-5	X2080A00	IC	SN74AHCT1G32DCKR		ロジックIC	01
IC6	X3833A00	IC	SN74AHC1G08DCKR		ロジックIC	01
IC51	XS534A00	IC	NJM78M05DL1A (TE1)		電源IC	02
IC52	X3936A00	IC	SN74LVU04APWR		ロジックIC	
* IC53	X7195A00	IC	R1172S121D-E2-F		電源IC	
IC54	X6869A00	IC	NJM2885DL1-33		電源IC	03
* IC55	X6227B00	IC	F2602E-01	UC	CPU/周辺IC	
IC56	X6989A00	IC	LC89057W-VF4A-E		IC	07
IC58	X6123A00	IC	SN74LV157APWR	UC	ロジックIC	02
IC59	X3833A00	IC	SN74AHC1G08DCKR	UC	ロジックIC	01
IC61	X2080A00	IC	SN74AHCT1G32DCKR	UC	ロジックIC	01
IC62	X2080A00	IC	SN74AHCT1G32DCKR		ロジックIC	01
IC63	X3824A00	IC	SN74AHC08PWR		ロジックIC	01
IC64	X2590B00	IC	W9816G6CH-7 SDRAM		メモリIC 16M	06
IC65	X3693A00	IC	SN74LV245APWR TRAN		ロジックIC	
* IC66	X7577A00	IC	S29AL004D70TF1020		メモリIC 4M	
IC67	X6123A00	IC	SN74LV157APWR		ロジックIC	02
* IC68	X7355A00	IC	PCM1680DBQR		IC	
* IC69	X7375A00	IC	PCM1781DBQR	559	IC	
* IC70	X7357A00	IC	PCM1803DBR		IC	
* IC71-74	X7378A00	IC	NJM4565M (TE1)		アンプIC	
* IC75	X7378A00	IC	NJM4565M (TE1)	559	アンプIC	
* IC76	X7378A00	IC	NJM4565M (TE1)		アンプIC	
J201-202		R. CHP	0Ω 1/16W J	UC	チップ抵抗	
J203-206		R. CHP	0Ω 1/16W J	JRTKAGEL	チップ抵抗	
PJ51	V4483900	JACK. PIN	1P YKC21-3895N		ピンジャック	02
PN1-3	V9637500	PIN	L=70 #18		スタイルピン	
Q1	VP872600	TR	2SA1708 S, T		トランジスタ	01
Q2	VV655700	TR. DGT	DTC144EKA		デジタルトランジスタ	01
Q3-7	VV556500	TR	2SA1037K Q, R, S		トランジスタ	01
Q8	WF767900	FET	5HP01C-TB-E		FET	01
Q9	WF767900	FET	5HP01C-TB-E		FET	01
R21		R. CHP	10Ω 1/16W J	J	チップ抵抗	
R21		R. CHP	1.2KΩ 1/16W J	UC	チップ抵抗	

* New Parts * 新規部品

RX-V559/DSP-AX559

HTR-5950

P.C.B. DSP & P.C.B. FUNCTION

Ref. No.	Part No.	Description		Remarks	Markets	部 品 名	Rank
R21	HV753100	R. CHP	4.7KΩ 1/16W J	559	R	チップ抵抗	01
R21		R. CHP	6.8KΩ 1/16W J		T	チップ抵抗	
R21		R. CHP	10KΩ 1/16W J		K	チップ抵抗	
R21		R. CHP	15KΩ 1/16W J		A	チップ抵抗	
R21		R. CHP	47KΩ 1/16W J		GE	チップ抵抗	
R21		R. CHP	100KΩ 1/16W J		L	チップ抵抗	
R23		R. CHP	15KΩ 1/16W J		JRTKAGEL	チップ抵抗	
R47		R. CHP	100Ω 1/16W J		UC	チップ抵抗	
R52-54		R. CHP	100Ω 1/16W J		UC	チップ抵抗	
R209		R. CAR. FP	1Ω 1/4W			不燃化カーボン抵抗	
R211		R. CHP	470Ω 1/16W J		UC	チップ抵抗	
R212		R. CHP	1MΩ 1/16W J		UC	チップ抵抗	
R215-216		R. CHP	100Ω 1/16W J		UC	チップ抵抗	
R217-218		R. CHP	1KΩ 1/16W J		UC	チップ抵抗	
R219	V8070000	R. MTL. FLM	1Ω 1W		金属被膜抵抗	01	
R221-224	R. CHP	270Ω 1/16W J	UC	チップ抵抗			
R225	V8070000	R. CHP	470KΩ 1/16W J	UC	チップ抵抗	01	
R226		R. MTL. FLM	1Ω 1W		金属被膜抵抗		
R228	HV753100	R. CHP	100KΩ 1/16W J	UC	チップ抵抗	01	
R229		R. CHP	470KΩ 1/16W J	UC	チップ抵抗		
R232-234		R. CHP	100KΩ 1/16W J	UC	チップ抵抗		
R240		R. CHP	47Ω 1/16W J	UC	チップ抵抗		
R241		R. CHP	22Ω 1/16W J	UC	チップ抵抗		
R251-252		R. CHP	47Ω 1/16W J	UC	チップ抵抗		
R319		R. CAR. FP	1Ω 1/4W		不燃化カーボン抵抗		
R320	V8070400	R. MTL. FLM	15Ω 1W		金属被膜抵抗		01
R322	HV753100	R. CAR. FP	1Ω 1/4W	UC	不燃化カーボン抵抗		
R323-324	VU224000	R. MTL. FLM	0.22Ω 1W		金属被膜抵抗	01	
R325-326	V8070100	R. MTL. FLM	2.2Ω 1W		金属被膜抵抗	01	
R334-335	WG559700	R. CHP	10KΩ 1/16W J	559	UC	チップ抵抗	559
R338-339		R. CHP	3.9KΩ 1/16W J	559	UC	チップ抵抗	
R354-355		R. CHP	2.7KΩ 1/16W J	559	UC	チップ抵抗	
R356-357		R. MTL. CHP	3.3KΩ 1/16W D	559	UC	チップ金属被膜抵抗	
R365-366		R. MTL. CHP	1.5KΩ 1/16W D	559	UC	チップ金属被膜抵抗	
R389-390		R. CHP	100Ω 1/16W J	559	UC	チップ抵抗	
U201	WG559700	CN. PHOTO	1P GP1FAV50TK0F			光ファイバデータリンク	03
U202-204	WG559800	CN. PHOTO	1P GP1FAV50RK0F			光ファイバ受信器	
XL1	WA674700	RSNR. CE	16MHz CSTLS16MOX51			セラミック振動子	
XL51	WE436500	RSNR. CRY	45.1584MHz		UC	水晶振動子	
XL52	V3625700	RSNR. CRY	24.576MHz			水晶振動子	
	WG686000	P. C. B.	FUNCTION	559	J	P C B ファンクション	
	WG686100	P. C. B.	FUNCTION	559	UCTKA	P C B ファンクション	
	WG686200	P. C. B.	FUNCTION	559	R	P C B ファンクション	
	WG686400	P. C. B.	FUNCTION	559	GE	P C B ファンクション	
	WG686500	P. C. B.	FUNCTION	559	L	P C B ファンクション	
	WG689100	P. C. B.	FUNCTION	5950	UCTA	P C B ファンクション	
CB200	VQ047900	CN	29P			F F Cコネクター	03
CB201	VB389800	CN. BS. PIN	2P			ベースピン	01
CB202	VQ047500	CN. BS. PIN	20P			F F Cコネクター	01
CB203	VB390400	CN. BS. PIN	8P			ベースピン	01
CB204	VM859600	CN. BS. PIN	15P			F F Cコネクター	01
CB205	VB390100	CN. BS. PIN	5P			ベースピン	01
CB206	VB390400	CN. BS. PIN	8P			ベースピン	01
CB207	VB390200	CN. BS. PIN	6P			コネクタベースポスト	01
CB286-289	WE262500	CN	14P SE		J	D端子コネクタ	05
CB290	VN520900	CN. BS. PIN	52045 26P TE			F F Cコネクター	02
CB291	VQ045400	CN. BS. PIN	25P			F F Cコネクター	03

* New Parts * 新規部品

P.C.B. FUNCTION

Ref. No.	Part No.	Description	Remarks	Markets	部 品 名	Rank
* CB313	V9377800	CN. BS. PIN	3P	RL	ベース付ポスト	
* CB314	V9377900	CN. BS. PIN	4P	RL	ベース付ポスト	
CB315	WC050700	CLIP. FUSE	EYF-52BCY	R	ヒューズクリップ	01
CB317	WC050700	CLIP. FUSE	EYF-52BCY	R	ヒューズクリップ	01
C2000	US064100	C. CE. CHP	0.01uF 50V B		チップセラコン	01
C2002-2003	US064100	C. CE. CHP	0.01uF 50V B		チップセラコン	01
C2004	UR837100	C. EL	10uF 16V		ケミコン	01
C2005-2006	FG651470	C. CE	47pF 50V	559	セラコン	01
C2007	UA654100	C. MYLAR	0.01uF 50V J		マイラーコン	01
C2008-2013	US062220	C. CE. CHP	220pF 50V B		チップセラコン	01
C2014-2015	FG651470	C. CE	47pF 50V		セラコン	01
C2016-2019	US062220	C. CE. CHP	220pF 50V B		チップセラコン	01
C2020-2021	FG651470	C. CE	47pF 50V		セラコン	01
C2022-2027	US062220	C. CE. CHP	220pF 50V B		チップセラコン	01
C2028-2030	UR837100	C. EL	10uF 16V		ケミコン	01
C2031	UR837100	C. EL	10uF 16V		ケミコン	01
C2033-2034	UR837100	C. EL	10uF 16V	559	ケミコン	01
C2035	UR837100	C. EL	10uF 16V		ケミコン	01
C2036	UR237100	C. EL	10uF 50V		ケミコン	
C2037-2038	US135100	C. CE. CHP	0.1uF 16V	559	チップセラコン	01
C2039-2040	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C2043	UR237100	C. EL	10uF 50V		ケミコン	
C2044	UR237100	C. EL	10uF 16V		ケミコン	01
C2046-2047	UR237100	C. EL	10uF 16V		ケミコン	01
C2049	UR837100	C. EL	10uF 16V		ケミコン	01
C2050-2051	UR237100	C. EL	10uF 16V		ケミコン	01
C2052	UR837100	C. EL	10uF 16V		ケミコン	01
C2055	UR837100	C. EL	10uF 16V		ケミコン	01
C2057	UR837100	C. EL	10uF 16V		ケミコン	01
C2058-2059	VE326300	C. MYLAR	0.18uF 50V		マイラーコン	01
C2060	UA653470	C. MYLAR	4700pF 50V J		マイラーコン	01
C2061-2064	UR837100	C. EL	10uF 16V		ケミコン	01
C2066-2067	UR837100	C. EL	10uF 16V		ケミコン	01
C2068-2069	VE326200	C. MYLAR	0.15uF 50V		マイラーコン	
C2070	UA653470	C. MYLAR	4700pF 50V J		マイラーコン	01
C2071-2072	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C2073	US062150	C. CE. CHP	150pF 50V B		チップセラコン	01
C2074-2075	UR867470	C. EL	47uF 50V		ケミコン	01
C2076-2077	US062100	C. CE. CHP	100pF 50V B		チップセラコン	01
C2078	UR837100	C. EL	10uF 16V		ケミコン	01
C2079	US135100	C. CE. CHP	0.1uF 16V	GE	チップセラコン	01
C2080-2082	UR837100	C. EL	10uF 16V		ケミコン	01
C2083	US062330	C. CE. CHP	330pF 50V B	GE	チップセラコン	01
C2084	UR837470	C. EL	47uF 16V		ケミコン	01
C2085-2086	UR867470	C. EL	47uF 50V		ケミコン	01
C2087-2092	UR837100	C. EL	10uF 16V		ケミコン	01
C2093	US062330	C. CE. CHP	330pF 50V B	GE	チップセラコン	01
C2094	UR837100	C. EL	10uF 16V		ケミコン	01
C2095	UR837100	C. EL	10uF 16V		ケミコン	01
C2096	UR837470	C. EL	47uF 16V		ケミコン	01
C2097	UR837470	C. EL	47uF 16V	GE	ケミコン	01
C2100	UR837470	C. EL	47uF 16V	GE	ケミコン	01
C2101-2102	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C2106	US062560	C. CE. CHP	560pF 50V B	GE	チップセラコン	01
C2107-2108	UR837100	C. EL	10uF 16V		ケミコン	01
C2111-2112	US062100	C. CE. CHP	100pF 50V B		チップセラコン	01
C2114-2115	US061470	C. CE. CHP	47pF 50V B		チップセラコン	01
C2116-2117	UR837100	C. EL	10uF 16V		ケミコン	01
C2118	US061270	C. CE. CHP	27pF 50V B	GE	チップセラコン	01
C2120	US135100	C. CE. CHP	0.1uF 16V	GE	チップセラコン	01

* New Parts * 新規部品

RX-V559/DSP-AX559

HTR-5950

P.C.B. FUNCTION

Ref. No.	Part No.	Description	Remarks	Markets	部 品 名	Rank
C2122	US061270	C. CE. CHP	27pF 50V B	GE	チップセラコン	01
C2123-2124	US061220	C. CE. CHP	22pF 50V B		チップセラコン	01
C2127	UR837470	C. EL	47uF 16V	GE	ケミコン	01
C2128-2129	US062100	C. CE. CHP	100pF 50V B		チップセラコン	01
C2130-2131	UR839100	C. EL	1000uF 16V		ケミコン	01
C2132-2133	US062100	C. CE. CHP	100pF 50V B		チップセラコン	01
C2135	US063100	C. CE. CHP	1000pF 50V B		チップセラコン	01
C2136	US062100	C. CE. CHP	100pF 50V B		チップセラコン	01
C2137	US064100	C. CE. CHP	0.01uF 50V B		チップセラコン	01
C2138	US062100	C. CE. CHP	100pF 50V B		チップセラコン	01
C2140	US064100	C. CE. CHP	0.01uF 50V B		チップセラコン	01
C2141-2142	UR837100	C. EL	10uF 16V	UCTKA	ケミコン	01
C2851-2852	UR837100	C. EL	10uF 16V		ケミコン	01
C2853-2855	UR837470	C. EL	47uF 16V		ケミコン	01
C2856	UR837100	C. EL	10uF 16V		ケミコン	01
C2857	UR837470	C. EL	47uF 16V		ケミコン	01
C2858	UR837100	C. EL	10uF 16V		ケミコン	01
C2901-2903	US060800	C. CE. CHP	8pF 50V B		チップセラコン	01
C2904-2912	US060800	C. CE. CHP	8pF 50V B	J	チップセラコン	01
C2913-2915	US064100	C. CE. CHP	0.01uF 50V B	J	チップセラコン	01
C2916-2918	US060800	C. CE. CHP	8pF 50V B	J	チップセラコン	01
C2919-2921	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C2922	US135100	C. CE. CHP	0.1uF 16V	J	チップセラコン	01
C2923-2925	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C2926	US135100	C. CE. CHP	0.1uF 16V	J	チップセラコン	01
C2927	US064100	C. CE. CHP	0.01uF 50V B		チップセラコン	01
C2928-2929	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C2930	US061220	C. CE. CHP	22pF 50V B		チップセラコン	01
C2931	US062560	C. CE. CHP	560pF 50V B		チップセラコン	01
C2932-2935	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C2936-2938	US061220	C. CE. CHP	22pF 50V B		チップセラコン	01
D2000-2001	VU994300	DIODE. ZENR	MA8075-H 7.7V		ツェナーダイオード	
D2002	VU993000	DIODE. ZENR	MA8056-M 5.6V		ツェナーダイオード	01
D2003-2004	VV307700	DIODE	1N4002S		ダイオード	01
D2005-2006	VT332900	DIODE	1SS355		ダイオード	01
D2851-2859	VT332900	DIODE	1SS355	J	ダイオード	01
D2860-2867	VT332900	DIODE	1SS355		ダイオード	01
F3002	KB000790	FUSE	T4A 250V	R	ヒューズ	01
IC200	X5092A00	IC	BD3816K1		IC	
IC201	X3547A00	IC	BD3841FS	559	IC	06
IC202	X3547A00	IC	BD3841FS		IC	06
IC205	X7378A00	IC	NJM4565M(Te1)		アンプIC	
IC207	X7378A00	IC	NJM4565M(Te1)		アンプIC	
IC209	X0082A00	IC	LC72722PM		IC	
IC211	XP844A00	IC	NJM4556AL		IC	02
IC286-288	XS790A00	IC	TC74HC4052AF MPX		ロジックIC	
IC289	XS790A00	IC	TC74HC4052AF MPX	J	ロジックIC	
IC290	X2904A00	IC	NJM2581M VIDEO AMP		アンプIC	06
IC291	XZ509A00	IC	TC74VHC04FT INVER		ロジックIC	01
PJ200	V7046800	JACK. PIN	6P		ピンジャック	
PJ200-201	V7046800	JACK. PIN	6P		ピンジャック	
PJ201	V7046800	JACK. PIN	6P		ピンジャック	
PJ202	V7189700	JACK. PIN	1P		ピンジャック	01
PJ202	V7189700	JACK. PIN	1P		ピンジャック	01
PJ203	V7046700	JACK. PIN	4P		ピンジャック	03
PJ203	V7046700	JACK. PIN	4P		ピンジャック	03
PJ204	WG674800	JACK. PIN	6P	559	ピンジャック	
PJ204	WG674900	JACK. PIN	4P	5950	ピンジャック	
PJ286	WG471900	JACK. PIN	6P		ピンジャック	
PJ286-287	WG471900	JACK. PIN	6P		ピンジャック	

* New Parts * 新規部品

P.C.B. FUNCTION

Ref. No.	Part No.	Description	Remarks	Markets	部 品 名	Rank
* PJ287	WG471900	JACK. PIN	6P		ピンジャック	
PN200	V9637500	PIN	L=70 #18		スタイルピン	
PN200-201	V9637500	PIN	L=70 #18		スタイルピン	
PN201-202	V9637500	PIN	L=70 #18		スタイルピン	
PN202-203	V9637500	PIN	L=70 #18		スタイルピン	
PN203-204	V9637500	PIN	L=70 #18		スタイルピン	
PN204-205	V9637500	PIN	L=70 #18		スタイルピン	
PN205-206	V9637500	PIN	L=70 #18		スタイルピン	
PN206	V9637500	PIN	L=70 #18		スタイルピン	
PN286	V9637500	PIN	L=70 #18		スタイルピン	
PN286	V9637500	PIN	L=70 #18		スタイルピン	
Q2000-2001	VZ725900	TR	2SD1938F S, T	559	トランジスタ	01
Q2003-2004	VZ725900	TR	2SD1938F S, T	559	トランジスタ	01
Q2006	iC181510	TR	2SC1815 Y		トランジスタ	01
Q2007	iA101510	TR	2SA1015 Y		トランジスタ	01
Q2008	iC174020	TR	2SC1740S QRS	GE	トランジスタ	01
Q2009	VZ725900	TR	2SD1938F S, T		トランジスタ	01
Q2010	iC181510	TR	2SC1815 Y		トランジスタ	01
Q2011	VZ725900	TR	2SD1938F S, T		トランジスタ	01
Q2012-2019	VD303700	TR	2SC3326 A, B		トランジスタ	01
R2016-2017			100Ω 1/16W J	559	チップ抵抗	
R2046-2049			10KΩ 1/16W J	559	チップ抵抗	
R2056-2057			220Ω 1/16W J	559	チップ抵抗	
R2059-2060			1KΩ 1/16W J	559	チップ抵抗	
R2064-2065			100KΩ 1/16W J	559	チップ抵抗	
R2067-2068			100KΩ 1/16W J	559	チップ抵抗	
R2091-2092	HF356560	R. CAR	5.6KΩ 1/2W		カーボン抵抗	
R2098-2099	HF356150	R. CAR	1.5KΩ 1/2W		カーボン抵抗	
R2104		R. CHP	100KΩ 1/16W J	GE	チップ抵抗	
R2105		R. CHP	33KΩ 1/16W J	GE	チップ抵抗	
R2111	HV754470	R. CAR. FP	47Ω 1/4W		不燃化カーボン抵抗	01
R2114		R. CHP	3.3KΩ 1/16W J	GE	チップ抵抗	
R2115	HV754470	R. CAR. FP	47Ω 1/4W		不燃化カーボン抵抗	01
R2118		R. CHP	22KΩ 1/16W J	GE	チップ抵抗	
R2127		R. CHP	100Ω 1/16W J	GE	チップ抵抗	
R2135-2136	HF356100	R. CAR	1KΩ 1/2W		カーボン抵抗	
R2137	HV753220	R. CAR. FP	2.2Ω 1/4W		不燃化カーボン抵抗	01
R2138		R. CHP	470Ω 1/16W J	GE	チップ抵抗	
R2139	HF356100	R. CAR	1KΩ 1/2W		カーボン抵抗	
R2145		R. CHP	470Ω 1/16W J	GE	チップ抵抗	
R2147		R. CHP	10KΩ 1/16W J	GE	チップ抵抗	
R2151		R. CHP	10KΩ 1/16W J	GE	チップ抵抗	
R2152	HV755220	R. CAR. FP	220Ω 1/4W		不燃化カーボン抵抗	01
R2153	HV755150	R. CAR. FP	150Ω 1/4W		不燃化カーボン抵抗	01
R2156	HF353220	R. CAR	2.2Ω 1/2W		カーボン抵抗	
R2159	HF353220	R. CAR	2.2Ω 1/2W		カーボン抵抗	
R2173-2174	HV755100	R. CAR. FP	100Ω 1/4W		不燃化カーボン抵抗	01
R2863-2874		R. CHP	100Ω 1/16W J	J	チップ抵抗	
R2878-2880		R. CHP	75Ω 1/16W J	J	チップ抵抗	
R2884	HV753220	R. CAR. FP	2.2Ω 1/4W		不燃化カーボン抵抗	01
R2895-2897		R. CHP	10KΩ 1/16W J	J	チップ抵抗	
ST286	V4040500	SCR. TERM	M3		スクリュー/ターミナル	01
SW320	WB493700	VOLT. SELCT	R8140246	R	電圧切替器	
SW320	WD073700	VOLT. SELCT	R8140254	L	電圧切替器	
XL200	V3930900	RSNR. CRY	4.332MHz	GE	水晶振動子	05

* New Parts * 新規部品

RX-V559/DSP-AX559

RX-V559/DSP-AX559 P.C.B. OPERATION

	Ref. No.	Part No.	Description	Remarks	Markets	部 品 名	Rank		
*****		WG769900	P.C.B.	OPERATION	559	J	P C B オペレーション		
		WG770000	P.C.B.	OPERATION	559	UC	P C B オペレーション		
		WG770100	P.C.B.	OPERATION	559	R	P C B オペレーション		
		WG770200	P.C.B.	OPERATION	559	TK	P C B オペレーション		
		WG770300	P.C.B.	OPERATION	559	A	P C B オペレーション		
		WG770500	P.C.B.	OPERATION	559	GE	P C B オペレーション		
		WG770600	P.C.B.	OPERATION	559	L	P C B オペレーション		
!	CB302	VQ045300	CN.BS.PIN	23P	559	UCGE	F F C コネクター	01	
	CB303	VG879900	CN.BS.PIN	2P	559		ベースピン	01	
CB304-305	WC050700	CLIP.FUSE	EYF-52BCY	559	ヒューズクリップ		01		
CB306-307	WC050700	CLIP.FUSE	EYF-52BCY	559	ヒューズクリップ		01		
!	CB308	VG879900	CN.BS.PIN	2P	559		ベースピン	01	
CB311	VB858400	CN.BS.PIN	5P	559	ベースピン		01		
CB312	LB919020	CN.BS.PIN	2P	559	ベース付ポスト		01		
	CB331	LB918020	CN.BS.PIN	2P	559	ベース付ポスト	01		
	C3000-3001	US063100	C.CE.CHP	1000pF 50V B	559	JUC RTKAGEL	チップセラコン	01	
	C3002	US135100	C.CE.CHP	0.1uF 16V	559		チップセラコン	01	
	C3003-3006	US063100	C.CE.CHP	1000pF 50V B	559		チップセラコン	01	
	C3007	UM397100	C.EL	10uF 16V	559		ケミコン	01	
	C3008	UR866220	C.EL	2.2uF 50V	559		ケミコン	01	
	C3009	US135100	C.CE.CHP	0.1uF 16V	559		チップセラコン	01	
	C3010	US065100	C.CE.CHP	0.1uF 50V B	559		チップセラコン	01	
	C3011-3012	US063100	C.CE.CHP	1000pF 50V B	559		チップセラコン	01	
	C3013	UR866220	C.EL	2.2uF 50V	559		ケミコン	01	
	C3014	US064100	C.CE.CHP	0.01uF 50V B	559		チップセラコン	01	
	C3015	WB687100	C.POL.MTL	0.047uF 400V	559		メタライズドポリコン	01	
	C3015	WC041600	C.PP	0.022uF 630V	559		P P コン	01	
	C3016	UR866100	C.EL	1uF 50V	559		ケミコン	01	
	C3017	US135100	C.CE.CHP	0.1uF 16V	559		チップセラコン	01	
	C3018	UA653470	C.MYLAR	4700pF 50V J	559		マイラーコン	01	
	C3019	US135100	C.CE.CHP	0.1uF 16V	559		チップセラコン	01	
	C3020	UA653100	C.MYLAR	1000pF 50V J	559		マイラーコン	03	
	C3021	UM417100	C.EL	10uF 50V	559		ケミコン	01	
	C3022	UM388330	C.EL	330uF 6.3V	559		ケミコン	01	
	C3023	US135100	C.CE.CHP	0.1uF 16V	559		チップセラコン	01	
	C3024-3026	US062100	C.CE.CHP	100pF 50V B	559		チップセラコン	01	
	C3027	US135100	C.CE.CHP	0.1uF 16V	559		チップセラコン	01	
	C3029	WB696300	C.POL.MTL	0.1uF 400V	559		メタライズドポリコン	01	
	C3029	WD257600	C.PP	0.047uF 800V	559		P P コン	01	
	!	C3030	V6185300	C.CE.SAFETY	0.01uF 275V		559	規格認定コン	
	C3031	US135100	C.CE.CHP	0.1uF 16V	559		チップセラコン	01	
	C3033	UR239330	C.EL	3300uF 16V	559		JUCTKAGEL	ケミコン	02
	C3033	UR269330	C.EL	3300uF 50V	559		R	ケミコン	
	C3034	WE102900	C.PP	0.01uF 100V	559		P P コン		
	C3035-3036	US135100	C.CE.CHP	0.1uF 16V	559	チップセラコン	01		
	C3037	US064100	C.CE.CHP	0.01uF 50V B	559	チップセラコン	01		
	C3038-3039	UA653100	C.MYLAR	1000pF 50V J	559	マイラーコン	03		
	C3040	UA654100	C.MYLAR	0.01uF 50V J	559	マイラーコン	01		
	C3041	UA653100	C.MYLAR	1000pF 50V J	559	マイラーコン	03		
	C3042	US135100	C.CE.CHP	0.1uF 16V	559	チップセラコン	01		
	C3043-3044	US062220	C.CE.CHP	220pF 50V B	559	チップセラコン	01		
	C3045-3046	US135100	C.CE.CHP	0.1uF 16V	559	チップセラコン	01		
	C3047	US064100	C.CE.CHP	0.01uF 50V B	559	チップセラコン	01		
	D3000	VT332900	DIODE	1SS355	559		ダイオード	01	
	D3001	V2598200	LED	SIR-505ST	559		L E D		
	D3003-3004	VT332900	DIODE	1SS355	559		ダイオード	01	
	D3005	VU990500	DIODE.ZENR	MA8030-L 2.9V	559		ツェナーダイオード	01	
	D3006	VU993800	DIODE.ZENR	MA8068-M 6.8V	559		ツェナーダイオード	01	
	D3007	VU995400	DIODE.ZENR	MA8100-M 10V	559		ツェナーダイオード		
	D3008-3012	VT332900	DIODE	1SS355	559		ダイオード	01	

* New Parts * 新規部品

RX-V559/DSP-AX559

HTR-5950

RX-V559/DSP-AX559 P.C.B. OPERATION & HTR-5950 P.C.B. OPERATION

Ref. No.	Part No.	Description	Remarks	Markets	部 品 名	Rank
D3015	VU995000	DIODE. ZENR	MA8091-M 9.1V	559	JUCTKAGEL	ツェナーダイオード
D3015	VU994700	DIODE. ZENR	MA8082-H 8.5V	559	R	ツェナーダイオード
D3016	V4756800	DIODE	S1NB60 1.0A 600V	559		D i スタック
D3017	VT332900	DIODE	1SS355	559		ダイオード
D3018	VR253700	DIODE. BRG	S1NB20 1A 200V	559		D I ブリッジ X 4
D3019-3020	VU171500	DIODE. ZENR	UDZ 3.6BTE-17 3.6V	559		ツェナーダイオード
D3021	VU995000	DIODE. ZENR	MA8091-M 9.1V	559		ツェナーダイオード
D3022-3028	VT332900	DIODE	1SS355	559		ダイオード
F3000	WG410700	FUSE	8A 125V	559	UC	ヒューズ
F3000	VT942900	FUSE	T2. 5A 250V	559	GE	ヒューズ
F3001	WG410700	FUSE	8A 125V	559	JUCR	ヒューズ
F3001	KB000790	FUSE	T4A 250V	559	TKAGEL	ヒューズ
IC300	V8100500	PHOT. CPL	TLP421 GR	559		フォトカブラ
IC301	X6386A00	IC	M66003-0131FP	559		I C
IC302	iG001180	IC	TC4013BP FF	559		ロジック I C
IC303	V8100500	PHOT. CPL	TLP421 GR	559		フォトカブラ
JK300	V9408200	JACK. PHONE	MSJ-064-05B GR	559		ホーンジャック
JK302	WG514200	JACK. MNI	JY-3535+01-090G	559		ミニジャック
PJ300	V7190100	JACK. PIN	3P	559		ピンジャック
PN331	V9637500	PIN	L=70 #18	559		スタイルピン
Q3000-3001	VV556400	TR	2SC2412K Q, R, S	559		トランジスタ
Q3002	VV655700	TR. DGT	DTC144EKA	559		デジタルトランジスタ
Q3003	iC181510	TR	2SC1815 Y	559		トランジスタ
Q3004	VV556400	TR	2SC2412K Q, R, S	559		トランジスタ
Q3006	iC181510	TR	2SC1815 Y	559		トランジスタ
Q3007	WC741200	FET	2SK3850	559		F E T
Q3008-3009	VV556400	TR	2SC2412K Q, R, S	559		トランジスタ
R3031	V6730000	R. CAR.	2. 2MΩ 1/2W	559	UC	放電抵抗
R3034	HF356220	R. CAR	2. 2KΩ 1/2W	559		カーボン抵抗
RY301	V6434900	RELAY	DC DLS12D1-0(M)	559		リレー 1 2 V T V - 8
ST300	V4040500	SCR. TERM	M3	559		スクリュー/ターミナル
ST301	WA246200	SCR. TERM	3. 5	559		スクリューターミナル
ST302	V4040500	SCR. TERM	M3	559		スクリュー/ターミナル
SW300	V9597100	SW. RT. ENC	EC12E2460802	559		ロータリーエンコーダ
SW301-302	WG266400	SW. RT. ENC	XREB12105PVB25F	559		ロータリーエンコーダ
SW303-316	WD483100	SW. TACT	SKRGAAD010	559		タクト SW
SW318-319	WD483100	SW. TACT	SKRGAAD010	559		タクト SW
SW321	WF875900	SW. PUSH	SPUN127100	559		プッシュ SW
T3000	XW605A00	TRANS. PWR		559	J	電源トランス
T3000	XW606A00	TRANS. PWR		559	UC	電源トランス
T3000	X6351A00	TRANS. PWR		559	R	電源トランス
T3000	XW608A00	TRANS. PWR		559	TKAGEL	電源トランス
TE300	VU543100	OUTLET. AC	2P	559	JUC	A C アウトレット
TE300	V5867400	OUTLET. AC	2P AC-182-GB-11V	559	RTK	A C アウトレット
TE300	VT915000	OUTLET. AC	1P	559	A	A C アウトレット
TE300	VU543400	OUTLET. AC	2P	559	GEL	A C アウトレット
U3000	V8210200	L. DTCT	GP1UD271XK	559		リモコン受光ユニット
V3000	WG474000	FL. DSPLY	HNA-17MM03T	559		蛍光表示管
	V6880300	SHEET		559		シート/ F L
	V6007100	SPACER. FL	4. 6/10/32	559		スペーサ F L
	WG771400	P. C. B.	OPERATION	5950	UC	P C B オペレーション
	WG956400	P. C. B.	OPERATION	5950	T	P C B オペレーション
	WG771500	P. C. B.	OPERATION	5950	A	P C B オペレーション
CB303	VG879900	CN. BS. PIN	2P	5950		ベースピン
CB304-305	WC050700	CLIP. FUSE	EYF-52BCY	5950	UC	ヒューズクリップ
CB306-307	WC050700	CLIP. FUSE	EYF-52BCY	5950		ヒューズクリップ
CB308	VG879900	CN. BS. PIN	2P	5950		ベースピン

* New Parts * 新規部品

HTR-5950

HTR-5950 P.C.B. OPERATION

Ref. No.	Part No.	Description	Remarks	Markets	部 品 名	Rank
CB309	VM689000	CN. BS. PIN	23P	5950	FFCコネクター	02
CB310	LB919020	CN. BS. PIN	2P	5950	ベース付ポスト	01
CB331	LB918020	CN. BS. PIN	2P	5950	ベース付ポスト	01
C3000	US135100	C. CE. CHP	0.1uF 16V	5950	チップセラコン	01
C3001-3004	US063100	C. CE. CHP	1000pF 50V B	5950	チップセラコン	01
C3005	UM397100	C. EL	10uF 16V	5950	ケミコン	01
C3006	US135100	C. CE. CHP	0.1uF 16V	5950	チップセラコン	01
C3007	US065100	C. CE. CHP	0.1uF 50V B	5950	チップセラコン	
C3008	UR866220	C. EL	2.2uF 50V	5950	ケミコン	01
C3009-3010	US135100	C. CE. CHP	0.1uF 16V	5950	チップセラコン	01
C3011	UM388330	C. EL	330uF 6.3V	5950	ケミコン	01
C3012	US135100	C. CE. CHP	0.1uF 16V	5950	チップセラコン	01
C3013	UR866220	C. EL	2.2uF 50V	5950	ケミコン	01
C3014	US064100	C. CE. CHP	0.01uF 50V B	5950	チップセラコン	01
C3015	WB687100	C. POL. MTL	0.047uF 400V	5950	メタライズドポリコン	01
C3015	WC041600	C. PP	0.022uF 630V	5950	PPコン	01
C3016	UR866100	C. EL	1uF 50V	5950	ケミコン	01
C3017	US062100	C. CE. CHP	100pF 50V B	5950	チップセラコン	01
C3018	UA653470	C. MYLAR	4700pF 50V J	5950	マイラーコン	01
C3019	US135100	C. CE. CHP	0.1uF 16V	5950	チップセラコン	01
C3020	UA653100	C. MYLAR	1000pF 50V J	5950	マイラーコン	03
C3021-3022	US062100	C. CE. CHP	100pF 50V B	5950	チップセラコン	01
C3024-3026	US135100	C. CE. CHP	0.1uF 16V	5950	チップセラコン	01
C3027	US064100	C. CE. CHP	0.01uF 50V B	5950	チップセラコン	01
C3028	UA653100	C. MYLAR	1000pF 50V J	5950	マイラーコン	03
C3029	WB696300	C. POL. MTL	0.1uF 400V	5950	メタライズドポリコン	
C3029	WD257600	C. PP	0.047uF 800V	5950	PPコン	
C3030	V6185300	C. CE. SAFTY	0.01uF 275V	5950	規格認定コン	
C3031-3032	UA653100	C. MYLAR	1000pF 50V J	5950	マイラーコン	03
C3033	UR239330	C. EL	3300uF 16V	5950	ケミコン	02
C3034	WE102900	C. PP	0.01uF 100V	5950	PPコン	
C3035	UA654100	C. MYLAR	0.01uF 50V J	5950	マイラーコン	01
C3036-3037	US135100	C. CE. CHP	0.1uF 16V	5950	チップセラコン	01
C3043-3044	US063680	C. CE. CHP	6800pF 50V B	5950	チップセラコン	01
C3046	US135100	C. CE. CHP	0.1uF 16V	5950	チップセラコン	01
C3047	US064100	C. CE. CHP	0.01uF 50V B	5950	チップセラコン	01
D3000-3001	VT332900	DIODE	1SS355	5950	ダイオード	01
D3002	VU171500	DIODE. ZENR	UDZ 3.6BTE-17 3.6V	5950	ツェナーダイオード	01
D3003-3004	VT332900	DIODE	1SS355	5950	ダイオード	01
D3005	VU990500	DIODE. ZENR	MA8030-L 2.9V	5950	ツェナーダイオード	01
D3006	VU993800	DIODE. ZENR	MA8068-M 6.8V	5950	ツェナーダイオード	01
D3007	VU995400	DIODE. ZENR	MA8100-M 10V	5950	ツェナーダイオード	
D3008	VT332900	DIODE	1SS355	5950	ダイオード	01
D3009	VU171500	DIODE. ZENR	UDZ 3.6BTE-17 3.6V	5950	ツェナーダイオード	01
D3010	VU995000	DIODE. ZENR	MA8091-M 9.1V	5950	ツェナーダイオード	
D3011-3012	VT332900	DIODE	1SS355	5950	ダイオード	01
D3015	VU995000	DIODE. ZENR	MA8091-M 9.1V	5950	ツェナーダイオード	
D3016	V4756800	DIODE	S1NB60 1.0A 600V	5950	D i スタック	01
D3017	VT332900	DIODE	1SS355	5950	ダイオード	01
D3018	VR253700	DIODE. BRG	S1NB20 1A 200V	5950	D i ブリッジ X 4	02
D3019-3020	VT332900	DIODE	1SS355	5950	ダイオード	01
D3026-3027	VT332900	DIODE	1SS355	5950	ダイオード	01
F3000	WG410700	FUSE	8A 125V	5950	ヒューズ	01
F3001	WG410700	FUSE	8A 125V	5950	ヒューズ	01
F3001	KB000790	FUSE	T4A 250V	5950	ヒューズ	01
IC300	V8100500	PHOT. CPL	TLP421 GR	5950	フォトカプラ	01
IC301	X6386A00	IC	M66003-0131FP	5950	I C	07
IC302	iG001180	IC	TC4013BP FF	5950	ロジック I C	05
IC303	V8100500	PHOT. CPL	TLP421 GR	5950	フォトカプラ	01
JK300	V9408200	JACK. PHONE	MSJ-064-05B GR	5950	ホーンジャック	03

* New Parts * 新規部品

HTR-5950 P.C.B. OPERATION & P.C.B. MAIN

Ref. No.	Part No.	Description	Remarks	Markets	部 品 名	Rank
* JK302	WG514200	JACK. MNI	JY-3535+01-090G	5950	ミニジャック	
PJ300	V7190100	JACK. PIN	3P	5950	ピンジャック	
PN331	V9637500	PIN	L=70 #18	5950	スタイルピン	
Q3000-3001	VV556400	TR	2SC2412K Q, R, S	5950	トランジスタ	01
Q3002	VV655700	TR. DGT	DTC144EKA	5950	デジタルトランジスタ	01
Q3003	iC181510	TR	2SC1815 Y	5950	トランジスタ	01
Q3004-3005	VV556400	TR	2SC2412K Q, R, S	5950	トランジスタ	01
Q3006	iC181510	TR	2SC1815 Y	5950	トランジスタ	01
Q3007	WC741200	FET	2SK3850	5950	F E T	
Q3008	VV556400	TR	2SC2412K Q, R, S	5950	トランジスタ	01
R3031	V6730000	R. CAR.	2.2MΩ 1/2W	5950	放電抵抗	01
RY301	V6434900	RELAY	DC DLS12D1-0(M)	5950	リレー 12V TV-8	03
ST300	V4040500	SCR. TERM	M3	5950	スクリュー/ターミナル	01
ST316	WA246200	SCR. TERM	3.5	5950	スクリューターミナル	
ST318	WA246200	SCR. TERM	3.5	5950	スクリューターミナル	
SW300	V9597100	SW. RT. ENC	EC12E2460802	5950	ロータリーエンコーダ	04
SW301	V9266400	SW. RT. ENC	XREB12105PVB25F	5950	ロータリーエンコーダ	02
SW302	WD483100	SW. TACT	SKRGAAD010	5950	タクト SW	01
SW304	WD483100	SW. TACT	SKRGAAD010	5950	タクト SW	01
SW306	WD483100	SW. TACT	SKRGAAD010	5950	タクト SW	01
SW309-319	WD483100	SW. TACT	SKRGAAD010	5950	タクト SW	01
SW321-324	WD483100	SW. TACT	SKRGAAD010	5950	タクト SW	01
* T3000	XW606A00	TRANS. PWR		5950	電源トランス	
* T3000	XW608A00	TRANS. PWR		5950	電源トランス	
TE300	VU543100	OUTLET. AC	2P	5950	ACアウトレット	03
TE300	V5867400	OUTLET. AC	2P	5950	ACアウトレット	
TE300	VT915000	OUTLET. AC	1P	5950	ACアウトレット	06
U3000	V8210200	L. DTCT	GP1UD271XK	5950	リモコン受光ユニット	03
* V3000	WG473900	FL. DSPLY	17-BT-XXGNK	5950	蛍光表示管	
	V6880300	SHEET		5950	シート/FL	
	V6007100	SPACER. FL	4.6/10/32	5950	スペーサ FL	
* * * * *	WG700000	P. C. B.	MAIN	559	JRTA PCB メイン	
	WG700100	P. C. B.	MAIN	559	UC PCB メイン	
	WG700200	P. C. B.	MAIN	559	KGEL PCB メイン	
	WG701000	P. C. B.	MAIN	5950	UC PCB メイン	
	WG701100	P. C. B.	MAIN	5950	TA PCB メイン	
CB103	LB932060	CN. BS. PIN	6P		ベースポスト	01
CB104	LB918100	CN. BS. PIN	10P		ベース付ポスト	02
CB105	LB918030	CN. BS. PIN	3P		ベース付ポスト	01
CB113	V7827500	SOCKET	8P SE TUC SERIES		コネクタースocket	
CB114	V7825800	CN	8P TE TUC SERIES		コネクタープラグ	
CB115	V7825700	CN	7P TE TUC SERIES		コネクタープラグ	
CB116	V7827400	SOCKET	7P TE TUC SERIES		コネクタースocket	
C1000	UR238100	C. EL	100uF 16V		ケミコン	
C1001-1002	UR066470	C. EL	4.7uF 50V		ケミコン	
C1003-1004	UR066470	C. EL	4.7uF 50V		ケミコン	01
C1005	UR066470	C. EL	4.7uF 50V		ケミコン	
C1006	UR066470	C. EL	4.7uF 50V		ケミコン	01
C1007	UR237100	C. EL	10uF 16V		ケミコン	
C1008	UR248100	C. EL	100uF 25V		ケミコン	
C1009	UT652100	C. PP	100pF 100V		PPコン	01
C1010	UA652220	C. MYLAR	220pF 50V J		マイラーコン	01
C1011	UT652100	C. PP	100pF 100V		PPコン	01
C1012	UA652220	C. MYLAR	220pF 50V J		マイラーコン	01
C1013	UA652100	C. MYLAR	100pF 50V J		マイラーコン	01
C1014	UA652220	C. MYLAR	220pF 50V J		マイラーコン	01
C1015	UA652100	C. MYLAR	100pF 50V J		マイラーコン	01

* New Parts * 新規部品

RX-V559/DSP-AX559

HTR-5950

P.C.B. MAIN

Ref. No.	Part No.	Description	Remarks	Markets	部 品 名	Rank
C1016	UA652220	C. MYLAR	220pF 50V J		マイラーコン	01
C1017	UT652100	C. PP	100pF 100V		P P コン	01
C1018	UA652220	C. MYLAR	220pF 50V J		マイラーコン	01
C1019	UA652100	C. MYLAR	100pF 50V J		マイラーコン	01
C1020	UA652220	C. MYLAR	220pF 50V J		マイラーコン	01
C1021	UA653330	C. MYLAR	3300pF 50V J		マイラーコン	01
C1022-1023	UT653330	C. PP	3300pF 100V		P P コン	03
C1024-1025	UA653330	C. MYLAR	3300pF 50V J		マイラーコン	01
C1026	UT653330	C. PP	3300pF 100V		P P コン	03
C1027	UR268100	C. EL	100uF 50V		ケミコン	
C1028	UR837470	C. EL	47uF 16V		ケミコン	01
C1029	UT654100	C. PP	0.01uF 100V		P P コン	01
C1030-1031	UR268100	C. EL	100uF 50V		ケミコン	
C1032-1033	UR837470	C. EL	47uF 16V		ケミコン	01
C1034-1039	WG211700	C. CE	22pF 500V		セラコン	
C1040-1041	UR297100	C. EL	10uF 100V		ケミコン	
C1042	UT652150	C. PP	150pF 100V		P P コン	01
C1043	UR297100	C. EL	10uF 100V		ケミコン	
C1044-1045	UT652150	C. PP	150pF 100V		P P コン	01
C1046	UR297100	C. EL	10uF 100V		ケミコン	
C1047-1048	UT652150	C. PP	150pF 100V		P P コン	01
C1049	UR297100	C. EL	10uF 100V		ケミコン	
C1050-1051	UT652150	C. PP	150pF 100V		P P コン	01
C1052	UR297100	C. EL	10uF 100V		ケミコン	
C1053-1054	UT652150	C. PP	150pF 100V		P P コン	01
C1055	UR297100	C. EL	10uF 100V		ケミコン	
C1056-1057	UT652150	C. PP	150pF 100V		P P コン	01
C1058	UR297100	C. EL	10uF 100V		ケミコン	
C1059	UT652150	C. PP	150pF 100V		P P コン	01
C1060	UR297100	C. EL	10uF 100V		ケミコン	
C1061-1065	VR324700	C. MYLAR	0.022uF 100V		マイラーコン	
C1066	UT654220	C. PP	0.022uF 100V		P P コン	01
C1067	UR818100	C. EL	100uF 6.3V		ケミコン	01
C1068-1069	WE100900	C. PP	220pF 630V		P P コン	
C1070	UR866470	C. EL	4.7uF 50V		ケミコン	01
C1071	WG601900	C. EL	10000uF 16V		ケミコン	
C1072	UR867470	C. EL	47uF 50V		ケミコン	01
C1073	VF467000	C. CE. TUBLR	1000pF 50V	559	円筒セラコン	01
C1074	UR858100	C. EL	100uF 35V		ケミコン	01
C1075	UR249470	C. EL	4700uF 25V		ケミコン	
C1076	UR249220	C. EL	2200uF 25V		ケミコン	
C1077	WG602000	C. EL	15000uF 16V		ケミコン	
C1078	WG601700	C. EL	4700uF 16V		ケミコン	
C1079	VF467000	C. CE. TUBLR	1000pF 50V	559	円筒セラコン	01
C1080	VF467300	C. CE. TUBLR	0.01uF 16V	559	円筒セラコン	01
C1081	UR866470	C. EL	4.7uF 50V		ケミコン	01
C1082-1083	VR325200	C. MYLAR	0.022uF 100V		マイラーコン	01
C1084-1085	WG416300	C. EL	10000uF 71V		ケミコン	
C1086	VF467300	C. CE. TUBLR	0.01uF 16V	559	円筒セラコン	01
C1087-1088	VR325400	C. MYLAR	0.1uF 100V		マイラーコン	01
C1089	VF467300	C. CE. TUBLR	0.01uF 16V	559	円筒セラコン	01
C1090	UR268330	C. EL	330uF 50V		ケミコン	
C1091	UR268100	C. EL	100uF 50V		ケミコン	
C1092-1093	UA654220	C. MYLAR	0.022uF 50V J		マイラーコン	01
C1094-1095	VR325400	C. MYLAR	0.1uF 100V		マイラーコン	01
C1096	WG602000	C. EL	15000uF 16V		ケミコン	
C1097	UA654100	C. MYLAR	0.01uF 50V J		マイラーコン	01
C1098	WG602000	C. EL	15000uF 16V		ケミコン	
C1099	UA654100	C. MYLAR	0.01uF 50V J		マイラーコン	01
C1100-1101	VR325400	C. MYLAR	0.1uF 100V		マイラーコン	01

* New Parts * 新規部品

P.C.B. MAIN

Ref. No.	Part No.	Description	Remarks	Markets	部 品 名	Rank
C1102	UA654100	C. MYLAR	0.01uF 50V J		マイラーコン	01
C1103	UA354100	C. MYLAR	0.01uF 50V		マイラーコン	01
C1104-1107	WA747600	C. MYLAR	1000pF 100V		マイラーコン	01
C1108	UA654220	C. MYLAR	0.022uF 50V J		マイラーコン	01
C1109	VE326000	C. MYLAR	0.1uF 50V	UC	マイラーコン	01
C1110	UA354100	C. MYLAR	0.01uF 50V		マイラーコン	01
C1111	UA654220	C. MYLAR	0.022uF 50V J		マイラーコン	01
C1112	VR325400	C. MYLAR	0.1uF 100V		マイラーコン	01
C1113	UA354100	C. MYLAR	0.01uF 50V		マイラーコン	01
C1114	UA654220	C. MYLAR	0.022uF 50V J		マイラーコン	01
C1115-1118	UA653470	C. MYLAR	4700pF 50V J		マイラーコン	01
C1119	UA654220	C. MYLAR	0.022uF 50V J		マイラーコン	01
C1120	VJ599100	C. CE. TUBLR	0.1uF 50V	UC	円筒セラコン	01
C1121	UR237470	C. EL	47uF 16V	UC	ケミコン	
C1122-1123	UR266100	C. EL	1uF 50V		ケミコン	
C1124	VJ599100	C. CE. TUBLR	0.1uF 50V		円筒セラコン	01
C1126-1127	UR266100	C. EL	1uF 50V		ケミコン	
C1129-1130	UR266100	C. EL	1uF 50V		ケミコン	
C1131	UR238100	C. EL	100uF 16V		ケミコン	
C1132	UR266100	C. EL	1uF 50V		ケミコン	
C1135-1137	UR266100	C. EL	1uF 50V		ケミコン	
C1138	UR238100	C. EL	100uF 16V		ケミコン	
C1140	UR266100	C. EL	1uF 50V		ケミコン	
C1141	UR238100	C. EL	100uF 16V		ケミコン	
C1150	UR237100	C. EL	10uF 16V	UC	ケミコン	
D1000	VG440700	DIODE. ZENR	MTZJ15A 15V		ツェナーダイオード	
D1001-1016	VD631600	DIODE	1SS133, 176		ダイオード	01
D1017-1018	VG435500	DIODE. ZENR	MTZJ2.4B 2.4V		ツェナーダイオード	01
D1019-1030	VN008700	DIODE	1SS270A		ダイオード	01
D1031	VD631600	DIODE	1SS133, 176	559	ダイオード	01
D1032	VG443200	DIODE. ZENR	MTZJ30A 30V		ツェナーダイオード	01
D1033-1034	VD631600	DIODE	1SS133, 176	559	ダイオード	01
D1035	WA653100	DIODE. BRG	KBP103G 1.0A 200V		ダイオードブリッジ	02
D1036	WF300200	DIODE. BRG	TS4B03G C2		ダイオードブリッジ	
D1037-1039	VG442900	DIODE. ZENR	MTZJ27B 27V		ツェナーダイオード	01
D1040	WA653200	DIODE. BRG	TS6P03G 6.0A 200V		ダイオードブリッジ	04
D1041-1042	VS997800	DIODE	1T2		ダイオード	01
D1043	VG442900	DIODE. ZENR	MTZJ27B 27V		ツェナーダイオード	01
D1044-1045	VS997800	DIODE	1T2		ダイオード	01
D1046	WA653100	DIODE. BRG	KBP103G 1.0A 200V		ダイオードブリッジ	02
D1047	VG442900	DIODE. ZENR	MTZJ27B 27V		ツェナーダイオード	01
D1048	V4269600	DIODE. BRG	D2SBA20 1.5A 200V		ダイオードブリッジ	
D1049	VG442900	DIODE. ZENR	MTZJ27B 27V		ツェナーダイオード	01
D1050	VG440800	DIODE. ZENR	MTZJ15B 15V		ツェナーダイオード	01
D1051	VU647200	DIODE. SHOT	RB441Q-40 T-77		ショットキーダイオード	01
D1052	VU647200	DIODE. SHOT	RB441Q-40 T-77		ショットキーダイオード	01
D1053-1058	VG437500	DIODE. ZENR	MTZJ5.1C 5.1V		ツェナーダイオード	01
D1060	VG437500	DIODE. ZENR	MTZJ5.1C 5.1V		ツェナーダイオード	01
D1061	VG435500	DIODE. ZENR	MTZJ2.4B 2.4V		ツェナーダイオード	01
G1000	V5995800	PLATE. GND			アースプレート	
IC100	X6143A00	IC	NJM2388F05 5.0V		電源 I C	
IC101	X0515A00	IC	LM61C1Z THERMAL		電源 I C	03
IC102	X6143A00	IC	NJM2388F05 5.0V		電源 I C	
IC103	XE436A00	IC	NJM79M05FA		I C	03
IC104	XJ608A00	IC	NJM7812FA		I C	02
IC105	XD343A00	IC	NJM79M12FA		I C	03
IC106	X6143A00	IC	NJM2388F05 5.0V		電源 I C	
IC107	X6248A00	IC	NJM2388F33		電源 I C	04
IC110	XJ607A00	IC	NJM7805FA 5V		I C	02
JK100-102	V9435700	JACK. MNI	MSJ-035-12APC	559	モノラル ミニジャック	01

* New Parts * 新規部品

RX-V559/DSP-AX559

HTR-5950

P.C.B. MAIN

Ref. No.	Part No.	Description	Remarks	Markets	部 品 名	Rank
PN101-107	V9637500	PIN	L=70 #18		スタイルピン	
Q1000	VP872600	TR	2SA1708 S,T		トランジスタ	01
Q1001-1012	VP883100	TR	2SC1890A D,E		トランジスタ	01
Q1013-1018	V3966800	TR	2SA949 O,Y		トランジスタ	02
Q1019-1024	VK432900	TR	2SD1915F S,T		トランジスタ	01
Q1025-1030	VR325600	TR	2SC2229 O,Y		トランジスタ	01
Q1031	WC398400	TR	2N5551C-AT		トランジスタ	
Q1032	WC397700	TR	2N5401C-AT		トランジスタ	
Q1033	V4096100	TR	2SC4614 S,T		トランジスタ	02
Q1034	V4096000	TR	2SA1770 S,T		トランジスタ	03
Q1035	V4096100	TR	2SC4614 S,T		トランジスタ	02
Q1036	V4096000	TR	2SA1770 S,T		トランジスタ	03
Q1037	V4096100	TR	2SC4614 S,T		トランジスタ	02
Q1038	V4096000	TR	2SA1770 S,T		トランジスタ	03
Q1039	V4096100	TR	2SC4614 S,T		トランジスタ	02
Q1040	V4096000	TR	2SA1770 S,T		トランジスタ	03
Q1041	V4096100	TR	2SC4614 S,T		トランジスタ	02
Q1042	V4096000	TR	2SA1770 S,T		トランジスタ	03
Q1043	V4096100	TR	2SC4614 S,T		トランジスタ	02
Q1044	V4096000	TR	2SA1770 S,T		トランジスタ	03
Q1045-1046	VC614000	TR	2SB1274 Q,R,S		トランジスタ	02
Q1047	WC398400	TR	2N5551C-AT		トランジスタ	
Q1048A	iX630850	TR	2SA1695 O,P,Y		トランジスタ	04
Q1048C	iX630860	TR	2SC4468 O,P,Y		トランジスタ	04
Q1049A	iX630850	TR	2SA1695 O,P,Y		トランジスタ	04
Q1049C	iX630860	TR	2SC4468 O,P,Y		トランジスタ	04
Q1050A	iX630850	TR	2SA1695 O,P,Y		トランジスタ	04
Q1050C	iX630860	TR	2SC4468 O,P,Y		トランジスタ	04
Q1051A	iX630850	TR	2SA1695 O,P,Y		トランジスタ	04
Q1051C	iX630860	TR	2SC4468 O,P,Y		トランジスタ	04
Q1052A	iX630850	TR	2SA1695 O,P,Y		トランジスタ	04
Q1052C	iX630860	TR	2SC4468 O,P,Y		トランジスタ	04
Q1053A	iX630850	TR	2SA1695 O,P,Y		トランジスタ	04
Q1053C	iX630860	TR	2SC4468 O,P,Y		トランジスタ	04
Q1060-1065	WC398400	TR	2N5551C-AT		トランジスタ	
Q1066	WC397700	TR	2N5401C-AT		トランジスタ	
Q1067	iC181510	TR	2SC1815 Y		トランジスタ	01
Q1068	iA101510	TR	2SA1015 Y		トランジスタ	01
Q1069	VP872600	TR	2SA1708 S,T	559	トランジスタ	01
Q1070	VG722000	TR. DGT	DTC144ES	559	デジタルトランジスタ	01
Q1071-1076	VP872700	TR	2SC4488 S,T		トランジスタ	01
R1006-1007	HF356100	R. CAR	1K Ω 1/2W		カーボン抵抗	
R1011	HF356100	R. CAR	1K Ω 1/2W		カーボン抵抗	
R1019	HV756100	R. CAR. FP	1K Ω 1/4W		不燃化カーボン抵抗	01
R1040-1041	HF355330	R. CAR	330 Ω 1/2W		カーボン抵抗	
R1044	HF355330	R. CAR	330 Ω 1/2W		カーボン抵抗	
R1045	HF356120	R. CAR	1.2K Ω 1/2W		カーボン抵抗	
R1047-1048	HF356120	R. CAR	1.2K Ω 1/2W		カーボン抵抗	
R1052-1054	HF357330	R. CAR	33K Ω 1/2W		カーボン抵抗	
R1057-1062	HV755100	R. CAR. FP	100 Ω 1/4W		不燃化カーボン抵抗	01
R1064	HF353220	R. CAR	2.2 Ω 1/2W		カーボン抵抗	
R1065-1067	HF355470	R. CAR	470 Ω 1/2W		カーボン抵抗	
R1084	HL006270	R. MTL. OXD	2.7K Ω 1/2W		酸化金属被膜抵抗	
R1085	HL005470	R. MTL. OXD	470 Ω 1/2W		酸化金属被膜抵抗	
R1086	HL005820	R. MTL. OXD	820 Ω 1/2W		酸化金属被膜抵抗	
R1087	HL006270	R. MTL. OXD	2.7K Ω 1/2W		酸化金属被膜抵抗	
R1088	HL005470	R. MTL. OXD	470 Ω 1/2W		酸化金属被膜抵抗	
R1089	HL005820	R. MTL. OXD	820 Ω 1/2W		酸化金属被膜抵抗	
R1090	HL006270	R. MTL. OXD	2.7K Ω 1/2W		酸化金属被膜抵抗	
R1091	HL005470	R. MTL. OXD	470 Ω 1/2W		酸化金属被膜抵抗	

* New Parts * 新規部品

P.C.B. MAIN

Ref. No.	Part No.	Description	Remarks	Markets	部 品 名	Rank
R1092	HL005820	R. MTL. OXD	820 Ω 1/2W		酸化金属被膜抵抗	
R1093	HL006270	R. MTL. OXD	2.7K Ω 1/2W		酸化金属被膜抵抗	
R1094	HL005470	R. MTL. OXD	470 Ω 1/2W		酸化金属被膜抵抗	
R1095	HL005820	R. MTL. OXD	820 Ω 1/2W		酸化金属被膜抵抗	
R1096	HL006270	R. MTL. OXD	2.7K Ω 1/2W		酸化金属被膜抵抗	
R1097	HL005470	R. MTL. OXD	470 Ω 1/2W		酸化金属被膜抵抗	
R1098	HL005820	R. MTL. OXD	820 Ω 1/2W		酸化金属被膜抵抗	
R1099	HL006270	R. MTL. OXD	2.7K Ω 1/2W		酸化金属被膜抵抗	
R1100	HL005470	R. MTL. OXD	470 Ω 1/2W		酸化金属被膜抵抗	
R1101	HL005820	R. MTL. OXD	820 Ω 1/2W		酸化金属被膜抵抗	
R1104	HL006100	R. MTL. OXD	1K Ω 1/2W		酸化金属被膜抵抗	
R1105	HV755100	R. CAR. FP	100 Ω 1/4W		不燃化カーボン抵抗	01
R1106	HL006100	R. MTL. OXD	1K Ω 1/2W		酸化金属被膜抵抗	
R1107	HV755100	R. CAR. FP	100 Ω 1/4W		不燃化カーボン抵抗	01
R1108	HL006100	R. MTL. OXD	1K Ω 1/2W		酸化金属被膜抵抗	
R1109	HV755100	R. CAR. FP	100 Ω 1/4W		不燃化カーボン抵抗	01
R1110	HL006100	R. MTL. OXD	1K Ω 1/2W		酸化金属被膜抵抗	
R1111	HV755100	R. CAR. FP	100 Ω 1/4W		不燃化カーボン抵抗	01
R1112	HL006100	R. MTL. OXD	1K Ω 1/2W		酸化金属被膜抵抗	
R1113	HV755100	R. CAR. FP	100 Ω 1/4W		不燃化カーボン抵抗	01
R1114	HL006100	R. MTL. OXD	1K Ω 1/2W		酸化金属被膜抵抗	
R1115	HV755100	R. CAR. FP	100 Ω 1/4W		不燃化カーボン抵抗	01
⚠ R1116	V8072100	R. MTL. OXD	5.6K Ω 1W		酸化金属被膜抵抗	
R1117	HV755560	R. CAR. FP	560 Ω 1/4W		不燃化カーボン抵抗	01
⚠ R1119-1130	HV755100	R. CAR. FP	100 Ω 1/4W		不燃化カーボン抵抗	01
R1131	HV756470	R. CAR. FP	4.7K Ω 1/4W		不燃化カーボン抵抗	01
R1132	V8072000	R. MTL. OXD	4.7K Ω 1W		酸化金属被膜抵抗	
⚠ R1133-1144	HV753470	R. CAR. FP	4.7 Ω 1/4W		不燃化カーボン抵抗	01
R1145	HV754100	R. CAR. FP	10 Ω 1/4W		不燃化カーボン抵抗	01
R1147-1148	HV754100	R. CAR. FP	10 Ω 1/4W		不燃化カーボン抵抗	01
⚠ R1149-1150	V3873200	R. CEMENT	0.22 Ω 3W		セメント抵抗	02
* ⚠ R1151-1153	WG471300	R. WW	0.22 Ω+0.22 Ω		セメント抵抗	
⚠ R1154	V3873200	R. CEMENT	0.22 Ω 3W		セメント抵抗	02
⚠ R1173-1178	V8070300	R. MTL. FLM	10 Ω 1W		金属被膜抵抗	
R1202-1203	V8070200	R. MTL. FLM	4.7 Ω 1W		金属被膜抵抗	
⚠ R1214	HV755100	R. CAR. FP	100 Ω 1/4W		不燃化カーボン抵抗	01
R1215	HV756100	R. CAR. FP	1K Ω 1/4W		不燃化カーボン抵抗	01
R1222	HV755180	R. CAR. FP	180 Ω 1/4W		不燃化カーボン抵抗	01
R1230	HV755180	R. CAR. FP	180 Ω 1/4W		不燃化カーボン抵抗	01
R1232	HV753470	R. CAR. FP	4.7 Ω 1/4W		不燃化カーボン抵抗	01
R1237	HV755180	R. CAR. FP	180 Ω 1/4W		不燃化カーボン抵抗	01
R1238	HV753470	R. CAR. FP	4.7 Ω 1/4W		不燃化カーボン抵抗	01
R1240	HV755180	R. CAR. FP	180 Ω 1/4W		不燃化カーボン抵抗	01
⚠ R1243-1244	HV753100	R. CAR. FP	1 Ω 1/4W		不燃化カーボン抵抗	01
R1245	HV753470	R. CAR. FP	4.7 Ω 1/4W		不燃化カーボン抵抗	01
R1246	HV755180	R. CAR. FP	180 Ω 1/4W		不燃化カーボン抵抗	01
R1249	HV753470	R. CAR. FP	4.7 Ω 1/4W		不燃化カーボン抵抗	01
R1252	HV753470	R. CAR. FP	4.7 Ω 1/4W		不燃化カーボン抵抗	01
R1253	HV755180	R. CAR. FP	180 Ω 1/4W		不燃化カーボン抵抗	01
R1254	HV753470	R. CAR. FP	4.7 Ω 1/4W		不燃化カーボン抵抗	01
RY100-102	WA544800	RELAY	DC G5PA-28		リレー 2 4 V	04
RY103	V5178900	RELAY	DC DQ24D1-OS(M)		リレー 2 4 V	
RY104	WA544800	RELAY	DC G5PA-28		リレー 2 4 V	04
RY105	WE648700	RELAY	DC DH24D2-0-Q		リレー 2 4 V	06
ST100	V4040500	SCR. TERM	M3		スクリュー/ターミナル	01
TE100	WC631900	TERM. SP	LTS0810-1017FM	JUCRTA	スピーカーターミナル	06
* TE100	WD477500	TERM. SP	LTS0810-1015FM	KGEL	スピーカーターミナル	
TE101	WC631900	TERM. SP	LTS0810-1017FM	JUCRTA	スピーカーターミナル	06
* TE101	WD477500	TERM. SP	LTS0810-1015FM	KGEL	スピーカーターミナル	
	WE774200	SCR. BND. HD	3x10 MFZN2W3		バインドBタイトネジ	01

* New Parts * 新規部品

RX-V559/DSP-AX559

HTR-5950

P.C.B. VIDEO

Ref. No.	Part No.	Description	Remarks	Markets	部 品 名	Rank
	WG769500	P.C.B.	VIDEO		P C B V I D E O	
	WG769600	P.C.B.	VIDEO		P C B V I D E O	
CB401	VB389900	CN.BS.PIN	3P		ベースピン	01
CB402	VN520900	CN.BS.PIN	52045 26P TE		F F C コネクター	02
C4001-4002	UR837470	C. EL	47uF 16V		ケミコン	01
C4003	UR837100	C. EL	10uF 16V		ケミコン	01
C4004-4005	UR818100	C. EL	100uF 6.3V		ケミコン	01
C4006	UR837100	C. EL	10uF 16V		ケミコン	01
C4007-4010	UR837470	C. EL	47uF 16V		ケミコン	01
C4011	UR837100	C. EL	10uF 16V		ケミコン	01
C4012	UR837470	C. EL	47uF 16V		ケミコン	01
C4013	UR818100	C. EL	100uF 6.3V		ケミコン	01
C4014	UR818470	C. EL	470uF 6.3V		ケミコン	01
C4015	UR866100	C. EL	1uF 50V		ケミコン	01
C4016	UR837100	C. EL	10uF 16V		ケミコン	01
C4017	UR818100	C. EL	100uF 6.3V		ケミコン	01
C4021	UR866470	C. EL	4.7uF 50V		ケミコン	01
C4023	UR818100	C. EL	100uF 6.3V		ケミコン	01
C4024	UR818330	C. EL	330uF 6.3V		ケミコン	01
C4025	UR818100	C. EL	100uF 6.3V		ケミコン	01
C4027-4029	UR818100	C. EL	100uF 6.3V		ケミコン	01
C4031-4033	UR818100	C. EL	100uF 6.3V		ケミコン	01
C4101-4102	US062100	C. CE. CHP	100pF 50V B		チップセラコン	01
C4103	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C4104-4107	US062100	C. CE. CHP	100pF 50V B		チップセラコン	01
C4108-4126	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C4127	US064100	C. CE. CHP	0.01uF 50V B		チップセラコン	01
C4128	US062120	C. CE. CHP	120pF 50V B		チップセラコン	01
C4129	US062220	C. CE. CHP	220pF 50V B		チップセラコン	01
C4130-4135	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C4136	US060500	C. CE. CHP	5pF 50V B	JUCRK	チップセラコン	01
C4136	US060300	C. CE. CHP	3pF 50V B	TAGEL	チップセラコン	01
C4137	US060800	C. CE. CHP	8pF 50V B	JUCRK	チップセラコン	01
C4137	US060300	C. CE. CHP	3pF 50V B	TAGEL	チップセラコン	01
C4138	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C4139	US060800	C. CE. CHP	8pF 50V B	JUCRK	チップセラコン	01
C4139	US060300	C. CE. CHP	3pF 50V B	TAGEL	チップセラコン	01
C4140	US062470	C. CE. CHP	470pF 50V B		チップセラコン	01
C4141	US061240	C. CE. CHP	24pF 50V B		チップセラコン	01
C4142	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C4143	US061240	C. CE. CHP	24pF 50V B		チップセラコン	01
C4144	US063120	C. CE. CHP	1200pF 50V B		チップセラコン	01
C4145	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C4149-4150	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C4157-4163	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C4164	WG251600	C. CE. CHP	4.7uF 6.3V		チップセラ	01
C4165	US064100	C. CE. CHP	0.01uF 50V B		チップセラコン	01
C4166-4168	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C4169-4172	US064100	C. CE. CHP	0.01uF 50V B		チップセラコン	01
C4173	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C4174	US064100	C. CE. CHP	0.01uF 50V B		チップセラコン	01
C4175	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C4176	US034820	C. CE. CHP	0.082uF 16V K		チップセラコン	01
C4177	US064100	C. CE. CHP	0.01uF 50V B		チップセラコン	01
C4178-4179	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C4180-4181	US064100	C. CE. CHP	0.01uF 50V B		チップセラコン	01
C4182	WG251600	C. CE. CHP	4.7uF 6.3V		チップセラ	01
C4183	US064100	C. CE. CHP	0.01uF 50V B		チップセラコン	01
C4184-4185	US060900	C. CE. CHP	9pF 50V B		チップセラコン	01
C4186-4190	US064100	C. CE. CHP	0.01uF 50V B		チップセラコン	01

* New Parts * 新規部品

P.C.B. VIDEO

Ref. No.	Part No.	Description	Remarks	Markets	部 品 名	Rank
C4193-4194	UR818100	C. EL	100uF 6.3V		ケミコン	01
C4195-4197	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
C4198-4200	UR837100	C. EL	10uF 16V		ケミコン	01
C4201-4202	US062100	C. CE. CHP	100pF 50V B		チップセラコン	01
C4203-4205	US135100	C. CE. CHP	0.1uF 16V		チップセラコン	01
D4001-4007	VT332900	DIODE	1SS355		ダイオード	01
D4009	VT332900	DIODE	1SS355		ダイオード	01
D4011	VT332900	DIODE	1SS355		ダイオード	01
IC401	X6742A00	IC	LA73050-TLM-E		アンプ I C	04
IC402-404	XY549A00	IC	TC74HC4051AFEL		ロジック I C	
IC405	XY879A00	IC	TC74HC4053AF (EL)		ロジック I C	
IC406	XZ509A00	IC	TC74VHC04FT INVER		ロジック I C	01
IC407	XY879A00	IC	TC74HC4053AF (EL)		ロジック I C	
IC408	X5597A00	IC	LC74781JM-9798		I C アナログ	07
IC409	X6869A00	IC	NJM2885DL1-33		電源 I C	03
IC410	X6868A00	IC	NJM2885DL1-18		電源 I C	03
IC411	X7325A00	IC	ADV7180BSTZ		I C	
IC412	X6671A00	IC	ADV7172KSTZ		I C	
IC413	X6741A00	IC	LA7106M-TLM-E		アンプ I C	
JK401-402	V9273500	CN. DIN	2P YKF51-5605		D I N コネクタ	
JK403	VS867300	CN. DIN	4P YKF51-5501		D I N コネクタ	03
PJ401	V7189800	JACK. PIN	1P		ピンジャック	01
PJ402-403	V7190000	JACK. PIN	2P		ピンジャック	
PN401-402	V9637500	PIN	L=70 #18		スタイルピン	
Q4001	VV556400	TR	2SC2412K Q, R, S		トランジスタ	01
Q4002	WF550000	TR	2SC3837K T146 N, P		トランジスタ	01
Q4003	VV556500	TR	2SA1037K Q, R, S		トランジスタ	01
Q4004	VV556400	TR	2SC2412K Q, R, S		トランジスタ	01
Q4005	WF549900	TR	2SC3906K T146 R, S		トランジスタ	01
Q4006	VV556400	TR	2SC2412K Q, R, S		トランジスタ	01
Q4010-4013	WG261200	FET	2SK2158-T2B-A		F E T	01
R4022	HV753100	R. CAR. FP	1 Ω 1/4W		不燃化カーボン抵抗	01
R4035	HV753220	R. CAR. FP	2.2 Ω 1/4W		不燃化カーボン抵抗	01
R4038	HV753100	R. CAR. FP	1 Ω 1/4W		不燃化カーボン抵抗	01
R4040	HV757100	R. CAR. FP	10K Ω 1/4W		不燃化カーボン抵抗	01
R4041	HV753220	R. CAR. FP	2.2 Ω 1/4W		不燃化カーボン抵抗	01
R4046	HV753100	R. CAR. FP	1 Ω 1/4W		不燃化カーボン抵抗	01
R4048	HV755470	R. CAR. FP	470 Ω 1/4W		不燃化カーボン抵抗	01
R4052-4053	HV755470	R. CAR. FP	470 Ω 1/4W		不燃化カーボン抵抗	01
R4067	HV755470	R. CAR. FP	470 Ω 1/4W		不燃化カーボン抵抗	01
R4072	V8070000	R. MTL. FLM	1 Ω 1W		金属被膜抵抗	01
R4078	V8070000	R. MTL. FLM	1 Ω 1W		金属被膜抵抗	01
XL401	WD280800	RSNR. CRY	14.31818M SMD-49	JUCRK	水晶振動子	
XL401	WD280900	RSNR. CRY	17.734475M SMD-49	TAGEL	水晶振動子	
XL402	VZ772700	RSNR. CRY	28.63636MHz		水晶振動子	03

* New Parts * 新規部品

HTR-5950

RX-V559/DSP-AX559


Chip Resistors

Ref. No.	Part No.	Description	Remarks	Markets	部 品 名	Rank
	R.CHP	0 Ω	1/16W J		チップ抵抗	
	R.CHP	2.2 Ω	1/16W J		チップ抵抗	
	R.CHP	10 Ω	1/16W J		チップ抵抗	
	R.CHP	75 Ω	1/16W J		チップ抵抗	
	R.CHP	100 Ω	1/16W J		チップ抵抗	
	R.CHP	220 Ω	1/16W J		チップ抵抗	
	R.CHP	270 Ω	1/16W J		チップ抵抗	
	R.CHP	330 Ω	1/16W J		チップ抵抗	
	R.CHP	470 Ω	1/16W J		チップ抵抗	
	R.CHP	1k Ω	1/16W J		チップ抵抗	
	R.CHP	3.3k Ω	1/16W J		チップ抵抗	
	R.CHP	4.7k Ω	1/16W J		チップ抵抗	
	R.CHP	10k Ω	1/16W J		チップ抵抗	
	R.CHP	15k Ω	1/16W J		チップ抵抗	
	R.CHP	22k Ω	1/16W J		チップ抵抗	
	R.CHP	33k Ω	1/16W J		チップ抵抗	
	R.CHP	47k Ω	1/16W J		チップ抵抗	
	R.CHP	100k Ω	1/16W J		チップ抵抗	
	R.CHP	470k Ω	1/16W J		チップ抵抗	
	R.CHP	680k Ω	1/16W J		チップ抵抗	
	R.CHP	820 Ω	1/16W D		チップ金属被膜抵抗	
	R.MTL.CHP	4.7k Ω	1/16W D		チップ金属被膜抵抗	
	R.MTL.CHP	5.6k Ω	1/16W D		チップ金属被膜抵抗	
	R.MTL.CHP	47k Ω	1/16W D		チップ金属被膜抵抗	

- The chip resistor is not supplied as a replacement part.
- チップ抵抗はピーズ部品として供給しません。
- * When a chip resistor is necessary, use the following part.
- * チップ抵抗が必要な場合は、下記の部品をご利用ください。
- AA60720: CHIP RESISTOR SAMPLE BOOK
- AA60720: CHIP RESISTOR SAMPLE BOOK

Carbon Resistors

Value	1/4W Type Part No.	1/6W Type Part No.	Value	1/4W Type Part No.	1/6W Type Part No.
1.0 Ω	HJ35 3100	HF85 3100	10 kΩ	HF45 7100	HF45 7100
1.8 Ω	HJ35 3180	* 11 kΩ	11 kΩ	HF45 7110	HF45 7110
2.2 Ω	HJ35 3220	HF85 3220	12 kΩ	HJ35 7120	HF85 7120
3.3 Ω	HJ35 3330	HF85 3330	13 kΩ	HF45 7130	HF45 7130
4.7 Ω	HJ35 3470	HF85 3470	15 kΩ	HF45 7150	HF45 7150
5.6 Ω	HJ35 3560	HF85 3560	18 kΩ	HF45 7180	HF45 7180
10 Ω	HF45 4100	HF45 4100	22 kΩ	HF45 7220	HF45 7220
15 Ω	HJ35 4150	HF85 4150	24 kΩ	HF45 7240	HF45 7240
22 Ω	HF45 4220	HF45 4220	27 kΩ	HJ35 7270	HF85 7270
27 Ω	HJ35 4270	HF85 4270	30 kΩ	HF45 7300	HF45 7300
33 Ω	HF45 4330	HF45 4330	33 kΩ	HF45 7330	HF45 7330
39 Ω	HJ35 4390	HF85 4390	36 kΩ	HF45 7360	HF45 7360
47 Ω	HF45 4470	HF45 4470	39 kΩ	HF45 7390	HF45 7390
56 Ω	HF45 4560	HF45 4560	47 kΩ	HF45 7470	HF45 7470
68 Ω	HF45 4680	HF45 4680	51 kΩ	HF45 7510	HF45 7510
75 Ω	HF45 4750	HF45 4750	56 kΩ	HF45 7560	HF45 7560
82 Ω	HF45 4820	HF45 4820	62 kΩ	HF45 7620	HF45 7620
91 Ω	HF45 4910	HF45 4910	68 kΩ	HF45 7680	HF45 7680
100 Ω	HF45 5100	HF45 5100	82 kΩ	HF45 7820	HF45 7820
110 Ω	HJ35 5110	HF85 5110	91 kΩ	HF45 7910	HF45 7910
120 Ω	HF45 5120	HF45 5120	100 kΩ	HF45 8100	HF45 8100
150 Ω	HF45 5150	HF45 5150	110 kΩ	HF45 8110	HF45 8110
160 Ω	HJ35 5160	* 120 kΩ	120 kΩ	HF45 8120	HF45 8120
180 Ω	HF45 5180	HF45 5180	150 kΩ	HF45 8150	HF45 8150
200 Ω	HF45 5200	HF45 5200	180 kΩ	HF45 8180	HF45 8180
220 Ω	HF45 5220	HF45 5220	220 kΩ	HJ35 8220	HF85 8220
270 Ω	HF45 5270	HF45 5270	270 kΩ	HF45 8270	HF45 8270
330 Ω	HF45 5330	HF45 5330	300 kΩ	HF45 8300	HF45 8300
390 Ω	HF45 5390	HF45 5390	330 kΩ	HF45 8330	HF45 8330
430 Ω	HF45 5430	HF45 5430	390 kΩ	HJ35 8390	HF85 8390
470 Ω	HF45 5470	HF45 5470	470 kΩ	HF45 8470	HF45 8470
510 Ω	HF45 5510	HF45 5510	560 kΩ	HJ35 8560	HF85 8560
560 Ω	HF45 5560	HF45 5560	680 kΩ	HJ35 8680	HF85 8680
680 Ω	HF45 5680	HF45 5680	820 kΩ	HJ35 8820	HF85 8820
820 Ω	HF45 5820	HF45 5820	1.0 MΩ	HF45 9100	HF45 9100
910 Ω	HF45 5910	HF45 5910	1.2 MΩ	HJ35 9120	*
1.0 kΩ	HF45 6100	HF45 6100	1.5 MΩ	HJ35 9150	HF85 9150
1.2 kΩ	HF45 6120	HF45 6120	1.8 MΩ	HJ35 9180	HF85 9180
1.5 kΩ	HF45 6150	HF45 6150	2.2 MΩ	HJ35 9220	HF85 9220
1.8 kΩ	HF45 6180	HF45 6180	3.3 MΩ	HJ35 9330	HF85 9330
2.0 kΩ	HJ35 6200	HF85 6200	3.9 MΩ	HJ35 9390	*
2.2 kΩ	HF45 6220	HF45 6220	4.7 MΩ	HJ35 9470	HF85 9470
2.4 kΩ	HJ35 6240	HF85 6240			
2.7 kΩ	HF45 6270	HF45 6270			
3.0 kΩ	HF45 6300	HF45 6300			
3.3 kΩ	HF45 6330	HF45 6330			
3.6 kΩ	HJ35 6360	HF85 6360			
3.9 kΩ	HF45 6390	HF45 6390			
4.7 kΩ	HF45 6470	HF45 6470			
5.1 kΩ	HF45 6510	HF45 6510			
5.6 kΩ	HF45 6560	HF45 6560			
6.8 kΩ	HF45 6680	HF45 6680			
8.2 kΩ	HF45 6820	HF45 6820			
9.1 kΩ	HF45 6910	HF45 6910			




* : Not available

* : New Parts * 新部品

RX-V559/HTR-5950/DSP-AX559

1 • OVERALL ASS'Y RX-V559/DSP-AX559



● OVERALL ASS'Y RX-V559/DSP-AX559

Ref. No.	Part No.	Description	Remarks	Markets	部 品 名	Rank
5	W6681000	P.C.B. ASS'Y	DSP	J	P.C.B. DSP	
* 5	W6681100	P.C.B. ASS'Y	DSP	UC	P.C.B. DSP	
* 5	W6681200	P.C.B. ASS'Y	DSP	R	P.C.B. DSP	
* 5	W6681300	P.C.B. ASS'Y	DSP	T	P.C.B. DSP	
* 5	W6681400	P.C.B. ASS'Y	DSP	K	P.C.B. DSP	
* 5	W6681500	P.C.B. ASS'Y	DSP	A	P.C.B. DSP	
* 5	W6681700	P.C.B. ASS'Y	DSP	GE	P.C.B. DSP	
* 5	W6681800	P.C.B. ASS'Y	DSP	L	P.C.B. DSP	
* 6	W6686000	P.C.B. ASS'Y	FUNCTION	J	P.C.B. ファンクション	
* 6	W6686100	P.C.B. ASS'Y	FUNCTION	UCTKA	P.C.B. ファンクション	
* 6	W6686200	P.C.B. ASS'Y	FUNCTION	R	P.C.B. ファンクション	
* 6	W6686400	P.C.B. ASS'Y	FUNCTION	GE	P.C.B. ファンクション	
* 6	W6686500	P.C.B. ASS'Y	FUNCTION	L	P.C.B. ファンクション	
* 7	W6769900	P.C.B. ASS'Y	OPERATION	J	P.C.B. オペレーション	
* 7	W6770000	P.C.B. ASS'Y	OPERATION	UC	P.C.B. オペレーション	
* 7	W6770100	P.C.B. ASS'Y	OPERATION	R	P.C.B. オペレーション	
* 7	W6770200	P.C.B. ASS'Y	OPERATION	TK	P.C.B. オペレーション	
* 7	W6770300	P.C.B. ASS'Y	OPERATION	A	P.C.B. オペレーション	
* 7	W6770500	P.C.B. ASS'Y	OPERATION	GE	P.C.B. オペレーション	
* 7	W6770600	P.C.B. ASS'Y	OPERATION	L	P.C.B. オペレーション	
* 8	W6769500	P.C.B. ASS'Y	VIDEO	JUCKR	P.C.B. ビデオ	
* 8	W6769600	P.C.B. ASS'Y	VIDEO	TABEL	P.C.B. ビデオ	
12	V6782200	AM/FM TUNER	TFCE1J117A	J	AM/FMチューナー	
12	V6782300	AM/FM TUNER	TFCE1U115A	UCRTL	AM/FMチューナー	
12	V6782400	AM/FM TUNER	TFCE1E317A	KAGE	AM/FMチューナー	
* 15	X7499A00	POWER TRANSFORMER		J	電源トランス	
* 15	X7500A00	POWER TRANSFORMER		UC	電源トランス	
* 15	X7501A00	POWER TRANSFORMER		RL	電源トランス	
* 15	X7502A00	POWER TRANSFORMER		TK	電源トランス	
* 15	X7503A00	POWER TRANSFORMER		A	電源トランス	
* 15	X7504A00	POWER TRANSFORMER		GE	電源トランス	
* 16	Wf723000	POWER CABLE	2m	J	電源コード	
* 16	V2727500	POWER CABLE	2m	UC	電源コード	
* 16	Wc992700	POWER CABLE	2m	R	電源コード	
* 16	Wb120600	POWER CABLE	2m	T	電源コード	
* 16	Wc753000	POWER CABLE	2m	K	電源コード	
* 16	Wc743700	POWER CABLE	2m	A	電源コード	
* 16	Vb363600	POWER CABLE	2m	GE	電源コード	
17	V2438700	CORD STOPPER	1P1		コードストッパー	
25	Mf125200	FLEX IBLE FLAT CABLE	2P 200mm P=1.25		カード電線 C&C	
26	Mf115140	FLEX IBLE FLAT CABLE	1P 140mm P=1.25		カード電線 C&C	
27	Mf129070	FLEX IBLE FLAT CABLE	2P 70mm P=1.25		カード電線 C&C	
28	Mf120070	FLEX IBLE FLAT CABLE	2P 70mm P=1.25		カード電線 C&C	
29	Mf126100	FLEX IBLE FLAT CABLE	2P 100mm P=1.25		カード電線 C&C	
50	VU590000	BINDING TIE	C8TD00101B		インジエロックタイ	
101	W6364700	TOP COVER		GD	トップカバー	
101	W6364600	TOP COVER		BL	トップカバー	
101	W6364800	TOP COVER		TI	トップカバー	
103	W6367600	REAR PANEL		J	リアパネル	
103	W6366800	REAR PANEL		UC	リアパネル	
103	W6366900	REAR PANEL		R	リアパネル	
103	W6367000	REAR PANEL		T	リアパネル	
103	W6367100	REAR PANEL		K	リアパネル	
103	W6367200	REAR PANEL		A	リアパネル	
103	W6367400	REAR PANEL		GE	リアパネル	
103	W6367500	REAR PANEL		L	リアパネル	
105	W6975100	PLATE SIDE			プレートサイド	
105	W6975000	PLATE SIDE			プレートサイド	
105	W6975200	PLATE SIDE			プレートサイド	


* New Parts * 新規部品

Ref. No.	Part No.	Description	Remarks	Markets	部 品 名	Rank
120	V0042500	LEG	LEG		レッグ	
* 120	V5025000	LEG	D60xH21	BL, TI	レッグ	
* 121	W6375500	KNOB D50	VOLUME	GD	ノブD50	
* 121	W6375400	KNOB D50	VOLUME	BL	ノブD50	
* 121	W6375600	KNOB D50	VOLUME	TI	ノブD50	
* 122	W6375800	KNOB D21.5	PROGRAM, INPUT	GD	ノブD21.5	
* 122	W6375700	KNOB D21.5	PROGRAM, INPUT	BL	ノブD21.5	
* 122	W6375900	KNOB D21.5	PROGRAM, INPUT	TI	ノブD21.5	
* 135	W6918400	BARRIER FFC	3/30/60		バリアー/FFC	
137	W6742300	DAMPER	3/30/60		ダンパー	
139	W6379000	DAMPER		K	ダンパー	
150	V0466300	COVER AC OUTLETS			カバー/ACアウトレット	
155	V0368600	PUSH RIVET	P3555-B		プッシュリベット	
* 156	Wb137300	DAMPER	1/35/55	RL	ダンパー 1/35/55	
160	Wc774100	BIND HEAD B-TIGHT SCREW	3x8		ボンドヘッドBタイトネジ	
163	Wc774300	BIND HEAD B-TIGHT SCREW	3x8		ボンドヘッドBタイトネジ	
167	Wf002600	PW HEAD B-TIGHT SCREW	3x8		PWヘッドBタイトネジ	
* 168	Wf010900	SCREW 1C	3x20		スクリュー 1C	
170	Wc774700	BIND HEAD S-TIGHT SCREW	4x10		ボンドヘッドSタイトネジ	
171	V0069600	BIND HEAD S-TIGHT SCREW	4x8-10	GD, TI	PWヘッドSタイトネジ	
171	Vb313200	PW HEAD S-TIGHT SCREW	4x8-10	BL	PWヘッドSタイトネジ	
172	Wc200400	DISH HEAD B-TIGHT SCREW	3x6	GD, TI	DISH Bタイトネジ	
172	Wc200500	DISH HEAD B-TIGHT SCREW	3x6	BL	DISH Bタイトネジ	
173	Wc774800	BIND HEAD P-TIGHT SCREW	3x8		ボンドPタイトネジ	
200	W6646400	ACCESSORIES	RAV323	JRTKABEL	付属品	
* 200	W6646300	REMOTE CONTROL	RAV322	UC	リモコン	
* 200-1	AAx76600	BATTERY COVER			電池蓋	
202	V6267000	INDOOR FM ANTENNA	1.4m 1pc	JUCRTL	F M簡易アンテナ	
202	V0147100	INDOOR FM ANTENNA	1.4m 1pc	KAGE	F M簡易アンテナ	
203	Vb248500	AM LOOP ANTENNA	1.0m 1pc		AMループアンテナ	
		BATTERY	SUM-3N 2pcs		乾電池 2PCS	

* New Parts * 新規部品

RX-V559/HTR-5950/DSP-AX559

• OVERALL ASS'Y HTR-5950



OVERALL ASS'Y HTR-5950

Ref. No.	Part No.	Description	Remarks	Markets
5	WG682000	P.C.B. ASS'Y	DSP	UC
* 5	WG656300	P.C.B. ASS'Y	DSP	T
* 5	WG682100	P.C.B. ASS'Y	DSP	A
* 6	WG689100	P.C.B. ASS'Y	FUNCTION	
* 7	WG671400	P.C.B. ASS'Y	OPERATION	UC
* 7	WG6956400	P.C.B. ASS'Y	OPERATION	T
* 7	WG771500	P.C.B. ASS'Y	OPERATION	A
* 8	WG769500	P.C.B. ASS'Y	VIDEO	UC
* 8	WG769600	P.C.B. ASS'Y	VIDEO	TA
12	V6782300	AM/FM TUNER	TFCEU115A	UCT
12	V6782400	AM/FM TUNER	TFCE1E317A	A
* 15	X7500A00	POWER TRANSFORMER		UC
* 15	X7502A00	POWER TRANSFORMER		T
* 15	X7503A00	POWER TRANSFORMER		A
* 16	V2727500	POWER CABLE	2m	UC
* 16	WB120600	POWER CABLE	2m	T
* 16	WC743700	POWER CABLE	2m	A
17	V2438700	CORD STOPPER	10P1	
25	MF125200	FLEXIBLE FLAT CABLE	25P 200mm P=1.25	
26	MF115140	FLEXIBLE FLAT CABLE	15P 140mm P=1.25	
27	MF129070	FLEXIBLE FLAT CABLE	29P 70mm P=1.25	
28	MF120070	FLEXIBLE FLAT CABLE	20P 70mm P=1.25	
29	MF126100	FLEXIBLE FLAT CABLE	26P 100mm P=1.25	
50	VU590000	BINDING TIE	CBTD001B	
101	WG437900	TOP COVER		GD
* 101	WG437800	TOP COVER		BL
* 101	WG438100	TOP COVER		SI
103	WG438200	REAR PANEL		
103	WG438300	REAR PANEL		
103	WG438500	REAR PANEL		
103	WG438200	REAR PANEL		
120	V0042500	LEG		GD
120	VV544300	LEG	D60xH21	BL
120	VS025000	LEG	D60xH21	SI
121	WG442700	KN08 D48	VOLUME	GD
121	WG442600	KN08 D48	VOLUME	BL
121	WG442900	KN08 D48	VOLUME	SI
122	WG443300	KN08 D23	INPUT	GD
122	WG443200	KN08 D23	INPUT	BL
122	WG443500	KN08 D23	INPUT	SI
135	WG918400	BARRIER FFC		
137	V6742300	DAMPER	3/30/60	
139	WC879000	DAMPER		
155	V0368600	PUSH RIVET	P3555-B	
160	WE774100	BIND HEAD BONDING B-T. SCREW	3x8	MFZN2B3
163	WE774300	BIND HEAD B-TIGHT SCREW	3x8	MFZN2W3
167	WFO02600	PW HEAD B-TIGHT SCREW	3x8	MFZN2W3
168	WH010900	SCREW IC	3x20	MFZN2W3
170	WE774700	BIND HEAD S-TIGHT SCREW	4x10	MFZN2W3
171	V0069600	PW HEAD S-TIGHT SCREW	4x8-10	MFN133
171	VH313200	PW HEAD S-TIGHT SCREW	4x8-10	MFN13BL
172	WE200400	DISH HEAD B-TIGHT SCREW	3x6	MFN133
172	WE200500	DISH HEAD B-TIGHT SCREW	3x6	MFN13BL
173	WE774800	BIND HEAD P-TIGHT SCREW	3x8	MFZN2W3

※ New Parts

Ref. No.	Part No.	Description	Remarks	Markets
200	WG646300	ACCESSORIES		
* 200	WG646400	REMOTE CONTROL	EUR7661K00	UC
* 200-1	AAAX76600	BATTERY COVER	EUR7661K00	TA
202	V6257000	INDOOR FM ANTENNA	UR76EC6103A	
202	V0147100	INDOOR FM ANTENNA		UCT
203	VR248500	AM LOOP ANTENNA BATTERY		A
		RAV322		
		RAV323		
		1.4m 1pc		
		1.4m 1pc		
		1.0m 1pc		
		SUM-3N 2pcs		

※ New Parts


RX-V559/HTR-5950/DSP-AX559

FRONT PANEL UNIT HTR-5950

FRONT PANEL UNIT HTR-5950

Ref. No.	Part No.	Description	Remarks	Markets
1-2	MF123400	FLEXIBLE FLAT CABLE		
1-4	WG517000	FRONT PANEL ASS'Y	GD	UC
1-4	WG516300	FRONT PANEL ASS'Y	BL	A
1-4	WG445500	FRONT PANEL ASS'Y	SI	
1-4	WG445600	FRONT PANEL ASS'Y	SI	
1-5	WG441300	BUTTON CASE	GD	
1-5	WG441100	BUTTON CASE	BL	
1-5	WG441500	BUTTON CASE	SI	
1-13	WG443600	SHEET WINDOW	GD	
1-13	WG443800	SHEET WINDOW	BL	
1-13	WG443700	SHEET WINDOW	SI	
1-13	WG443600	SHEET WINDOW	SI	
1-25	WE774800	BIND HEAD P-TIGHT SCREW	3x8 MFZN2W3	UC
1-40	V6034200	EMBLEM		A
1-40	V6034100	EMBLEM	GD BL, SI	
7	WG771400	P.C.B. ASS'Y		UC
7	WG956400	P.C.B. ASS'Y	OPERATION	T
7	WG771500	P.C.B. ASS'Y	OPERATION	A

* * * * *



※ New Parts

1 ■ REMOTE CONTROL RAV322: RX-V559 (U, C models), HTR-5950 (U, C models)
RAV323: RX-V559 (R, T, K, A, G, E, L models), HTR-5950 (T, A models), DSP-AX557 (J model)

• SCHEMATIC DIAGRAM

